



## **Model No.:**

**PT24** 

**PT30** 

**PT36** 

**PT48** 

## With 7-Circuit Cold Plate

PT24+7

PT30+7

PT36+7

PT48+7

- 304 Stainless Steel, Welded and Polished Top Assembly, Apron, Ends, and Liner
- Insulated Ice Bin With Factory-Installed Stainless Steel Drain With 1 1/2" Standard Male Pipe Thread (When Provided With Cold Plate, Drain Is 1/2" Standard Female Pipe Thread)
- Legs: Steel Tube and Welded Cross-Brace Construction, With Corrosion-Resistant Hammertone Paint and High-Impact Plastic Adjustable Feet
- Available With Optional Stainless Steel Cover
- Constructed to Meet NSF Specifications





## **Model No.:**

**PT24** 

**PT30** 

**PT36** 

**PT48** 

## With 7-Circuit Cold Plate


PT24+7


PT30+7

PT36+7

PT48+7

					ICE
MODEL NO.	A	В	C	D	CAPACITY
PT24	24"	12"	12"	1 1/2"	139 lbs.
PT30	30"	12"	15"	1 1/2"	176 lbs.
PT36	36"	12"	18"	1 1/2"	220 lbs.
PT48	48"	12"	24"	1 1/2"	265 lbs.
PT24+7	24"	15"	12"	1/2"	139 lbs.
PT30+7	30"	15"	15"	1/2"	176 lbs.
PT36+7	36"	15"	18"	1/2"	220 lbs.
PT48+7	48"	15"	24"	1/2"	265 lbs.





Contact factory or local representative for further information.

Since La Crosse has a policy of continuous product improvement, it reserves the right to change design and specifications without notice.