

Enclosed Tray Trucks

Low Profile - 5" Ledge Spacing

Features

- Low profile design for safe, full view during transport.
- Perimeter bumper protects your furnishings and doors.
- Accepts 14" x 18" (356 x 457 mm) or 15" x 20" (381 x 508 mm) trays.
- Doors conveniently open 270° for easy tray access.
- Designed for rugged acute care foodservice use.
- Easy to clean and sanitize. Simply wipe down or steam clean.
- Removable ledge panels for easy cleaning.



Model 835



Specifications

Unit shall be of welded and riveted type 304 stainless steel construction and shall accommodate either 14" x 18" or 15" x 20" meal trays. Back, top and sides shall be of 18-gauge stainless steel. Floor/base shall be of 18-gauge stainless steel and shall have drain(s) to facilitate cleaning. Tray compartment(s) shall feature louvered vents on side and back panels. Angle style tray ledges shall be of 16-gauge stainless steel welded to 14-gauge stainless steel upright frames with 5" spacing. Ledge frame assemblies shall be adjustable to accommodate 14" x 18" or 15" x 20" trays and shall be removable to facilitate cleaning. Door(s) shall be of double pan construction, with 1" rigid fiberglass insulation for sound deadening and shall have a stainless steel flush-mount paddle latch. Door(s) shall be mounted on heavy-duty stainless steel lift-off hinges which allow 270° door swing. Unit shall feature non-marking full-perimeter bumper and stainless steel push handle. Casters shall be extra-load 8" diameter, two fixed and two swivel with brakes, with 2" wide non-marking rounded cushion tread wheels. Unit shall be NSF listed.

Models 831 and 832 only:

Casters shall be extra-load 6" diameter, two fixed and two swivel with brakes, with 2" wide non-marking rounded cushion tread wheels.

Lakeside Manufacturing, Inc.
1977 South Allis Street • Milwaukee, WI 53207-1295 U.S.A.
800-558-8565 • 414-481-3900 • Fax 414-481-9313 • www.eLakeside.com



Enclosed Tray Trucks

Low Profile - 5" Ledge Spacing

Optional Accessories





- 8" diameter casters (Models 831 and 832)
- Extra push handle.
- Identification card holder.
- Decorative laminate door panels.



2 Compartment
Top View



1 Compartment
Top View



AutoCAD drawings available through KCL CADalog

Dimensions

Model	Tray Capacity		Ledge Spacing	# of Interior Compartments	Overall Size			Lake-Glide® Casters		Case Weight		Case Cube	
					W	D	H	Type	Dia.	lb.	(kg.)	ft. ³	(m ³)
831	18 ea.	14" x 18" (356 x 457) or 15" x 20" (381 x 508)	5" (127)	1	36-3/4" (908)	26-1/8" (664)	56" (1422)	2 swivel, 2 fixed	6"	200	(90.7)	37.6	(1.1)
832	20 ea.	14" x 18" (356 x 457) or 15" x 20" (381 x 508)	5" (127)	1	36-3/4" (908)	26-1/8" (664)	61" (1549)	2 swivel, 2 fixed	6"	220	(99.8)	40.8	(1.2)
835	24 ea.	14" x 18" (356 x 457) or 15" x 20" (381 x 508)	5" (127)	2	51-1/8" (1299)	34-1/8" (867)	41" (1041)	2 swivel, 2 fixed	8"	250	(113.4)	50.9	(1.4)
836	28 ea.	14" x 18" (356 x 457) or 15" x 20" (381 x 508)	5" (127)	2	51-1/8" (1299)	34-1/8" (867)	46" (1168)	2 swivel, 2 fixed	8"	260	(117.9)	57.8	(1.6)
837	32 ea.	14" x 18" (356 x 457) or 15" x 20" (381 x 508)	5" (127)	2	51-1/8" (1299)	34-1/8" (867)	51" (1295)	2 swivel, 2 fixed	8"	270	(122.5)	63.6	(1.8)

Measurements in () denote metric millimeters, unless otherwise specified.

AIA #

Spec. #



Lakeside Manufacturing, Inc.

1977 South Allis Street • Milwaukee, WI 53207-1295 U.S.A.
800-558-8565 • 414-481-3900 • Fax 414-481-9313 • www.eLakeside.com