

Mobile Self-Leveling Cabinets

Adjust-a-Fit® Adjustable Diameter - Unheated



Model 925

Adjustable Diameter And Dispensing Height Adjustments Without Tools

- Four tube sizes, each with a 3-1/4" diameter adjustment range.
- Height adjustment springs detach and attach from inside the dispenser. No need to remove dispenser from mobile unit.
- All-welded stainless steel construction.
- Corner bumpers protect cabinet, furniture and doors.
- Easy-Glide™ design provides quiet, non-stick operation.
- 4" Lake-Glide® casters - all swivel, 2 each with brake.



Specifications

Mobile Cabinet: Mobile cabinets shall be of all-welded stainless steel construction, with 18 gauge top and 20-gauge sides and bottom and shall include bottom perimeter bumper. Cabinet bottom shall have center clean out hole. Casters shall be 4" (102 mm) diameter extra-load swivel (two with locking brake). Unit shall feature a heavy-duty independent undercarriage frame of galvanized steel to which casters shall be mounted. Units shall be NSF listed.

Dispenser Tubes: Dispenser tubes shall be of welded stainless steel construction and shall drop in to mobile cabinet top openings. Dispensers shall hang from cabinet opening by an 18-gauge flange ring and feature three each 22-gauge vertical side supports welded to 20-gauge bottom plate. Self-leveling dish carriage shall be of welded stainless steel construction and shall travel vertically in dispenser tube with three sets of nylon roller guides running in vertical tracks for smooth operation. Carriage shall have 22-gauge removable dish platform. Dispensers shall feature flange mounted perimeter extension springs, which are detachable from the dish carriage to provide proper dish height adjustment without tools. Dispensers shall also feature three stainless steel dish guides running the entire height of the dispenser. Dish guides shall pivot to provide diameter adjustability of 3-1/4" (83 mm) without tools or removing components to accommodate various diameter dishes. Each dispenser shall have a vertical stacking capacity of 25" (635 mm).

LAKESIDE
Ingenuity On Wheels™


Lakeside Manufacturing, Inc.

4900 West Electric Avenue • West Milwaukee, WI 53219 U.S.A.

800-558-8565 • 414-902-6400 • Fax 414-902-6446 • www.eLakeside.com

Mobile Self-Leveling Cabinets

Adjust-a-Fit® Adjustable Diameter - Unheated



Top Views

AutoCAD drawings available through KCL CADalog

Dimensions

Model	Adjusts To Fit Plate Size		Overall Size							lbs.	(kg.)
			W	L	H	(W	L	H)			
2-Stack Models											
905	2-3/4" to 6"	(970 to 152)	17-1/4"	30-5/8"	39-1/8"	(438	778	994)	85	(38.6)	
915	4-1/4" to 7-1/2"	(108 to 191)	17-1/4"	30-5/8"	39-1/8"	(438	778	994)	92	(41.7)	
925	6-1/2" to 9-3/4"	(165 to 248)	17-1/4"	30-5/8"	39-1/8"	(438	778	994)	100	(45.4)	
935	8-3/4" to 12"	(222 to 305)	19-1/2"	35-1/8"	39-1/8"	(495	892	994)	115	(52.2)	
3-Stack Models											
942	2-3/4" to 6"	(970 to 152)	17-1/4"	45"	39-1/8"	(438	1145	994)	112	(50.8)	
952	4-1/4" to 7-1/2"	(108 to 191)	17-1/4"	45"	39-1/8"	(438	1145	994)	120	(54.4)	
962	6-1/2" to 9-3/4"	(165 to 248)	17-1/4"	45"	39-1/8"	(438	1145	994)	132	(59.9)	
972	8-3/4" to 12"	(222 to 305)	19-3/16"	51-13/16"	39-1/8"	(487	1316	994)	152	(69.0)	
4-Stack Models											
908	4-1/4" to 7-1/2"	(108 to 191)	26-1/8"	27-1/4"	39-1/8"	(664	692	994)	127	(57.6)	
918	6-1/2" to 9-3/4"	(165 to 248)	26-1/8"	27-1/4"	39-1/8"	(664	692	994)	131	(59.4)	
928	8-3/4" to 12"	(222 to 305)	30-5/8"	30-5/8"	39-1/8"	(778	778	994)	153	(69.4)	

Measurements in () denote metric millimeters, unless otherwise specified.

OPTIONAL ACCESSORIES

- Stainless steel dispenser tube covers
- Laminate or vinyl decorative exterior finishes
- Full-perimeter bumper
- 208/240 VAC 60Hz (heated models)
- 220 VAC 50 Hz (heated models)



Lakeside Manufacturing, Inc.

4900 West Electric Avenue • West Milwaukee, WI 53219 U.S.A.

800-558-8565 • 414-902-6400 • Fax 414-902-6446 • www.eLakeside.com