

Production Equipment 3300 Series

Freezer Equipment Stands
Stainless Steel Top, Remote



3350-RF shown with options

SPECIFICATIONS:

TOP: Die-formed construction of one-piece 18 GA stainless steel type 304-#4 finish with 1 1/8" high marine edge nosing, ends and back turned up to match front

EXTERIOR: Back and bottom of 20 GA steel with painted enamel finish, Body supported by 14 GA galvanized steel box channels for legs, Ends of 20 GA stainless steel, type 304-#4 finish

INTERIOR: Bottom, Back, and Ends of 22 GA stainless steel type 304-#2B finish, Top of aluminum

INSULATION: Rigid Polyurethane Foam

DRAWER JAMS: One-piece high-impact plastic with concealed magnets on perimeter for positive sealing and jam heaters to prevent gasket freezing

DRAWERS: Exterior of one-piece die-stamped 22 GA stainless steel type 304-#4 finish, Interior of high-impact plastic, Gasket mounted w/ aluminum strips and screws for easy removability and to ensure a proper seal, Drawer frame of combination 20 GA and 16 GA stainless steel and corrosion resistant 1 5/16" rollers w/ ball bearing assembly, Each drawer includes (2) removable 12x20x4 dp polycarbonate pans front to back with (1) stainless steel divider support bar

LEGS: Removable 6" high x 1 5/8" tubing welded to steel plate and fastened to body support channel, Bullet foot has 1 1/8" of adjustment, legs of stainless steel

REFRIGERATION: Remote unit has low temperature balanced system using a hermetically sealed condenser. Unit has forced air evaporator coil with protective coated coil and expansion valve, defrost heater, and timer, System comes assembled w/ a junction box ready for final connection, Recommended temperature to operate between -5 and 0 degrees F

ITEM # _____

PROJECT _____

DATE _____

MODEL	DIM
3350-RF	50"L x 31.5"D
3376-RF	76"L x 31.5"D
3304-RF	104"L x 31.5"D

FEATURES

- Stainless Steel ends
- Condensate Evaporator
- Legs removable in field
- Uniform integration in design, quality, and parts
- Self-closing drawers w/ (2) 12x20x4 dp polycarbonate pans ea.
- Automatic Defrost Timer and evaporator heater provided
- Door jam heaters to prevent gasket freezing

OPTIONS

- Casters in lieu of legs
- (1) Door in place of (2) Drawers
- Adjustable Wire Shelf (per door)
- Cutting boards: 9 1/2" x 1/2" Richlite board w/ s/s brackets
- Full Extension Drawer Slides

Production Equipment 3300-RF

Freezer Equipment Stand
Remote



3350-RF



3376-RF




3304-RF

OPTIONS

(1) Door In place of (2) drawers

9 1/2" x 1/2" Richlite Board
w/ S/S Brackets



STATISTICAL DATA

MODEL	LGTH	DRAWERS PER UNIT	CAPACITY CUBIC FOOT	BTU PER HOUR TD ¹	VOLTS/ CYCLE/ PHASE	TOTAL ² AMPS	RECOM. ³ HP	SHIP WT.
3350-RF	50"	2	3.44	1200 R-404	115v/60/1	1.28	1/4	430#
3376-RF	76"	4	5.68	1200 R-404	115v/60/1	1.28	1/3	560#
3304-RF	104"	6	7.92	1600 R-404	115v/60/1	1.28	1/2	675#

NOTE:

1. Custom Units may require upgraded BTU ratings on evaporator coil and/or condensing unit
2. If optional electric condensate evaporator is required, add .39 AMPS to total
3. Recommended HP up to 25' of refrigeration line (at installers discretion)

MECHANICAL DATA

Production Equipment 3300 Series

- Junction Box 6" AFF hard-wired to coil
- 5/8" OD copper drain for condensate evaporator 6" AFF
- Refrigeration Lines, 1/4" inlet and 3/8" suction 6" AFF
- Defrost Timer 18" AFF, hard-wired to junction box

31 9/16"

6"

SECTION VIEW

