


ITEM NO. \_\_\_\_\_ PROJECT \_\_\_\_\_ LOCATION\_\_\_\_\_ DATE

OTY.



# **BLG-HGP SERIES**

Bottom Mounted Full-Height Swing Glass Door Freezer Merchandisers

# MODELS

□ BLG-23-HGP □ BLG-27-HGP □ BLG-48-HGP □ BLG-74-HGP

BLG-48-HGP

# FEATURES

#### CONSTRUCTION

- Standard interior double row LED lighting
- Standard programmable electronic controller featuring:
  - Audible and visual alarm
- Eliminates room thermostat, defrost termination/fan delay control, defrost timer and digital thermometer or other temperature indicator
- 24 gauge painted textured galvanized steel interior and exterior
- Standard finishes: White interior/white exterior or black exterior/black interior
- Stainless steel floor
- 1<sup>3</sup>/<sub>4</sub>" thick state-of-the-art, foamedin-place "zero ODP" polyurethane insulation provides high R-value
- Adjustable legs for leveling
- Four adjustable heavy-duty epoxycoated cantilever shelves per door
- Merchandiser profile matches other BLG/BMG Plus refrigerator and freezer models

### DOORS

- Full-height doors
- Auto-close, triple pane, heated safety glass doors with heated frames
- 90° hold-open feature
- Contemporary style door frame and handles
- Heavy-duty universal workflow handles
- Easily replaceable snap-in magnetic vinyl door gaskets
- Standard door swing configuration:
- 1-door .....hinged left
  2-door .....left door hinged left,
  right door hinged right
- 3-door ...... left door hinged left,
  - middle door hinged right,
    - right door hinged right
- Maximum visibility with these door sizes:

- BLG-48-HGP &
  - BLG-74-HGP ......25" x 631/2"

#### REFRIGERATION

- Self-contained bottom mount refrigeration system designed for optimum energy efficiency and low noise
- ENERGY STAR qualified, may be eligible for rebate programs
- Top mounted, low profile interior evaporator housing
- Energy-free condensate removal
- Refrigerant: R-404A
- Temperature range: 5° to -15°F (-18° to -26°C)

### WARRANTY

- Standard limited three year parts and labor
- Additional two year coverage on compressor part

### **OPTIONS**

- □ Additional shelving
- □ Flat bottom shelf with legs
- Bottom baskets
- Casters





# **BLG-HGP SERIES** BOTTOM MOUNTED FULL-HEIGHT SWING GLASS DOOR FREEZER MERCHANDISERS


# **TECHNICAL SPECIFICATIONS**

	<b>DIMENSIONS (in.)</b>			DIMENSIONS (mm)					UNIT	NO. OF	NO. OF		CAP.	SHIP WT.
MODEL	L	D*	Н	L	D*	Н	VOLTS	AMPS	H.P.	DOORS	SHELVES	SHELF SIZE (in.)	CU. FT.	(LB/KG)
BLG-23-HGP	27	30	79	686	762	2007	115	7.5	3/4	1	4	$22^{1/2}$ L x $21^{1/2}$ D	22.1	365/166
BLG-27-HGP	30	30	79	762	762	2007	115	7.5	3/4	1	4	$25^{1/2}$ L x $21^{1/2}$ D	25.0	380/173
BLG-48-HGP	52	30	79	1321	762	2007	115	12.3	1	2	8	23 <sup>1</sup> / <sub>2</sub> L x 21 <sup>1</sup> / <sub>2</sub> D	45.7	575/261
BLG-74-HGP	78	30	79	1981	762	2007	115/ 208-230**	12.8	11/4	3	12	23 <sup>1</sup> / <sub>2</sub> L x 21 <sup>1</sup> / <sub>2</sub> D (outer doors), 25 <sup>1</sup> / <sub>2</sub> L x 21 <sup>1</sup> / <sub>2</sub> D (middle door)	70.2	770/350

\*Does not include door handle. \*\*208-230/60/1 also requires neutral and safety ground wire.







# PLAN VIEW

## LISTINGS



- Listed under NSF-7 for the storage and/or display of packaged food
- Meets 2012 Federal DOE Requirements
- Meets Canadian energy efficiency regulations

## **BID SPECIFICATIONS**

Item no. BLG-\_\_\_\_-HGP. Provide \_\_\_\_\_ Bottom Mounted Full-Height Swing Glass Door Freezer Merchandiser(s), Master-Bilt model no. BLG-\_\_\_\_-HGP.

Merchandiser will be constructed of 24 gauge painted textured galvanized steel interior and exterior. Standard equipment will include interior LED lighting, programmable electronic controller system, and four

## SIDE VIEW

### HOOKUP

All models except BLG-74-HGP via plug in, 10 foot long, flexible three wire 14/3 cord with molded plug.

BLG-74-HGP via plug in, 10 foot long flexible four wire 208-230v 14/4 cord with neutral and ground wires and molded plug.

NEMA 5-15P (BLG-23-HGP & BLG-27-HG)

NEMA 5-20P (BLG-48-HGP)

NEMA L14-20P (BLG-74-HGP)

0

epoxy-coated cantilever shelves per door. Full-height, auto-close doors will be equipped with triple pane, heated safety glass and heated frames.

Refrigeration system will be self-contained and designed for optimum energy efficiency and low noise. An energy-free condensate removal system will also be standard.

The refrigerant will be R-404A. Tempera-

ture range will be 5° to -15°F (-18° to -26°C). Merchandiser to have standard limited three year parts and labor warranty with additional two year coverage on compressor part.

Merchandiser to be UL and C-UL listed, UL EPH classified, and ENERGY STAR qualified. Merchandiser will also meet Canadian energy efficiency regulations.

NOTE: Cabinet designed for optimum performance in air-conditioned area at 75°F ambient and 55% relative humidity. All specifications subject to change without notice.



908 Highway 15 North • New Albany, MS 38652 PHONE: 800-647-1284 or 662-534-9061 • FAX: 800-232-3966 or 662-534-6049 • www.master-bilt.com