

ITEM NO	
PROJECT	
LOCATION	
DATE	QTY



## **BMG-HGP SERIES**

Bottom Mounted Full-Height Swing Glass Door Refrigerator Merchandisers

#### **MODELS**

- □ BMG-23-HGP
- □ BMG-27-HGP
- □ BMG-48-HGP
- □ BMG-74-HGP

#### **FEATURES**

#### **CONSTRUCTION**

- Standard interior double row LED lighting
- Electronic digital thermostat
- 24 gauge painted textured galvanized steel interior and exterior
- Standard finishes:
  White interior/white exterior or black exterior/black interior
- Stainless steel floor
- 13/4" thick state-of-the-art, foamed-inplace "zero ODP" polyurethane insulation provides high R-value
- Adjustable legs for leveling
- Four adjustable heavy-duty epoxycoated cantilever shelves per door
- Merchandiser profile matches other BLG/BMG Plus refrigerator and freezer models

#### **DOORS**

- Full-height doors
- Auto-close, triple pane, safety glass doors
- 90° hold-open feature
- Contemporary style door frame and handles
- Heavy-duty universal workflow handles
- Easily replaceable snap-in magnetic vinyl door gaskets
- Standard door swing configuration:
- 1-door .....hinged left2-door .....left door hinged left,right door hinged right
- 3-door .....left door hinged left,
  middle door hinged right,
  right door hinged right
- Maximum visibility with these door sizes:
- BMG-23-HGP ......26" x 63<sup>1</sup>/<sub>2</sub>" – BMG-27-HGP .....29" x 63<sup>1</sup>/<sub>2</sub>" – BMG-48-HGP &
- BMG-74-HGP......25" x 63<sup>1</sup>/<sub>2</sub>"

#### REFRIGERATION

- Self-contained bottom mount refrigeration system designed for optimum energy efficiency and low noise
- ENERGY STAR qualified, may be eligible for rebate programs
- Top mounted, low profile interior evaporator housing
- Energy-free condensate removal
- Refrigerant: R-134a
- Temperature range: 34° to 41°F (1° to 5°C)

#### WARRANTY

- Standard limited three year parts and labor
- Additional two year coverage on compressor part

$\overline{}$	_	$\sim$	7	$\mathbf{r}$
-			N	
-		v		ю.

- ☐ Additional shelving
- ☐ Flat bottom shelf with legs
- ☐ Bottom baskets
- □ Casters






## **BMG-HGP SERIES**


# BOTTOM MOUNTED FULL-HEIGHT SWING GLASS DOOR REFRIGERATOR MERCHANDISERS


## **TECHNICAL SPECIFICATIONS**

	DIMENSIONS (in.) DIMENSIONS (mm)					UNIT	NO. OF	NO. OF		CAP.	SHIP WT.			
MODEL	L	D*	H	L	D*	H	VOLTS	AMPS	H.P.	DOORS	SHELVES	SHELF SIZE (in.)	CU. FT.	(LB/KG)
BMG-23-HGP	27	30	79	686	762	2007	115	4.5	1/5	1	4	22 <sup>1</sup> / <sub>2</sub> L x 21 <sup>1</sup> / <sub>2</sub> D	22.1	330/150
BMG-27-HGP	30	30	79	762	762	2007	115	4.5	1/5	1	4	25 <sup>1</sup> / <sub>2</sub> L x 21 <sup>1</sup> / <sub>2</sub> D	25.0	345/157
BMG-48-HGP	52	30	79	1321	762	2007	115	6.9	1/3	2	8	23 <sup>1</sup> / <sub>2</sub> L x 21 <sup>1</sup> / <sub>2</sub> D	45.7	530/241
BMG-74-HGP	78	30	79	1981	762	2007	115	7.7	1/2	3	12	23 <sup>1</sup> / <sub>2</sub> L x 21 <sup>1</sup> / <sub>2</sub> D (outer doors), 25 <sup>1</sup> / <sub>2</sub> L x 21 <sup>1</sup> / <sub>2</sub> D	70.2	715/325
												(middle door)		

<sup>\*</sup>Does not include door handle.







**ELEVATION VIEW** 

**PLAN VIEW** 

LISTINGS

### HOOKUP

UL US ANSI/NSF 7

All models via plug in, 10 foot long, flexible three wire 14/3 cord with molded plug.



- Listed under NSF-7 for the storage and/or display of packaged food
- Meets 2012 Federal DOE Requirements
- Meets Canadian energy efficiency regulations

#### **BID SPECIFICATIONS**

Item no. BMG-\_\_\_\_-HGP. Provide \_\_\_\_\_Bottom Mounted Full-Height Swing Glass Door Refrigerator Merchandiser(s), Master-Bilt model no. BMG-\_\_\_\_-HGP.

Merchandiser will be constructed of 24 gauge painted textured galvanized steel interior and exterior. Standard equipment will include interior LED lighting and four epoxy-coated cantilever shelves per door.

Full-height, auto-close doors will be equipped with triple pane, heated safety glass and heated frames.

Refrigeration system will be self-contained and designed for optimum energy efficiency and low noise. An energy-free condensate removal system will also be standard.

The refrigerant will be R-134a. Temperature range will be 5° to -15°F (-18° to -26°C).

Merchandiser to have standard limited three year parts and labor warranty with additional two year coverage on compressor part.

Merchandiser to be UL and C-UL listed, UL EPH classified, and ENERGY STAR qualified. Merchandiser will also meet Canadian energy efficiency regulations.

NOTE: Cabinet designed for optimum performance in air-conditioned area at 75°F ambient and 55% relative humidity. All specifications subject to change without notice.



908 Highway 15 North • New Albany, MS 38652

PHONE: 800-647-1284 or 662-534-9061 • FAX: 800-232-3966 or 662-534-6049 • www.master-bilt.com