

tem No.	
Project	
Quantity	

# **SB36 Series**

Power [BTU/hr]

32,000

32,000

32,000

Temperature Control

Full-On/Off Full-On/Off

Full-On/Off



MONTAGUE	
Model SB36	

**MODEL GUIDE** 

Mounting

Wall Mount/Brackets

Range/High-Back

**Counter Model** 

- One piece nickel-plated steel cooking grid: 26-3/4" x 13-1/8" (679 x 333mm) deep
- Counter-balanced grid assembly for easy height adjustment
- Infinite grid height adjustment from 2" (51mm) to 5" (127mm)
- Positive locking lift handle with cool ball-style grip
- Quiet, ball bearing mounted pull-out grid assembly
- Full-width horizontal grab-bar handle

### **MOUNTING ALTERNATIVES:**

Model No.

SB36-BHS

SB36-C

**SB36-W** 

- -BHS Models are High Back mounted-left on a T or VT-Technostar Series
- -C Models are designed for (non-combustible) countertop mounting, without leas
- -W Models are designed for (non-combustible) wall-mounting & come with support brackets

### STANDARD CONSTRUCTION FEATURES:

- Satin finish stainless steel front, sides and top
- Other surfaces painted black with electrolytic zinc undercoating
- Broiler interior high temperature aluminized steel
- Full width grease deflector under rollout grid
- Large, removable full-width grease drawer
- 1" (25mm) high broiler flue riser
- 1/2" (13mm) NPT gas connection at upper-right rear

#### **AGENCY APPROVALS**

- NSF Listed
- CSA Design Certified to ANSI Z83.11 CSA 1.8

# SHORT/BID SPECIFICATION

Salamander Broiler shall be a Montague *Technostar* Model: **SB36** -[Specify Mounting]:

- ☐ **-BHS** with High Back for mounting on T or VT Series Technostar
- □ -C for (non-combustible) countertop mounting; or
- -W for wall-mounting with the brackets provided: ...a gas-fired, infrared broiler with 32,000 BTU/hr top-mounted ceramic burner; or
- ...mounted above a counter-balanced, height adjustable, chrome-plated steel cooking grid that is drawer-mounted for easy pull-out access, with a full width grease deflector and large capacity left-front-mounted grease container; plus all the features listed and options/accessories checked:

#### SB36 MODELS — Rapid-Start Burner Features:

- 32,000 BTU/hr ceramic tile burner
- Top-mounted ceramic burner ensures uniform infrared heating for:
- Full flow ON/OFF operation
- Standing pilot for automatic ignition






# Gas Infrared, HD Salamander Broilers

Item No.	
Project	
Quantity	

Dimensions in brackets are millimeters



FRONT VIEW RIGHT SIDE VIEW TOP VIEW

#### **OPTIONS GUIDE:**

**SB36 Series** 

- ☐ Stainless steel back panel
- ☐ Stainless steel bottom
- ☐ Interconnecting gas line between range &

broiler

#### **International Approvals:**

☐ Canadian Approval

### **INSTALLATION REQUIREMENTS & SHIPPING INFORMATION**

- Technostar units must be installed in accordance with local codes or in their absence with the National Fuel Gas Code: ANSI Z223.1; Natural Fuel Cas Code: CAN/CGA-B149.1 or Propane Installation Code: CAN/CGA-B149.2, as applicable. Compliance with codes is the responsibility of the Owner and Installer.
- 2. An adequate ventilation system is required. Refer to National Fire Protection Association Standard No. 96, "Vapor Removal from Cooking Equipment."
- This appliance is intended for commercial use by professionally trained personal. NOT intended for Residential Use.
- **4.** Specify installation elevation: \_\_\_\_\_\_ if above 2000 feet (610m).
- 5. GAS INLET SIZE: 1/2" NPT at top right rear. A 1/2" NPT gas pressure regulator is provided and must be installed (by others) when unit is connected to gas supply. Exception: Optional interconnecting gas line between range mounted SB36 eliminates the above gas connection.

	Specify Type of Gas: Gas Delivery Pressure:		☐ Natural	☐ Propane
ĺ			6.0" WC	10.0" WC
	Models:	Burners	BTU/hr (kWh)	BTU/hr (kWh)
	SB36 [All]	1	32,000 (9.4)	32,000 (9.4)

Mounting Requirements/Minimum Clearances		
Counter Mounting	Non-combustible counters & adjacent walls	
Wall Mounting	Non-combustible walls only — 18" (457mm) from side & bottom combustible material.	
Range Mounting	See range rating plate for clearances.	



Due to continuous product improvements, specifications are subject to change without notice.

