



AX-813RH

Full Size Convection Oven with Humidity Inverter system - manual controls – 3 shelves

Specifications :

| Manual Control knobs time, temperature, humidity Load capacity 3 shelves Full Size pans Fan(s) High Speed with reversing gear 1 Space between trays 2.95" Power / Voltage 4300 Watts / 208-240 V 60 Hz / Single Phase Oven supplied with power cord only / no plug / no plug | | |
|--|------------------------------------|---|
| Fan(s) High Speed with reversing gear 1 Space between trays 2.95" Power / Voltage 4300 Watts / 208-240 V 60 Hz / Single Phase 0ven supplied with power cord only | Manual Control knobs | time, temperature, humidity |
| reversing gear Space between trays 2.95" Power / Voltage 4300 Watts / 208-240 V 60 Hz / Single Phase Oven supplied with power cord only | oad capacity | 3 shelves Full Size pans |
| Space between trays 2.95" Power / Voltage 4300 Watts / 208-240 V 60 Hz / Single Phase 0ven supplied with power cord only | ⁻ an(s) High Speed with | 1 |
| Power / Voltage 4300 Watts / 208-240 V 60 Hz / Single Phase Oven supplied with power cord only | eversing gear | |
| 60 Hz / Single Phase Oven supplied with power cord only | Space between trays | 2.95" |
| Oven supplied with power cord only | ower / Voltage | 4300 Watts / 208-240 V |
| | | 60 Hz / Single Phase |
| / no plug | | Oven supplied with power cord only |
| | | / no plug |
| Temperature 120 ° - 510 °F | Temperature | 120 ° - 510 °F |
| Equipped with 0-120 minute timer - signal at end of cyc | Equipped with | 0-120 minute timer - signal at end of cycle |
| Dimension of cooking 27.33 x 10.16 x 18.73 (WxHxD) - 3 Cubic | Dimension of cooking | 27.33 x 10.16 x 18.73 (WxHxD) - 3 Cubic |
| chamber Feet | hamber | Feet |
| Shipping dimensions 35.46" x 35.46" 28.37" | Shipping dimensions | 35.46" x 35.46" 28.37" |
| Net / Ship Weight 126 lbs / 154 lbs | let / Ship Weight | 126 lbs / 154 lbs |



- Automatically reversing gear
- Manual controls
- Optimal airflow system
- High temperature motor bearings
- High speed fan
- Interior halogen light
- Micro safety switch shuts oven off when door is open
- Includes electro valve for direct water connection
- Heavy duty stainless steel body construction

- Safety "Cold door" design with double wall glass
- Reinforced door hinges
- Oven door can support a weight limit of 80 lbs
- Oven cavity is insulated with ultra-high temperature fibreglass insulation
 Dimensions are quitable to
- Dimensions are suitable to accomodate modular stacking for customized cooking set
 Two Year Limited Warranty
 - Two fear Linned Warranty



FRONT 4 1/4" 1/4" Ø 1 31/32" FEET DIAMETER 5 Ť I 9/16" 28 13/16" 1 3/8" 1 3/8" m 31 1/2" $\phi 1 \hspace{0.1 cm} 3 / 16^{\prime \prime}$ CHIMNEY EXHAUST FOR HOT FUMES WARNING HOT COOLING AIR OUTLET Ø DATA PLATE 20 31/32" G3/4" ELECTRIC VALVE WATER IN 4 5/32" LABEL WATER INLET POWER CABLE IN <u>21 7/</u>16" 10 3/32 ELECTRONIC CONTROL BOARD GROUND TERMINAL Ø1 3/16" AX-813RHD 1.2011 HUMIDIFICATION SETTING TEMPERATURE SETTING 31 19/32' AX-813RH Ű 30 HEATING LIGHT INDICATOR TIMER SETTING WATER IN PRESSURE: 150-200 kPa (1.5-2 bar) WATER IN TEMPERATURE: 10-30°C (50-86°F)