



## Features:

- · Optimal airflow system
- Manual controls
- High temperature motor bearings
- High speed fan
- Interior halogen light
- Includes electro valve for direct water connection
- Heavy duty stainless steel body construction
- Safety "Cold door" design with double wall glass

- Micro safety switch shuts oven off when door is open
- Reinforced door hinges
- Oven door can support a weight limit of 80 lbs
- Oven cavity is insulated with ultra-high temperature fibreglass insulation
- Dimensions are suitable to accomodate modular stacking for customized cooking set
- Two Year Limited Warranty

## **AX-C513H**

## Half Size Convection Oven with Humidity manual controls – 3 shelves

## **Specifications:**

<b>Manual Control knobs</b>	time, temperature, humidity
Load capacity	3 shelves Half Size pans
Fan(s) High Speed	1
Space between trays	2.95"
Power / Voltage	3600 Watts / 220-240 V / 50/60 Hz
	Single Phase / cable with NEMA 6-15P
Temperature	122° - 536°F (50° - 280°C)
Equipped with	0-120 minute timer - signal at end of cycle
Dimension of cooking	19.45 x 11.03 x 16.25 (WxHxD) - 2.02
chamber	Cubic Feet
<b>Shipping dimensions</b>	29.16" x 31.91" x 29.94"
Net / Ship Weight	85 lbs / 111 lbs



