

Sushi

Counter top stainless steel refrigerated display case

KSDC SERIES

Project name:	
Location:	
Item:	Qty:
Model:	



- Designed to display sushi, meats, salads, desserts and many other items for quick point of purchase sales

Curved front tempered glass for added visibility, safety and increased durability
 Hinged front glass tilts forward to simplify cleaning

- Interior LED lighting (with protective cover) enhances overall product appearance
-Removable sliding rear doors allow for easy access and simplify cleaning

- Upper double evaporator fin-type coil assures proper temperature throughout the cabinet - Electronic thermostat maintains temperatures between 33°F/1°C

and 40°F/7°C, digitally displays temperature at all times

- Upper stainless steel baffle plate creates a drip-free food safe environment

- Available with either a left side or right side compressor

- Sealed compressor with a double-vented high quality condenser

- 304 finish stainless steel deep drawn inner pan - Automatic defrosting

Stainless steel body

 Condensate from upper coil drains directly into a shelf contained evaporation channel, eliminating any drain connection requirement

- Environmentally friendly R134-A type Freon

- These units are designed for maximum performance

in an air-conditioned area of 77°F ambient temperature and 55% relative humidity



Tel.: 514.737.9701 / Toll Free: 888.275.4538 Fax: 514.342.3854 / Toll Free: 877.453.8832 sales@mvpgroupcorp.com www.mvpgroupcorp.com



KSDC SERIES

Model	Width		Depth		Height		NET	Max	SHIPPING SPECS			
	Ext.	Int.	Ext.	Int.	Ext.	Int.	Weight	Capacity	Weight	Depth	Height	Weight
KSDC - 5	65.5"	41.3"	15.1"	12.1"	12.0"	6.2"	101 lbs	2.88 cu.ft	65.5"	23.2"	22.5"	145 lbs
KSDC - 6	70.4"	55.0"	15.1"	12.1"	12.0"	6.2"	114 lbs	3.83 cu.ft	79.2"	23.2"	22.5"	170 lbs
KSDC - 7	84.3"	70.0"	15.1"	12.1"	12.0"	6.2"	123 lbs	4.80 cu.ft	91.3"	23.2"	22.5"	190 lbs

Electrical: 115/60/1 Saturation temperature: 33°F/1°C

Voltage variation: + / - 10% Ambient temp: 77°F/25°C, no load

Rated amperage: 4.5 A Refrigerant type: R-134A

Maximum ambient temperature: 77°F/25°C Maximum load height: 5.4"

Compressor: 0.25 HP

These units are designed for maximum performance in an air-conditioned area of 77°F ambient temperature and 55% relative humidity. There must be adequate ventilation at the top, sides & rear of the unit for proper operation.

Important: this unit doesn't have an automatic defrost system and must be turned off at night to allow the evaporator to defrost

Warranty: 12 months parts & labor. 24 months on the condenser & compressor





KOOL-IT is a registered trade mark of MVP Group. Specifications subject to change without notice.



Tel.: 514.737.9701 / Toll Free: 888.275.4538 Fax: 514.342.3854 / Toll Free: 877.453.8832 sales@mvpgroupcorp.com www.mvpgroupcorp.com