

# Piggy's BBQ Stainless Steel Cleaner 17 oz

## SAFETY DATA SHEET

### SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

**Product identifier**

|               |                                     |
|---------------|-------------------------------------|
| Chemical Name | Mixture                             |
| CAS No.       | Mixture                             |
| Trade Name    | Piggy's BBQ Stainless Steel Cleaner |
| Product Code  | PBSS-3668                           |

**Relevant identified uses of the substance or mixture and uses advised against**

|                        |  |
|------------------------|--|
| Identified Use(s)      | Cleaning & Polishing                                 |
| Uses Advised Against   | None   |
| Company Identification | AVW, Inc<br>PO Box 9962<br>Fort Lauderdale, FL 33310 |
| Telephone              | (954) 972-3338                                       |

**Emergency telephone number**

|                     |                |
|---------------------|----------------|
| Emergency Phone No. | (800) 424-9300 |
|---------------------|----------------|

### SECTION 2: HAZARDS IDENTIFICATION

**Classification of the substance or mixture**

OSHA HCS (29 CFR 1910.1200)

Flam. Aerosol 1; Liquefied gas; Skin Irrit. 2; STOT SE 3; Asp. Tox. 1

**Label elements**

Hazard Symbol



**DANGER**

Signal word(s)

Hazard Statement(s)

Extremely flammable aerosol.  
Contains gas under pressure; may explode if heated.  
Causes skin irritation.  
May cause drowsiness or dizziness.  
May be fatal if swallowed and enters airways.  
Keep away from heat/sparks/open flames/hot surfaces. – No smoking.  
Do not spray on an open flame or other ignition source.  
Do not pierce or burn, even after use.  
Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F.  
Wear protective gloves/protective clothing/eye protection/face protection.  
Use only outdoors or in a well-ventilated area.  
Avoid breathing spray.  
Wash hands and exposed skin after use.  
Keep out of reach of children.

Precautionary Statement(s)

# Piggy's BBQ Stainless Steel Cleaner 17 oz

Other hazards

Harmful to aquatic life.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

| Hazardous ingredient(s) | %W/W * | CAS No. | Hazard classification   |
|-------------------------|--------|---------|---|
| Petroleum Distillates   | 5 - 20 | various | Flam. Liq. 2; H225<br>Asp. Tox. 1; H304<br>Skin Irrit. 2; H315<br>STOT SE 3; H336<br>Aquatic Acute 2; H401<br>Aquatic Chronic 3; H412 |
| Propane                 | 5 - 10 | 74-98-6 | Flam. Gas 1, H220<br>Press. Gas (*)   |

Additional Information - None

\* The exact percentage withheld as a trade secret in accordance with 29 CFR 1910.1200.

## SECTION 4: FIRST AID MEASURES



### Description of first aid measures

Inhalation

Move person to fresh air. If breathing is laboured, administer oxygen. If symptoms develop, obtain medical attention.

Skin Contact

Wash affected skin with soap and water. If symptoms develop, obtain medical attention.

Eye Contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Ingestion

Do not give anything by mouth to an unconscious person. Do NOT induce vomiting.

**Most important symptoms and effects, both acute and delayed**

May be fatal if swallowed and enters airways. Will cause skin irritation. Vapours may cause drowsiness and dizziness.

**Indication of any immediate medical attention and special treatment needed**

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

## SECTION 5: FIRE-FIGHTING MEASURES

### Extinguishing Media

- Suitable Extinguishing Media
- Unsuitable Extinguishing Media

Extinguish with carbon dioxide, dry chemical, foam or waterspray. Do not use water jet.

**Special hazards arising from the substance or mixture**

Highly flammable vapour (flash point below 23°C).

### Advice for fire-fighters

A self contained breathing apparatus and suitable protective clothing should be worn in fire conditions. Keep containers cool by spraying with water if exposed to fire.

# Piggy's BBQ Stainless Steel Cleaner 17 oz

## SECTION 6: ACCIDENTAL RELEASE MEASURES

|  |   |
|--|---|
| <b>Personal precautions, protective equipment and emergency procedures</b> | Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Avoid contact with skin and eyes. Avoid breathing gas/spray. Avoid contact with skin and eyes. |
| <b>Environmental precautions</b>   | Prevent liquid entering sewers, basements and work pits.  |
| <b>Methods and material for containment and cleaning up</b>                | Cover spills with inert absorbent material. Transfer to a container for disposal or recovery.   |
| <b>Reference to other sections</b>   | None  |
| <b>Additional Information</b>  | None  |

## SECTION 7: HANDLING AND STORAGE

|   |  |
|---|--|
| <b>Precautions for safe handling</b>                                | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid contact with skin and eyes. Use product in a well-ventilated area only. |
| <b>Conditions for safe storage, including any incompatibilities</b> |  |
| -Storage temperature  | Keep in a cool, well ventilated place. Store at temperatures not exceeding 50°C / 122 °F.  |
| -Incompatible materials   | This product should be stored away from sources of strong heat or oxidizing chemicals.   |
| <b>Specific end use(s)</b>  | Automotive Care Product  |

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### Occupational Exposure Limits

| SUBSTANCE.   | CAS No.     | (8hr TWA)  |                        | (STEL)     |             | Note:      |
|--|-------------|------------|------------------------|------------|-------------|------------|
|  |             | PEL (OSHA) | TLV (ACGIH)            | PEL (OSHA) | TLV (ACGIH) |            |
| Heptane, branched, cyclic and linear                   | 426260-76-6 | 500 ppm*   | 1500 mg/m <sup>3</sup> | -----      | -----       | *n-heptane |
| C <sub>9</sub> -C <sub>15</sub> Alkanes & Cycloalkanes | Mixture     | -----      | 1200 mg/m <sup>3</sup> | -----      | -----       |            |
| Propane  | 74-98-6     | 1000 ppm   | Aspyx.#                | -----      | -----       | #          |

\*Assure minimum oxygen content of work atmosphere.

**Recommended monitoring method** NIOSH 1500 (hydrocarbons, B.P. 36 - 126 °C); NIOSH 1550 (Naphthas)

### Exposure controls

**Appropriate engineering controls** Use only with adequate ventilation to keep exposures (airborne levels of dust, fume, vapour etc) below recommended exposure limits.

### Personal protection equipment

Eye/face protection



Wear protective eyewear (goggles, face shield, or safety glasses).

Skin protection (Hand protection/ Other)



Wear suitable gloves if prolonged skin contact is likely (Nitrile rubber)

# Piggy's BBQ Stainless Steel Cleaner 17 oz

Respiratory protection



Normally no personal respiratory protection is necessary. In case of insufficient ventilation, wear suitable respiratory equipment. Check with protective equipment manufacturer's data.

Thermal hazards

Not normally required. Use gloves with insulation for thermal protection, when needed.

Environmental Exposure Controls

None known

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

|  |                                |
|--|--------------------------------|
| Appearance                               | Liquid / Liquefied gas         |
| Color.                                   | Clear                          |
| Odor                                     | Petroleum spirit               |
| Odor Threshold (ppm)                     | Not available                  |
| pH (Value)                               | Not available                  |
| Melting Point (°C) / Freezing Point (°C) | Not available                  |
| Boiling point/boiling range (°C):        | Not available                  |
| Flash Point (°C)                         | -104 (Propane)                 |
| Evaporation Rate                         | Not available                  |
| Flammability (solid, gas)                | Extremely flammable            |
| Explosive Limit Ranges                   | 2.1% - 9.5% v/v (Propane)      |
| Vapor pressure (Pascal)                  | ca. $95 \times 10^4$ (Propane) |
| Vapor Density (Air=1)                    | ca. 1.56 @ 0°C (Propane)       |
| Density (g/ml)                           | Not available                  |
| Solubility (Water)                       | Not available                  |
| Solubility (Other)                       | Not available                  |
| Partition Coefficient (n-Octanol/water)  | Not available                  |
| Auto Ignition Point (°C)                 | 450 (Propane)                  |
| Decomposition Temperature (°C)           | Not available                  |
| Kinematic Viscosity (cSt)                | <20                            |
| Explosive properties                     | Not explosive.                 |
| Oxidizing properties                     | Not oxidising.                 |
| <b>Other information</b>                 | Not available                  |

## SECTION 10: STABILITY AND REACTIVITY

|   |  |
|---|--|
| <b>Reactivity</b>                         | Stable under normal conditions.  |
| <b>Chemical stability</b>                 | Stable.  |
| <b>Possibility of hazardous reactions</b> | None anticipated.  |
| <b>Conditions to avoid</b>                | Avoid contact with heat and ignition sources.  |
| <b>Incompatible materials</b>             | This product should be stored away from sources of strong heat or oxidizing chemicals. |
| <b>Hazardous decomposition product(s)</b> | None known   |

## SECTION 11: TOXICOLOGICAL INFORMATION

**Exposure routes:** Inhalation, Skin Contact, Eye Contact

Heptane, branched, cyclic and linear (CAS# 426260-76-6) - By analogy with similar materials:

|                       |  |
|-----------------------|--|
| <b>Acute toxicity</b> | Oral: LD50 >5 g/kg-bw<br>Dermal: LD50 >2 g/kg-bw<br>Inhalation: LC50 = 65 - 103 mg/L (Vapour), 4-hr. rat<br>May cause drowsiness or dizziness. |
|-----------------------|--|

# Piggy's BBQ Stainless Steel Cleaner 17 oz

|                                |  |
|--------------------------------|--|
| <b>Irritation/Corrosivity</b>  | Causes skin irritation. Repeated exposure may cause skin dryness or cracking. May cause eye irritation.  |
| <b>Sensitisation</b>           | It is not a skin sensitiser.   |
| <b>Repeated dose toxicity</b>  | NOAEC: 12350 mg/m3 (2 yr, inhal., rat, Systemic effects)<br>LOAEC: 1650 mg/m3 (2 hr, inhal., rat, CNS effects)<br>May cause drowsiness or dizziness. |
| <b>Carcinogenicity</b>         | No data. It is unlikely to present a carcinogenic hazard to man.   |
| <b>Mutagenicity</b>            | There is no evidence of mutagenic potential.   |
| <b>Reproductive toxicity</b>   | None anticipated   |
| <u>Propane (CAS# 74-98-6):</u> |  |
| <b>Acute toxicity</b>          | Inhalation: LC50 = 1237 mg/L (2-hr, mouse, gas)  |
| <b>Irritation/Corrosivity</b>  | No evidence of irritant effects from normal handling and use.  |
| <b>Sensitisation</b>           | It is not a skin sensitiser.   |
| <b>Repeated dose toxicity</b>  | NOAEC: ≥19678 mg/m3 (28-day, rat, Systemic effects)<br>LOAEC: 21641 mg/m3 (28-day, rat, effects: Body weight)  |
| <b>Carcinogenicity</b>         | No data. It is unlikely to present a carcinogenic hazard to man.   |
| <b>Mutagenicity</b>            | There is no evidence of mutagenic potential.   |
| <b>Reproductive toxicity</b>   | None anticipated   |

## SECTION 12: ECOLOGICAL INFORMATION

### Aquatic toxicity:

Heptane, branched, cyclic and linear (CAS# 426260-76-6) - By analogy with similar materials:

|                   |   |
|-------------------|---|
| <b>Short term</b> | LL50 (96 hour): >13.4 mg/L ( <i>Oncorhynchus mykiss</i> )<br>EL50 (48 hour): 3 mg/l ( <i>Daphnia magna</i> , mobility)<br>EC50 (96 hour): 13 mg/l ( <i>Pseudokirchnerella subcapitata</i> ) |
| <b>Long Term</b>  | NOELR (28 days) 1.5 mg/l ( <i>Fish</i> ) QSAR<br>LOEC (21 days): 0.32 mg/l ( <i>Daphnia magna</i> )<br>NOEL (96 hour) 6.3 mg/l ( <i>Algae</i> )   |

## SECTION 13: DISPOSAL CONSIDERATIONS

|                                |  |
|--------------------------------|--|
| <b>Waste treatment methods</b> | Disposal should be in accordance with local, state or national legislation. Consult an accredited waste disposal contractor or the local authority for advice. |
|--------------------------------|--|

## SECTION 14: TRANSPORT INFORMATION

|                                     | <u>U.S. DOT</u>     | <u>Sea transport (IMDG)</u> | <u>Air transport (ICAO/IATA)</u> |
|-------------------------------------|---------------------|-----------------------------|----------------------------------|
| <b>UN number</b>                    | 1950                | 1950                        | 1950                             |
| <b>Proper Shipping Name</b>         | Aerosols, flammable | Aerosols, flammable         | Aerosols, flammable              |
| <b>Transport hazard class(es)</b>   | 2.1                 | 2.1                         | 2.1                              |
| <b>Packing group</b>                | Not applicable      | Not applicable              | Not applicable                   |
| <b>Environmental hazards</b>        | None assigned       | None assigned               | None assigned                    |
| <b>Special precautions for user</b> | None assigned       | None assigned               | None assigned                    |

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable

# Piggy's BBQ Stainless Steel Cleaner 17 oz

## SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture:

TSCA (Toxic Substance Control Act) - Inventory Status: All components listed or polymer exempt.

Designated Hazardous Substances and Reportable Quantities (40 CFR 302.4):

| Chemical Name  | CAS No.   | Typical %wt. | RQ (Pounds) |
|----------------|-----------|--------------|-------------|
| Sodium Nitrite | 7632-00-0 | 0.5          | 100         |

SARA 311/312 - Hazard Categories:

Fire     Sudden Release     Reactivity     Immediate (acute)     Chronic (delayed)

SARA 313 - Toxic Chemicals (40 CFR 372):

| Chemical Name  | CAS No.   | Typical %wt. |
|----------------|-----------|--------------|
| Sodium Nitrite | 7632-00-0 | 0.5          |

SARA 302 - Extremely Hazardous Substances(40 CFR 355):

| Chemical Name | CAS No. | Typical %wt. | TPQ (pounds) |
|---------------|---------|--------------|--------------|
| None          | ----    | ----         | ----         |

California Proposition 65 List:

| Chemical Name | CAS No. | Type of Toxicity |
|---------------|---------|------------------|
| None          | ----    | ----             |

## SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 1-16.

Date of preparation: September 23, 2014

Hazard Statement(s) and Risk Phrases Listed in:

Hazard Statement(s)

- H220: Extremely flammable gas.
- H225: Highly flammable liquid and vapour.
- H272: May intensify fire; oxidiser.
- H301: Toxic if swallowed.
- H302: Harmful if swallowed.
- H304: May be fatal if swallowed and enters airways.
- H312: Harmful in contact with skin.
- H315: Causes skin irritation.
- H319: Causes serious eye irritation.
- H332: Harmful if inhaled.
- H336: May cause drowsiness or dizziness.
- H401: Toxic to aquatic life.
- H412: Harmful to aquatic life with long lasting effects.

Training advice: None.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.