800-955-5253 715-386-2323 866-961-5253 Parts 800-388-5253 Service 715-386-6149 FAX

www.norlake.com



# ADVANTEDGETM SOLID DOOR BACK BAR REFRIGERATORS



PROJECT:

\_\_\_\_\_

ITEM NUMBER:

MODEL NUMBER:

# SPECIFICATIONS FOR: NLBB59, NLBB69, NLBB79, NLBB95

Heavy duty stainless steel top and black vinyl coated steel exterior front, sides and back. Finish:

Galvanized steel interior walls with stainless steel floor.

Insulation: Foamed-in-place 1-1/2" CFC-Free polyurethane insulation.

Hardware: Solid doors with locks, magnetic door gaskets, plastic breaker strips around door openings

to limit the formation of any condenstation. Two adjustable epoxy coated shelves per door

section standard. Interior fluorescent light.

115 volt, 60 Hz, 1 phase with cord and NEMA 5-15P Plug. Electrical:

Refrigeration: Self-contained forced air R-134a capillary tube refrigeration system. Temperature range from

35°F to 38°F. Adjustable temperature control.

ETL Safety and Sanitation listed Approvals:

#### STANDARD FEATURES

- Adjustable temperature control
- Black vinyl coated steel front, sides and back exterior
- Fluorescent interior light
- Free flowing air system at all times to ensure uniformly cooled product
- Heavy duty 18 gauge stainless steel top
- Slide out condensing unit
- Temperature range: 35°F to 38°F
- Two shelves per door
- ETL Safety and Sanitation listed
- Approved to NSF standard for bottled or canned products
- Warranties: 3 year parts & labor, 5 year compressor

### OPTIONAL FEATURES\*


- Epoxy coated flat shelves with clips
- Floor rack
- Glass doors
- Shelves with product guides
- 3" casters





Registered to ISO 9001:2008 File No. 10001816



TOP ••









**FRONT** NLBB69

**FRONT** NLBB59


NLBB59

SIDE


**SPECIFICATIONS** 

# 28 3/16 [716.00]

## **TOP** NLBB69



**FRONT** NLBB79




NLBB79


Model	NLBB59	NLBB69	NLBB79	NLBB95
Crated Height	43"	43"	43"	43"

Model	NLBB39	NLBB09	NLBB/9	NLBB93
Crated Height	43"	43"	43"	43"
Crated Width	60-1/2"	70-1/2"	81"	96-1/2"
Crated Depth	30"	30"	30"	30"
Crated Weight (lbs.)	312	360	378	440
Interior Height	31-3/4"	31-3/4"	31-3/4"	31-3/4"
Interior Width	44-9/16"	54-9/16"	65-1/16"	80-9/16"
Interior Depth	24-3/4"	24-3/4"	24-3/4"	24-3/4"
Overall Height	37-1/4"	37-1/4"	37-1/4"	37-1/4"
Overall Width	59-1/2"	69-1/2"	80"	95-1/2"
Overall Depth	28-3/16"	28-3/16"	28-3/16"	28-3/16"
Gross Cubage (ft.3)	23.7 (670)	28 (793)	30.8 (872)	39.2 (1112)
Ni walan a f Olan I wan		4	6	6
Number of Shelves	4		U	U
Condensing Unit Size	1/3	1/3	1/3	1/3
-	· · · · · · · · · · · · · · · · · · ·	•		
Condensing Unit Size	1/3	1/3	1/3	1/3
Condensing Unit Size Refrigerant	1/3 R134a	1/3 R134a	1/3 R134a	1/3 R134a
Condensing Unit Size Refrigerant Electrical Characteristics	1/3 R134a 115/60/1	1/3 R134a 115/60/1	1/3 R134a 115/60/1	1/3 R134a 115/60/1
Condensing Unit Size Refrigerant Electrical Characteristics Cord and Plug Furnished	1/3 R134a 115/60/1 Yes	1/3 R134a 115/60/1 Yes	1/3 R134a 115/60/1 Yes	1/3 R134a 115/60/1 Yes
Condensing Unit Size Refrigerant Electrical Characteristics Cord and Plug Furnished Nema Plug Configuration	1/3 R134a 115/60/1 Yes 5-15P	1/3 R134a 115/60/1 Yes 5-15P	1/3 R134a 115/60/1 Yes 5-15P	1/3 R134a 115/60/1 Yes 5-15P
Condensing Unit Size Refrigerant Electrical Characteristics Cord and Plug Furnished Nema Plug Configuration Total Amp Draw	1/3 R134a 115/60/1 Yes 5-15P 6.6	1/3 R134a 115/60/1 Yes 5-15P 6.6	1/3 R134a 115/60/1 Yes 5-15P 6.6	1/3 R134a 115/60/1 Yes 5-15P 7.2

Specifications subject to change without notice.



**FRONT** NLBB95



**TOP** NLBB95







Revision Date: 03/13 ©2013 NOR-LAKE, INC. Printed in the U.S.A. Part Number: 143584