

NOR-LAKE, INCORPORATED
727 Second Street
P.O. Box 248
Hudson, Wisconsin 54016

800-955-5253
715-386-2323
866-961-5253 Parts
800-388-5253 Service
715-386-4291 FAX
www.norlake.com



ADVANTEDGE™ SWING GLASS DOOR FREEZER MERCHANDISERS



NLGFP48-HG

NLGFP27-HG



PROJECT:

ITEM NUMBER:

MODEL NUMBER:

SWING GLASS DOOR MERCHANDISERS

SPECIFICATIONS FOR: NLGFP23-HG, NLGFP27-HG, NLGFP48-HG, NLGFP74-HG

- **Finish:** 24 gauge painted textured galvanized steel interior and exterior. Black or white exterior finish. Standard white interior finish with stainless steel floor
- **Insulation:** 1-3/4" thick state-of-the-art, foamed-in-place "zero ODP" polyurethane insulation
- **Hardware:** Interior LED lighting with switch, interior hanging thermometer, top backlit graphic panel (standard panel is blank without graphics), adjustable legs for leveling, four adjustable heavy-duty epoxy coated shelves per door - adjustable in 1/2" increments on pilasters
- **Door:** Auto-close, triple pane, safety glass doors, contemporary style black heated door frame, heated glass, heavy-duty universal anti-microbial workflow handles, heavy-duty self-closing torquemaster hinges with field adjustable leveling and closing tension capability
Standard door swing configuration:
– 1-doorhinged right
– 2-door left door hinged left, right door hinged right
– 3-door left door hinged left, middle door hinged right, right door hinged right
- **Electrical:** 115 volt, 60 Hz, 1 phase with cord and plug. 115/208-230/60/1 for NLGFP74-HG
- **Refrigeration** Self-contained bottom mount refrigeration system designed for optimum energy efficiency and low noise. Top mounted, low profile interior evaporator housing for increased storage, energy-free condensate removal. Refrigeration system is accessible for ease of service and regular preventative maintenance. Refrigerant: R-404a. Temperature range: +5°F to -15°F. Electronic temperature control.
- **Approvals:** UL/C-UL Safety, UL Sanitation, NRCAN and ENERGY STAR® listed **

STANDARD FEATURES

- 24 gauge painted textured galvanized steel interior and exterior
- 2-1/2" adjustable legs for leveling
- Anti-microbial finish on door handles
- Auto-close, triple pane, safety glass doors
- Contemporary style black heated door frame
- Energy-free condensate removal
- Four adjustable heavy-duty epoxy coated shelves per door
- Interior hanging thermometer
- Interior LED lighting with switch
- Product guard for optimum air flow
- Refrigerant: R-404a
- Self-contained bottom mount refrigeration system
- Standard and larger capacity single door models
- Top backlit graphic panel (standard panel is blank without graphics)
- Temperature range: +5°F to -15°F
- Top mounted, low profile interior evaporator housing for increased storage
- White interior finish with stainless steel floor
- Warranties: 3 year parts and labor, 5 year compressor
- Approvals: UL/C-UL Safety, UL Sanitation, NRCAN and ENERGY STAR®

OPTIONAL FEATURES*

- Additional shelving
- Black or white exterior finish
- Casters
- Graphic sign panels
- Price tag molding for shelving



Nor-Lake, Inc.
Registered to ISO 9001:2008
File No. 10001816

* Most options are available two weeks from receipt of order. Please contact us for specific questions.

** C-UL is Underwriters Laboratories Safety Certification Mark which indicates that UL has tested the equipment to applicable CSA Standards.

** UL Sanitation is Underwriters Laboratories Sanitation Mark which indicates that UL has tested the equipment to applicable NSF Standards.

