

NOR-LAKE, INCORPORATED  
727 Second Street  
P.O. Box 248  
Hudson, Wisconsin 54016

800-955-5253  
715-386-2323  
866-961-5253 Parts  
800-388-5253 Service  
715-386-4291 FAX  
www.norlake.com



## ADVANTEDGE™ SWING GLASS DOOR REFRIGERATOR MERCHANDISERS



NLGRP23-HG

NLGRP48-HG



PROJECT:

ITEM NUMBER:

MODEL NUMBER:

SWINGING GLASS DOOR MERCHANDISERS

### SPECIFICATIONS FOR: NLGRP23-HG, NLGRP27-HG, NLGRP48-HG, NLGRP74-HG

- **Finish:** 24 gauge painted textured galvanized steel interior and exterior. Black or white exterior finish. Standard white interior finish with stainless steel floor
- **Insulation:** 1-3/4" thick state-of-the-art, foamed-in-place "zero ODP" polyurethane insulation
- **Hardware:** Interior LED lighting with switch, interior hanging thermometer, top backlit graphic panel (standard panel is blank without graphics), adjustable legs for leveling, four adjustable heavy-duty epoxy coated shelves per door - adjustable in 1/2" increments on pilasters
- **Door:** Auto-close, triple pane, safety glass doors, contemporary style black door frame, heavy-duty universal anti-microbial workflow handles, heavy-duty self-closing torque-master hinges with field adjustable leveling and closing tension capability.  
Standard door swing configuration:  
 - 1-door .....hinged right  
 - 2-door ..... left door hinged left, right door hinged right  
 - 3-door ..... left door hinged left, middle door hinged right, right door hinged right
- **Electrical:** 115 volt, 60 Hz, 1 phase with cord and plug
- **Refrigeration** Self-contained bottom mount refrigeration system designed for optimum energy efficiency and low noise. Top mounted, low profile interior evaporator housing for increased storage space, energy-free condensate removal. Refrigeration system is accessible for ease of service and regular preventative maintenance. Refrigerant: R-134a. Temperature range: +34° to +41°F. Electronic temperature control.
- **Approvals:** UL/C-UL Safety, UL Sanitation, NRCAN and ENERGY STAR® listed \*\*

### STANDARD FEATURES

- 24 gauge painted textured galvanized steel interior and exterior
- 2-1/2" adjustable legs for leveling
- Anti-microbial finish on door handles
- Auto-close, triple pane, safety glass doors
- Contemporary style black door frame
- Energy-free condensate removal
- Four adjustable heavy-duty epoxy coated shelves per door
- Interior hanging thermometer
- Interior LED lighting with switch
- Refrigerant: R-134a
- Self-contained bottom mount refrigeration system
- Standard and larger capacity single door models
- Top backlit graphic panel (standard panel is blank without graphics)
- Temperature range: +34° to +41°F
- Top mounted, low profile interior evaporator housing for increased storage space
- White interior finish with stainless steel floor
- Warranties: 3 year parts and labor, 5 year compressor
- Approvals: UL/C-UL Safety, UL Sanitation, NRCAN and ENERGY STAR®

### OPTIONAL FEATURES\*

- Additional shelving
- Black or white exterior finish
- Casters
- Field reversible door swing hinging kit (one-door models only)
- Graphic sign panels
- Price tag molding for shelving



Nor-Lake, Inc.  
Registered to ISO 9001:2008  
File No. 10001816

\* Most options are available two weeks from receipt of order. Please contact us for specific questions.

\*\* C-UL is Underwriters Laboratories Safety Certification Mark which indicates that UL has tested the equipment to applicable CSA Standards.

\*\* UL Sanitation is Underwriters Laboratories Sanitation Mark which indicates that UL has tested the equipment to applicable NSF Standards.

