800-955-5253 715-386-2323 866-961-5253 Parts 800-388-5253 Service 715-386-4291 FAX www.norlake.com



## ADVANTEDGE™ MEGA TOP SANDWICH FOOD PREP REFRIGERATORS



PROJECT:

ITEM NUMBER:

MODEL NUMBER:

SPECIFICATIONS FOR: NLSMP27-12, NLSMP36-15, NLSMP48-18, NLSMP60-24, NLSMP72-30

■ Finish: Stainless steel interior and exterior.

■ <u>Insulation:</u> Complete cabinet and doors are foamed-in-place with polyurethane insulation.

Insulated pan cover.

■ <u>Hardware</u>: Curved handle with recessed pocket and one epoxy coated shelf per door, 6" diameter

casters standard.

■ Electrical: 115 volt, 60 Hz, 1 phase with cord and plug.

■ Refrigeration: Self contained forced air refrigeration system. The condensate is collected and

automatically evaporated from an energy efficient hot gas style vaporizer. Refrigerant flow is controlled by a capillary tube. R-134a refrigerant. Temperature range: +32°F

to +40°F.

■ <u>Accessories:</u> 1/6 size pans and 9-1/2" polyethylene cutting board included.

Approvals: UL, C-UL and ETL Sanitation listed \*\*

## STANDARD FEATURES

- 1/6 size pans included
   \*Note: NLSMP27-12 has (9) 1/6 size pans and (3) 1/9 size pans included.
- Air cooled condensing unit
- Automatic condensate vaporizer
- Automatic defrost
- Capillary tube system
- Casters
- Cutting board

- Magnetic gaskets
- Self closing doors
- Stainless steel interior and exterior
- UL, C-UL and ETL Sanitation listed \*\*
- Warranties: 3 year parts & labor, 5 year compressor

## **OPTIONAL FEATURES\***

- Additional shelves
- Overshelf assemblies
- Pull out drawers




Nor-Lake, Inc. Registered to ISO 9001:2008 File No. 10001816

\* Most options are available two weeks from receipt of order. Please contact us for specific questions.

\*\* C-UL is Underwriters Laboratories Safety Certification Mark which indicates that UL has tested the equipment to applicable CSA Standards.

\*\* UL-Sanitation is Underwriters Laboratories Safety Certification Mark which indicates that UL has tested the equipment to applicable NSF Standards.

SPECIFICATION



210 [8 1/4] 967 [38 1/8] 151 [6] 456 [18] **FRONT** 

44-1/2"

37-1/4"

35-3/8"

284

26-1/8"

32-3/4"

20-1/4"

44-1/8"

36-3/8"

35-1/4"


10

15

2

12\*

1



NLSMP60-24

44-1/2"

63"

35-3/8"

362

26-1/8"

56-3/4"

20-1/4"

44-1/8"

60-3/8'

35-1/4"

16

24

2

**SPECIFICATIONS** 

NLSMP72-30

44-1/2"

74-3/8"

35-3/8"

399

26-1/8"

68-5/8"

20-1/4"

44-1/8"

72-3/8"

35-1/4"

20

30

3

NLSMP36-15

NLSMP48-18

44-1/2"

51-1/8"

35-3/8"

318

26-1/8"

44-5/8"

20-1/4"

44-1/8"

48-1/4"


35-1/4"


13

18

2


## NLSMP27-12





Number of 1/6 Pans

Number of Shelves




		1421 TOP COVER S	[56] SIZE	
	1			1
967 [38 1/8]	210 [8 1/4]			FRONT
151 [6]		761 [30] DOOR	8	NLSMP60-2


Number of Casters	4	4	4	4	4
Condensing Unit Size	1/5 HP	1/5 HP	3/8 HP	3/8 HP	3/8 HP
Refrigerant	R-134a	R-134a	R-134a	R-134a	R-134a
Electrical Characteristics	115/60/1	115/60/1	115/60/1	115/60/1	115/60/1
Cord and Plug Furnished	Yes	Yes	Yes	Yes	Yes
Nema Plug Configuration	5-15P	5-15P	5-15P	5-15P	5-15P
Total Amp Draw	3.2	3.4	7.9	7.9	9.9

TOP 1468 [57 3/4]

1533 [60 3/8]

Specifications subject to change without notice.









©2013 Nor-Lake, Inc. Printed in the USA Part Number: 143381

NLSMP72-30