NOR-LAKE, INCORPORATED 727 Second Street P.O. Box 248 Hudson, Wisconsin 54016

800-955-5253 715-386-2323 800-388-5253 Parts 715-386-6149 FAX www.norlake.com

# **NOVA<sup>™</sup> HEATED PASS-THRU CABINETS**

NORLAKE



### SPECIFICATIONS FOR: PW252 & PW554

• Exterior finish:	Exterior front, sides, back and doors are stainless steel. The exterior top and bottom are galvanized steel. All exterior joints and seams fold in without lap joints. No exposed raw edges.
<ul> <li>Interior finish:</li> </ul>	Interior liner and interior door panels are stainless steel.
Insulation:	
	The complete cabinet and door(s) are foamed-in-place with polyurethane insulation.
<ul> <li>Hardware:</li> </ul>	Heavy duty, pivot hinges; centered key locks; full length, stainless steel pull handles; self adjusting
	magnetic gaskets; 4" dia. casters; and nickel chrome shelves.
Electrical:	All models are standard with an interior incandescent light activated by a door switch.
Instrumentation:	Digital LED thermometer reading degrees F.
<ul> <li>Heating system:</li> </ul>	Electrically operated 1500 watt heating system for 2 door model and a 3000 watt heating system for the
	4 door model, is controlled by a thermostat mounted in front of the cabinet. Heating element is located in
	the interior ducting. Forced air distribution maintains desired uniform temperature throughout the cabinet.
	Operating temperature is adjustable from 180° F to a maximum of 200° F.
<ul> <li>Approvals:</li> </ul>	UL listed
	C-UL listed**
	UL Sanitation listed**

## STANDARD FEATURES

- Casters
- · Digital thermometer
- · Ducted air distribution
- · Field reversible door · Full length stainless steel
- handles Incandescent interior light
- Key locks
- Magnetic gasketing
- Nickel chrome shelves
- Operating temperature: To 200° F
- · Polyurethane insulation
- Stainless steel exterior
- Stainless steel interior • UL, C-UL & UL Sanitation
- listed\*\* • Warranties: 90 day labor plus 1 year parts

## **OPTIONAL FEATURES\***

- · Alarm systems
- Bun pans
- · Extra shelves
- · Half solid doors
- · Legs in lieu of casters · Patterned stainless steel,
- dent resistant doors
- Stainless steel pan slides · Warranties: 1 year
- service




ATED PASS-THRU CABINE


SPECIFICATION

GUIDE

\* Most options are available two weeks from receipt of order. Please contact us for specific questions.
\*\*C-UL is Underwriters Laboratories Safety Certification Mark which indicates that UL has tested the equipment to applicable CSA Standards.
\*\*UL Sanitation is Underwriters Laboratories Sanitation Mark which indicates that UL has tested the equipment to applicable NSF Standards.



PW252




81 1/2"


76 3/4"

#### SPECIFICATIONS

PW554







Crated Height	81"	81"
Crated Width	31"	59"
Crated Depth	40-1/2"	40-1/2"
Crated Weight (lbs)	350	550
Interior Height	59"	59"
Interior Width	23-1/2"	51"
Interior Depth	32"	32"
Overall Height*	81-1/2"	81-1/2"
Overall Width	27-1/2"	55"
Overall Depth	37-3/4"	37-3/4"
Gross Cubage (ft.3)	25.6	55.7
Number of Shelves	3	6
Shelf Area (sq. ft.)	16.5	35.4
Number of Casters	4	4
Number of Legs (Optional)	4	4
Heater Wattage	1500	3000
Electrical Characteristics	115/60/1	115/208-230/60/1
Cord & Plug Furnished	Yes	No
Maximum Fuse Size	20	20
NEMA Plug Configuration	5-20P	N/A
Total Amp Draw	12.5	15.2

PW252

Specifications subject to change without notice.

<sup>81</sup> <sup>1/2</sup> \* The overall heights shown in the table and drawings are with casters. With 6" legs the overall height is 82-3/4".

SMALL BUSINESS & WOMAN OWNED





Revision Date: 7/00 NOR-LAKE, INC. 2000 Printed in the U.S.A. Part Number: 117511

PW554

FRONT

SIDE