

Perlick® **REMOTE BACK BAR REFRIGERATOR**
2- AND 4-DOOR, SLIDING



SDBR48 shown

JOB	
AREA	
ITEM NO.	
MODEL NO.	

SDBR48	2-Door Model
SDBR96	4-Door Model



MODEL NUMBERS		SDBR48	SDBR96
NUMBER OF DOORS		2	4
EXTERIOR CABINET DIMENSIONS	Length - in. (mm)	48 (1219)	96 (2438)
	Depth - in. (mm)	24.75 (629)	24.75 (629)
	Height - in. (mm)	34.565 (878)	34.565 (878)
INTERIOR CABINET DIMENSIONS	Length - in. (mm)	44 (1118)	92 (2337)
	Depth - in. (mm)	18.75 (476)	18.75 (476)
	Height - in. (mm)	28.5 (724)	28.5 (724)
INTERNAL VOLUME Net. Cu. Ft. (Litres)		15.3 (433)	32.6 (923)
PRODUCT CAPACITY	CASE PACKED - 12 OZ. BOTTLE/CAN	267/465	617/1025
	STAGGERED - 12 OZ. BOTTLE/CAN	288/488	667/1102
SHIPPING WEIGHT Lbs. (kg.)		264 (120)	447 (203)
ELECTRICAL SPECIFICATIONS	Electrical Supply	120 VAC/60 Hz/1 Ph	120 VAC/60 Hz/1 Ph
	Running Load Amps	1.6	2.5
	Electrical Connection	Hard wired	Cord connected
	Defrost Initiation	Automatic	Automatic
	Defrost Type	Off cycle	Off cycle
	Lighting Type	LED	LED
REFRIGERATION SPECIFICATIONS	Horsepower	1/4	1/3
	Expansion Device	TXV	TXV
	Evaporator Capacity - Remotes	1900 Btu/Hr @ 20° F Evaporator	2300 Btu/Hr @ 20° F Evaporator
	Remote Refrigerant Options	R134a & R22 & R404a	R134a & R22 & R404a
PLUMBING	Evaporator Condensate	Field plumbed	Field plumbed

Perlick® **REMOTE BACK BAR REFRIGERATOR**
2- AND 4-DOOR, SLIDING

Note: Open floor drain not provided on models intended for non-packaged food.

