STANDARD ICE CHESTS (FULL DEPTH) WITH COLD PLATE

MODELS

TSF Series

□ TSF18IC10



Perlick Features

- Patented design conceals cold plate under liner for improved sanitation
- Dent resistent ABS top ledge
- Stainless steel legs install without tools and have "Rust Free" thermoplastic feet
- · New slim width design with cold plate




Form No. IC09

Size and Specifications


18" Standard Ice Chests (Full Depth) with Cold Plate


Job	
Area	
Item No.	
Model No	

MODEL NOS.	TSF18IC10
LENGTH IN. (mm)	18" (457)
ICE CAP. lbs. (kg)	45 (25)
SHIP WT. lbs. (kg)	130 (75.5)
FRONT & SIDES	Stainless steel, top rim ABS
BACKSPLASH	Stainless steel 6" high (4" optional) with 1" return at top, mechanically fastened and sealed to ice chest top with steel support brackets
BACK & BOTTOM	Galvanized steel
INTERIOR	Stainless steel with 1/4" radius corners, welded and sealed with non-exposed cold plate. Interiors can be divided with freestanding ice dividers
INSULATION	Foamed-in-place polyurethane
LEGS	1-5/8" tubular, stainless steel with 1" adjustable thermoplastic foot
PLUMBING	Drain connection – 1/2" NPS male
COLD PLATE	Cast aluminum plate concealed under ice chest liner. Cold plate has 2 full-length circuits and 8 half-length circuits. Connections – 5/16" O.D. stainless steel tubing with swagged end to accept standard 1/4" I.D. beverage tubing
OPERATING SPECIFICATIONS	Each full circuit will deliver four, 6 oz drinks per minute at 40° continuously, or 40 oz. every three minutes in a single draw (Flow rate 2 oz./sec, 75° ambient, 75° product).
ACCESSORIES	Cover (stainless steel, two-piece, removable), Ice Divider, 2-Piece Cover, Bottle Wells, Condiment Trays



Note: Covers not included. Soda Chase not applicable; soda lines must be routed behind adjacent equipment.





Form No. IC09 Rev. 07.19.2011



8300 West Good Hope Road • Milwaukee, WI 53223 • Phone 414.353.7060 • Fax 414.353.7069 Toll Free 800.558.5592 • E-Mail perlick@perlick.com • www.perlick.com