




portable.
stackable.
storable.

EventXpress™ Portable Dance Floor

SPECIFICATION



Dance Floor Unit

- Plywood results in a lighter weight panel than particleboard plus provides superior warping protection thus allowing floor to be used outside as well as in high humidity environments
- Panels are cut and routed by “CNC” computer for precision sizing and fit with every panel

Panel Unit Core

- Dance floor core is constructed of 18MM calibrated exterior glue plywood with “bb” face and “cc” back. Meets California Air Resources Board’s Phase 2 Formaldehyde Emissions Standards.

Surface

- Each 1/8” thick commercial grade vinyl flooring tile is vacuum formed to the plywood core
 - Vacuum forming results in a smoother, tighter surface than glue or laminating
 - Permits the floor to be used outdoors as well as indoors
- Parquet Floors feature a true wood surface with either a light or dark Windsor finish

Surface Finish

- Each panel is pre-finished at the factory
- Bottom of panels are coated with an ultra-violet light cured polyurethane for protection from moisture

Border Trim

- Trim is tongue and groove, approximately 5” wide, heavy aluminum design with an 11° bevel and a straightened surface that meets all current safety requirements
- Two “slot-head” or “allen-head” screws are used to secure panels and trim pieces together quickly and tightly
- Finish on all trim is silver anodized

Cam-Lock Panel Interconnection (optional)

- Panel connection
 - Panels are connected with a full length extruded aluminum tongue and groove interlocking system with a male/female engagement.
 - Each panel has two (2) male sides and two (2) female sides
- Vertical Control
 - Full-length tongue and groove design prevents panels from moving in an up and down fashion
- Lateral Control
 - Each panel has a positive engagement system in the lock area that prevents the panels from sliding side to side
- Panel Lock
 - Panels are fastened together with Cam-Locks operated by a 7/32” hex key
 - Cam lock uses a 0.205” metal wire hook to engage the receiver machined in the female extrusion
 - There is one (1) cam lock on each male side for a total of two (2) cam-locks per panel
 - When engaged the cam locks maintain a clamping force of 450 lbs

Warranty

PS Furniture™ warrants that its EventXpress indoor/outdoor portable dance floors shall be free from defects in original materials and workmanship for a period of five years from the original shipment date. Warranty on sales for rental use is limited to one year. This warranty shall not apply to normal wear and tear or in the event products are damaged as a result of misuse, abuse, vandalism, neglect, accident, improper application and modification or repair by persons not authorized by PS Furniture. The company will, at its discretion, repair or replace any defects. Any repair or replacement must be approved in advance by the factory before any action is taken. There are no implied warranties of fitness or merchantability, and there are no other express warranties beyond the warranties expressed here.