




portable.  
stackable.  
storable.

## MAXX Edge® Laminate Round NS Table

### SPECIFICATION



#### 60" diameter and 72" diameter

##### Table Tops

- Table core is constructed of 18MM calibrated exterior glue plywood with "bb" face and "cc" back. Meets California Air Resources Board's Phase 2 Formaldehyde Emissions Standards.
- Laminate surface is a WilsonArt® high-pressure laminate
  - Meets or exceeds NEMA specifications
  - GREENGUARD® Indoor Air Quality Certified
  - Wood fiber content constructed of a minimum 20% post-consumer waste paper (SCS certified)
  - Laminate surface for 72" dia. models is made with two (2) sheets of laminate and there is a visible seam in the middle of the surface
- Backer sheet is phenolic material, color black
  - Constructed of a minimum 30% recycled pre and post-consumer mix (SCS certified)

##### Top Support

- Table tops supported with a 16 gauge, 1 13/16" deep formed cold rolled steel channel apron
  - Apron is securely fastened with #12 5/8" wood screws every 8-10"
- Four (4) patented plastic corner leg mounting devices each made with one (1) stacking bumper to prevent laminate damage in storage

##### Molded Edge

- Table features a poured urethane elastomer edge system designed for specialty molding applications
- Edge has a 3/8" radius, half round shape
- Edge color is black
- Edge is mechanically bonded to the table top and flush with the top and bottom surfaces (no gaps)
- Edge is seamless
- Edge has good color stability and mar resistance, with a tensile strength (ASTM D412) of 1,480 psi and durometer of 95 Shore A

##### Legs

- Legs are non-sequential style, manufactured with cold-rolled 16 gauge, 1" diameter powder coated steel tubing
  - Non-sequential legs both fold flat against the bottom of the table and underneath the apron's edge
  - For extra strength, steel horizontal cross-bars (tubing) are inserted fully into each vertical tubing component and joints are hand welded around the entire circumference of the joint
  - Each folding leg hinge secured to table top with six (6) #12 5/8" wood screws
  - All rivet are solid steel and all joints are hand welded
  - Vertical tubing rests on four non-marking plastic glides
  - Locking mechanism is a drop-ring gravity lock
- Four (4) patented plastic corner leg mounting devices hold legs securely
  - Each corner screwed to table top with five (5) #12 1-3/4" wood screws
  - Each cross-bar end secured by a plastic corner
- Standard table height is 30" from floor to top of table surface

##### Metal Finish

- All metal parts are treated for corrosion resistance and paint adhesion
- Metal surfaces are finished with a baked on black epoxy powder coating for superior resistance to abrasion, marring & scratching

##### Warranty

PS Furniture warrants that its Classic Series Laminate Tables shall be free from defects in original materials and workmanship for a period of five years from the original shipment date. Warranty on sales for rental use is limited to one year. This warranty shall not apply to normal wear and tear or in the event products are damaged as a result of misuse, abuse, vandalism, neglect, accident, improper application and modification or repair by persons not authorized by PS Furniture. The company will, at its discretion, repair or replace any defects. Any repair or replacement must be approved in advance by the factory before any action is taken. There are no implied warranties of fitness or merchantability, and there are no other express warranties beyond the warranties expressed here.