



PRODUCT SPECIFICATION - page 1 of 1

Wedding Classic™ Resin Folding Chair

Model # C450



Date Modified: 08-04-2009

Construction

- Solid resin chairs designed for indoor/outdoor use that never need painting
 - Chairs may be exposed to rain, humidity, and sunlight with no adverse esthetic impact to the resin outer skin
- The structural solid resin has an outer smooth all weather resistant aesthetic skin
 - The inner expanded closed cell modified resin core contains high mechanical resistance, behaving like a bone and giving exceptional strength to the chair
- The solid outer material, with the UV protection imbedded in the resin, guarantees a premium aesthetic finish that is resistant to the prolonged effects of UV rays, and temperature extremes, without turning yellow or gray
 - Bi-component resins yield a superior, premium quality product with a longer life than that of similar products manufactured using the conventional, single component injection molding process, or less expensive chairs that use both resin and ABS plastic in their designs

Dimensions

- Model 450 chairs feature a 13 ½ inch deep x 15 inch wide, removable, vinyl padded seat positioned at 17 ½ inch standard dining height
- Chair is 31 inches tall in folded out position
- Storage dimensions are 17 ¼ inches wide X 35 inches long X 2 ¼ inches deep
- Each chair weighs 10 pounds

Stacking & Storage

- Chairs stack together via a patented “interlocking system”
- Chairs may be stacked 25 high

Load Bearing Capacity

- The load on the seat is distributed on the two bars supporting the seat itself, and therefore it is not concentrated on the pivoting screws as it happens on competing chairs
- The Model 450/440 chair has been independently tested and carries a proven 300 # load bearing capacity

Warranty

PS Furniture™ warranties that all Wedding Classic™ resin chairs will be manufactured with quality materials and workmanship. PS Furniture™ further agrees to repair or replace promptly any parts that by reason of defective materials or workmanship fail under normal use for a period of 3 years from the date of acceptance. Warranty for rental companies is 1 year. All warranty issues are subject to management approval and are deemed prorated.