



General Construction

- Transport cart shall be a completely welded assembly
- Casters shall be bolted to cart base caster plate mounts
- Handle shall be connected to cart by inserting unit into handle bracket vertically
 - Handle shall be removable
 - o Handle can be secured into handle bracket with 5/16" x 2" pin
 - Handle shall be 38" high from floor to top
 - o Handle shall have a push/pull safety handle which will be welded to the vertical handle
 - Safety handle shall protrude 6" out from vertical handle tubing
- Cart shall be finished with an epoxy powder coating
- The color shall be Black

Capacities

- 12 rectangular tables (30"x72" or 36"x72") stacked horizontally
- 12 seminar tables (18"x72" or 24"x72") stacked horizontally

Dimensions

- Overall dimensions shall be 81.0"L x 31.5"W x 38.0"H
 - These dimensions include the cart handle
- Transport cart base dimensions shall be 74.5"L x 31.5"W

Cart base frame construction

- Outside frame brace: 3/16" x 2" x 2" steel angle iron
- Lateral frame brace: 3/16" x 2" x 2" steel angle iron
- End handle/swivel caster frame brace: 3/16" x 7/8" x 1 3/8" steel angle iron
- Caster plate mounts: 6" x 6.5" x 8 gage caster mounts welded to lateral frame brace steel angle iron
- Handle tubing: 1.25" diameter, 16 gauge steel tubing
- Handle brackets: 1 9/16", 10 gauge round steel tubing

Standard Casters

- Casters shall be weight rated to hold 650 pounds each / 2,600 pounds per cart
- Standard casters shall be (4) 5" diameter x 2" width, phenolic composition material, axle roller bearings, and axle grease fittings attached
- Fixed casters (2)
 - o Each caster shall be affixed to caster mount plate by grade 8, 3/8" 16 x 3/4" bolt with 3/8" locking nuts
- Swivel casters (2)
 - o Each caster shall be affixed to caster mount plate by grade 8, 3/8" 16 x ¾" bolt with 3/8"-16 lock nuts

Warranty

PS Furniture[™] warrants that all transportation carts will be new and manufactured with quality materials and workmanship. PS Furniture[™] further agrees to replace promptly any part or parts which by reason of defective material or workmanship shall fail under normal use for a period of 3 years from date of acceptance. Warranty for rental companies is 1 year. Cart casters are warranted for a period of one year. All warranty issues are subject to management approval and are deemed prorated.