



PRODUCT SPECIFICATION - page 1 of 1



Transportation Cart
Model # RTC



Date Modified: 02-19-2008

General Construction

- Transport cart shall be a completely welded assembly
- Casters shall be pressed into the handle support uprights
- Cart shall have two vertical support railings to allow for round or rectangular tables to “lean” against for maintaining tables within cart base
 - The railings shall be affixed to the outside frame brace
 - Railings shall be 38” wide and 42” high from floor to railing top
 - Railings shall be removable to accommodate any number of storage configurations
- Cart shall be finished with an epoxy powder coating
- The color shall be Dark Neutral

Capacities

- 8-12 round tables (48”, 60”, 66”, 72”) stacked vertically
 - (8) 100 Series tables
 - (12) 200 Series or PROFILE Series tables with the Space Saver leg
- 10 rectangular tables (18”x72”, 24”x72”, 30”x72”, 36”x72”) stacked vertically (2.875” width)

Dimensions

- Overall dimensions shall be 38.5”L x 32.75”W x 42.0”H
- Transport cart base dimensions shall be the same

Cart base frame construction

- Outside frame brace: (2) 14 gauge, 1 x 2 steel rectangular tubes
- Lateral frame brace: (4) double 14 gauge x 1.25” tubular steel braces
- End handle/swivel caster frame brace: (2) double rail receptacles to accommodate single rail/handle post at each cart corner shall be 5.5”x1 9/16” OD, 10 gauge round steel tubing
- Caster mounts: .812” friction ring caster stem shall be pressed into lower handle support
- Cart railings: 1.25” diameter, 16 gauge steel tubing
- Railing brackets: 1 9/16”, 10 gauge round steel tubing

Standard Casters

- Casters shall be weight rated to hold 255 pounds each / 1020 pounds per cart
- Standard casters shall be (4) 4” diameter x 1.25” width “duraform” swivel

Warranty

PS Furniture™ warrants that all transportation carts will be new and manufactured with quality materials and workmanship. PS Furniture™ further agrees to replace promptly any part or parts, which by reason of defective material or workmanship shall fail under normal use for a period of 3 years from date of acceptance. Cart casters are warranted for a period of one year. Warranty for rental companies is 1 year. All warranty issues are subject to management approval and are deemed prorated.