



PRODUCT SPECIFICATION - page 1 of 1



Transportation Cart
Model # HD-SUD



Date Modified: 11-19-2008

General Construction

- Cart designed to fit through all standard height doors and elevators and accommodate standard size rectangular tables up to 36 inches wide and 96 inches in length
- Transport cart shall be welded in complete assembly
- Handle shall be 43" high from floor to top
 - Handle shall have a push/pull safety handle which will be welded to the vertical support bars
 - Safety handle shall protrude a minimum of 6" out from vertical handle tubing to protect operator
- Transport cart shall have both vertical and horizontal steel/angle iron support railings for rectangular tables to "lean" against for maintaining tables within cart base
 - The two outside railings shall be welded to the outside frame brace
- Cart shall be finished with a black, epoxy powder coating painted finish

Capacities

- 6-8 rectangular tables 18-36 inches wide--- stacked vertically (internal storage width of 30 inches)

Dimensions

- Overall dimensions shall be 45" L x 30" W x 60"H
 - These dimensions include the cart handle
- Storage footprint dimensions shall be 62" L x 30" W

Cart base frame construction

- Outside & lateral frame braces: 3/16" x 2" x 2' steel angle iron
- Cart railings: 1.5" diameter, 16 gauge steel tubing
- Railing brackets: 1 9/16", 10 gauge round steel tubing
- Handle tubing: 1.5" diameter, 16 gauge steel tubing

Standard Casters

- Combination of two each fixed 10" diameter semi-pneumatic casters and tow each swivel 4" diameter standard phenolic casters
- Casters shall be weight rated to hold 300 pounds each
- Standard casters shall be (2) 4" diameter x 2" width, phenolic composition material, axle roller bearings, and axle grease fittings attached
- Casters shall be affixed to caster mount plate by grade 8, 3/8" - 16 x 3/4" bolt with 3/8" locking nuts

Warranty

PS Furniture™ warrants that all transportation carts will be new and manufactured with quality materials and workmanship. PS Furniture™ further agrees to replace promptly any part or parts which by reason of defective material or workmanship shall fail under normal use for a period of 3 years from date of acceptance. Cart casters are warranted for a period of one year. Warranty for rental companies is 1 year. All warranty issues are subject to management approval and are deemed prorated.