


Direct drive, 1.5 H.P., single phase motor with magnetic safety system and motor brake for user safety.

Control panel with push button "On-

Standard Unit packed with two processing discs (27566, 4mm (5/32") slicing disc & 27577, 2mm

4 Qt. stainless steel cutter bowl with handle, see-thru lid with

introduction port which allows user to add ingrediants while processing



robot A coupe

Dual- Purpose Food Processor with Mixer-Cutter Bowl Attachment and Continuous Feed Vegetable Prep

Attachment



Prepare 800 servings in 2 1/2 hours or less.

Bowl attachment designed for vertical cutting and mixing: **mix**, **chop**, **puree** and **blend**. Vegetable prep attachment specially designed for quality continuous feed: **slicing**, **dicing**, **shredding**, **grating**, **french fry** and **julienne**. Accommodates 21 different discs.

and stainless steel smooth edge "S" blade.
Stainless steel Veg Prep attachment with ABS plastic lid and two introduction ports.

Metal motor base.

Off" and pulse switches.

(5/64") grating disc).

- Complete selection of 21 stainless steel discs available to accommodate a large range and variety of cuts.
- Attachments easily removed for easy cleaning and optimum sanitation.
- 1 year parts and labor warranty.

Robot Coupe U.S.A., Inc. P.O. Box 16625 Jackson, MS 39236-6625 1-800-824-1646 • (601) 898-8411

FAX: (601) 898-9134

www.robotcoupeusa.com • e-mail: info@robotcoupeusa.com

SPECIFICATIONS ON REVERSE SIDE





R401

"The Inventor & World Leader in Food Processors"

Commercial Food Processor

Specifications

STANDARD MODEL: Includes motor base unit with continuous feed attachment, one 27566 - 5/32" (4mm) slicing disc and one 27577 5/64" (2mm) medium grating disc, 4 Qt. stainless steel cutter bowl with stainless steel smooth "S" blade.

ELECTRICAL REQUIREMENTS: 120V, 60Hz, 7.2 Amps, single phase. Contact your local electrician for local code requirements. NEMA 5-15 Plug.

SWITCHING: Control panel with push-type on and off and pulse buttons.

MOTOR: 1.5 HP, 1725 RPM, direct-drive, fan-cooled.

WEIGHT: 39 lbs. net, 42 lbs. approximate shipping weight.

Slicing Discs

27051 - 1/32" (1mm) 27555 - 5/64" (2mm) 27086 - 1/8" (3mm) 27566 - 5/32" (4mm)

27087 - 3/16" (5mm)

27786 - 1/4" (6mm)

Ripple Cut Slicers

27621 - 5/64" (2mm)

Graters

27588 - 1/16" (1.5mm) 27577 -5/64" (2mm) 27511 - 1/8" (3mm)

Pulping

27079 - Fine pulping disc 27764 - Pulping disc

Julienne

27599 - 5/64" (2x2mm)

27080 - 5/64" x 5/32" (2x4mm)

27081 - 5/64"x1/4" (2x6mm)


27047 - 5/32" (4x4mm)


27610 - 1/4" (6x6mm)


27048 - 5/16" (8x8mm)

OPTIONAL EQUIPMENT: 19 additional processing discs, and single or multiple disc rack or wall-mounted disc rack.


STANDARDS: ETL electrical & sanitation, cETL (Canada)








Continuous Feed Unit





Robot Coupe U.S.A., Inc.

P.O. Box 16625 Jackson, MS 39236-6625 1-800-824-1646 (601) 898-8411 FAX: (601) 898-9134

FAX: (601) 898-9134 www.robotcoupeusa.com e-mail: info@robotcoupeusa.com

Distributed by: