



**MS-150**



**MS-250**



**MS-355**

Eliminate the long waits for preparing hot menu items. The Miracle Steamer uses plain tap water to heat and cook foods. The generator converts water into super-heated dry steam for intense top-down heat that cooks and finishes foods while maintaining the original textures, colors, flavors, and nutrients.

The Miracle Steamer includes two steaming options. For instant steam that quickly reheats items or melts cheese, a simple push button releases dry, super-heated steam into the food chamber. Because the steam is released from the top of the food chamber, heat penetration is very efficient and fast. For items that require longer steaming times, a programmable time cycle is also provided.

NOTE: Units with a direct water hookup require a water pressure regulator. The psi should be between 20 and 30.

## Features

- Top-down steamer with spatula or drawer.
- Stainless steel construction.
- Programmable steam cycle.
- Instantly turns plain tap water into super-heated dry steam.
- Ideal for melting cheese, reheating and steaming a variety of food items.
- Quick and easy clean up.
- Models available with either a self-contained water reservoir or direct water hookup.



Model & Mfg. No.	Width	Depth	Height	Shipping Width	Shipping Depth	Shipping Height	Shipping Weight	Volts	Watts	Amps	Hertz	Plug Description
<b>Spatula Style with Self-Contained Water Reservoir (side)</b>												
MS-150 9100420	21" (533 mm)	21 3/8" (543 mm)	10 1/4" (260 mm)	28" (711 mm)	16" (406 mm)	24" (610 mm)	58 lbs. (26 kg)	208	3300	15.9	50/60	NEMA 6-20P 20 Amp., 250 Volt
MS-150 9100423	21" (533 mm)	21 3/8" (543 mm)	10 1/4" (260 mm)	28" (711 mm)	16" (406 mm)	24" (610 mm)	58 lbs. (26 kg)	120	1800	15	50/60	NEMA 5-15P 15 Amp., 120 Volt
MS-150 9100426	21" (533 mm)	21 3/8" (543 mm)	10 1/4" (260 mm)	28" (711 mm)	16" (406 mm)	24" (610 mm)	58 lbs. (26 kg)	230	3300	14.4	50/60	NEMA 6-20P 20 Amp., 250 Volt
MS-150 9100428	21" (533 mm)	21 3/8" (543 mm)	10 1/4" (260 mm)	28" (711 mm)	16" (406 mm)	24" (610 mm)	58 lbs. (26 kg)	230	3300	14.4	50/60	CEE 7/7 16 Amp., 250 Volt
<b>Spatula Style with Direct Water Hook-Up</b>												
MS-250 9100430	21" (533 mm)	21 3/8" (543 mm)	9 1/2" (241 mm)	28" (711 mm)	16" (406 mm)	24" (610 mm)	55 lbs. (25 kg)	208	3300	15.9	50/60	NEMA 6-20P 20 Amp., 250 Volt
MS-250 9100436	21" (533 mm)	21 3/8" (543 mm)	9 1/2" (241 mm)	28" (711 mm)	16" (406 mm)	24" (610 mm)	55 lbs. (25 kg)	230	3300	14.4	50/60	NEMA 6-20P 20 Amp., 250 Volt
MS-250 9100438	21" (533 mm)	21 3/8" (543 mm)	9 1/2" (241 mm)	28" (711 mm)	16" (406 mm)	24" (610 mm)	55 lbs. (25 kg)	230	3300	14.4	50/60	CEE 7/7 16 Amp., 250 Volt
MS-250 9100439	21" (533 mm)	21 3/8" (543 mm)	9 1/2" (241 mm)	28" (711 mm)	16" (406 mm)	24" (610 mm)	55 lbs. (25 kg)	120	1800	15	50/60	NEMA 5-15P 15 Amp., 120 Volt
<b>Drawer Style with Self-Contained Water Reservoir (side)</b>												
MS-155 9100450	21" (533 mm)	17 1/4" (438 mm)	10 1/4" (260 mm)	28" (711 mm)	16" (406 mm)	24" (610 mm)	60 lbs. (27 kg)	208	3300	15.9	50/60	NEMA 6-20P 20 Amp., 250 Volt
MS-155 9100452	21" (533 mm)	17 1/4" (438 mm)	10 1/4" (260 mm)	28" (711 mm)	16" (406 mm)	24" (610 mm)	60 lbs. (27 kg)	120	1800	15	50/60	NEMA 5-15P 15 Amp., 120 Volt
MS-155 9100456	21" (533 mm)	17 1/4" (438 mm)	10 1/4" (260 mm)	28" (711 mm)	16" (406 mm)	24" (610 mm)	60 lbs. (27 kg)	230	3300	14.4	50/60	NEMA 6-20P 20 Amp., 250 Volt
MS-155 9100458	21" (533 mm)	17 1/4" (438 mm)	10 1/4" (260 mm)	28" (711 mm)	16" (406 mm)	24" (610 mm)	60 lbs. (27 kg)	230	3300	14.4	50/60	CEE 7/7 16 Amp., 250 Volt
<b>Drawer Style with Direct Water Hook-Up</b>												
MS-255 9100460	21" (533 mm)	17 1/4" (438 mm)	9 1/2" (241 mm)	28" (711 mm)	16" (406 mm)	24" (610 mm)	60 lbs. (27 kg)	208	3300	15.9	50/60	NEMA 6-20P 20 Amp., 250 Volt
MS-255 9100462	21" (533 mm)	17 1/4" (438 mm)	9 1/2" (241 mm)	28" (711 mm)	16" (406 mm)	24" (610 mm)	60 lbs. (27 kg)	120	1800	15	50/60	NEMA 5-15P 15 Amp., 120 Volt
MS-255 9100466	21" (533 mm)	17 1/4" (438 mm)	9 1/2" (241 mm)	28" (711 mm)	16" (406 mm)	24" (610 mm)	60 lbs. (27 kg)	230	3300	14.4	50/60	NEMA 6-20P 20 Amp., 250 Volt
MS-255 9100468	21" (533 mm)	17 1/4" (438 mm)	9 1/2" (241 mm)	28" (711 mm)	16" (406 mm)	24" (610 mm)	60 lbs. (27 kg)	230	3300	14.4	50/60	CEE 7/7 16 Amp., 250 Volt
<b>Drawer Style with Self-Contained Water Reservoir (front)</b>												
MS-355 9100480	25 1/4" (641 mm)	17 1/4" (438 mm)	10 1/4" (260 mm)	33" (838 mm)	17" (432 mm)	24" (610 mm)	65 lbs. (29 kg)	208	3300	15.9	50/60	NEMA 6-20P 20 Amp., 250 Volt
MS-355 9100482	25 1/4" (641 mm)	17 1/4" (438 mm)	10 1/4" (260 mm)	33" (838 mm)	17" (432 mm)	24" (610 mm)	65 lbs. (29 kg)	120	1800	15	50/60	NEMA 5-15P 15 Amp., 120 Volt
MS-355 9100483	25 1/4" (641 mm)	17 1/4" (438 mm)	10 1/4" (260 mm)	33" (838 mm)	17" (432 mm)	24" (610 mm)	65 lbs. (29 kg)	120	1800	15	50/60	NEMA 5-20P 20 Amp., 120 Volt
MS-355 9100486	25 1/4" (641 mm)	17 1/4" (438 mm)	10 1/4" (260 mm)	33" (838 mm)	17" (432 mm)	24" (610 mm)	65 lbs. (29 kg)	230	3300	14.4	50/60	NEMA 6-20P 20 Amp., 250 Volt

NOTE: Water Pressure Regulator required on MS-250 and MS-255 units.

P/N 1020227 Rev. L 12/12