SAVE WATER. SERVE BETTER.

CONSERVEWELL™ UTENSIL HOLDER

Holds serving utensils above 140°F, keeping them safe against bacteria growth - environmentally smart and economically sound alternative to traditional dipper well perpetual-flow sinks

Convenient key slot mounting brackets make removal for cleaning quick and easy, mounts to a wall or sturdy vertical surface



GALLONS PER YEAR*

timer helps ensure timely

water changeouts; also available without timer



*52 weeks at 7 days per week at 12 hours per day. Average water and sewer rate of \$9.48 per 1,000 gal.



1.800.558.8722 ConserveWell-NotDipperWell.com













CONSERVEWELL™ Model CW

Application

- Replace a traditional dipper well perpetual-flow sink to save water, energy and money
- Mount next to a serving station to keep utensils clean and handy

Fast Facts

Environmentally friendly method of protecting utensils against bacteria growth versus traditional dipper wells; one unit can save over 250,000 gallons of water per year.

The ConserveWell™ keeps (2) ¹/9-size pans of serving utensils above 140°F, keeping them safe while saving water, energy and money.

Unit is mountable to a wall or sturdy vertical surface using key slot holes on back plate.



CLEAN HAS NEVER BEEN MORE GREEN.

CONSERVEWELL™


Model CW

Specifier Statement

Unit will be a Server Products Model CW ConserveWell™ designed to hold utensils above 140°F as an alternative to a perpetual-flow dipper well. Unit comes with (2) stainless steel ¹/₀-size pans 4" deep and is mountable to a wall or sturdy vertical surface using key slot holes on back plate. Models available with and without adjustable countdown timer. Timer model has an LED display and a volume adjustable alarm for water changeout notifications. NSF listed. C-UL-US listed. Two-year warranty. Made in the USA. Ships FOB Richfield, WI 53076.

ConserveWell™ Product Codes

| ConserveWell [™] with Timer | CW | 87750 |
|--|----|-------|
| ConserveWell™ without Timer | CW | 87740 |
| ¹ / ₉ -size pan, 4" Includes (2) | | 90106 |



Specifications

| Part Number | Dimensions (height x width x depth) | Capacity | Weight (with water in pans) | Electrical |
|----------------|--|---|-----------------------------|------------------------|
| 87750 | 10 ⁵ / ₈ " x 15 ¹ / ₄ " x 5 ¹ / ₄ " 27 x 38.7 x 13.3 cm | (2) ¹ /9-size pans 4" (150 mm) deep | 19 lbs 8.6 kg | 120V - 400W 3.3A |
| 87740 | 7 ⁵ / ₁₆ " x 15 ½" x 5 ½" 18.6 x 38.7 x 13.3 cm | | 15 lbs 6.8 kg | |

Plug is NEMA 5-15P with 72" (183 cm) or 108" (274 cm) cord







Related Item

Another option for replacing a traditional dipper well perpetual-flow sink is the Drop-In model that fits into most existing counter cut-outs. Unit includes (1) stainless steel inset and is available with or without a countdown timer.

ConserveWell[™] Drop-In with Timer CW-DI 87770

ConserveWell[™] Drop-In without Timer CW-DI 87760



CW-DI 87770

