

COMBITHERM®
CTC6-10E
ELECTRIC BOILER-FREE



CAPACITY

- Six (6) full-size or GN 1/1 pans, six (6) half-size sheet pans; one row deep
- Two (2) side racks with six (6) non-tilt support rails; 13" (330mm) horizontal width between rails, 2-3/4" (70mm) vertical spacing between rails

CONSTRUCTION

- Stainless steel exterior, bright annealed interior
- Seamless welded interior stainless steel cavity
- CoolTouch³™ triple pane window door with hinged inner glass prevents additional heat loss and increases cooking efficiency
- Door is hinged right with a 130° swing
- High efficiency LED lighting integrated in the door
- Door mounted self-draining drip tray
- Hands free positive catch door handle with lighted visual alerts [PATENT PENDING]
- PROrinse™ ergonomic retractable hand shower includes a safety shutoff interlock that shuts off water to the hose [PATENT PENDING] and a built-in back flow preventer
- SafeVent™ provides automatic steam venting at the end of the cooking cycle [PATENT #7,282,674]
- Zero Clearance system maximizes floor space utilization with features that carefully protect temperature sensitive components and controls [PATENT PENDING]
- Adjustable stainless steel legs provide stability

CT CLASSIC™ STANDARD FEATURES

- Oven with state-of-the-art innovative solutions that meld together perfectly to deliver high performance standards, consistent food quality, and production efficiency.
- Classic control provides a simple and intuitive push button operation that commands all the oven functions with icons that are easy to identify.

- LED display indicates cooking mode, temperature settings, time remaining, and various instructions.
- Three cooking modes:
 Steam - 85°F to 250°F (30°C to 120°C)
 Convection - 85°F to 575°F (30°C to 300°C)
 Combination - 212°F to 575°F (100°C to 300°C)
- Cook time is displayed in hours : minutes.

- Two different fan speeds expands cooking capabilities for products affected by a high velocity of air movement.
- Cool down feature provides the operator with the ability to lower the temperature of the oven compartment at an accelerated pace.
- CombiClean® fully automated cleaning with one heavy-duty cleaning cycle.

SHORT FORM SPEC

Provide Alto-Shaam CombiTherm® CT Classic™ counter-top model CTC6-10E boiler-free electric CombiOven designed with EcoSmart® technology for reduced energy and water consumption. Includes operational modes for steam, convection, and a combination of steam and convection heat. Oven is to be constructed of 18 gauge stainless steel interior cavity. Oven includes an attached retractable hand shower spray hose with safety shutoff interlock

system and a back flow preventer. Classic control includes a cool-down function, automatic cleaning function, fan with two (2) fan speeds. Oven includes four (4) adjustable stainless steel legs. Each oven is to accommodate up to six (6) half-size sheet pans or six (6) full-size hotel pans (GN 1/1), include standard right-hand door hinging, six (6) non-tilt support rails, and three (3) stainless steel shelves.

FACTORY INSTALLED OPTIONS

Boiler Version

Electrical Choices

- 208-240V 3ph 380-415V 3ph
 440-480V 3ph

Door Swing

- Right-hand Door Hinging, standard
 Recessed Door, optional; increases oven width by 4" (102mm), slides out of the way for safety and frees up aisle space

CombiHood PLUS™ Ventless Hood (not available on stacked combinations)

Extended One-year Warranty

Installation Start-Up Check - AVAILABLE THROUGH AN ALTO-SHAAM AUTHORIZED SERVICE AGENCY

Probe Choices

- Removable, single-point, quick-connect core temperature probe, optional
 Removable, single-point, quick-connect sous vide temperature probe, optional


Security Devices for correctional facility use

- Optional base package: includes tamper-proof screw package, excludes temperature probe
 Anti entrapment device, optional
 Control panel security cover, optional
 Hasp door lock (padlock not included), optional
 Removable, single-point, quick-connect core temperature probe, optional
 Seismic feet package, optional

Stacking Hardware (not available with CombiHood PLUS Ventless Hood)



A= UNTREATED WATER
B= TREATED WATER
C= ELECTRICAL
D= WATER DRAIN



DIMENSIONS: H x W x D
EXTERIOR: 34-1/2" x 35-11/16" x 41-7/16" (876mm x 906mm x 1053mm)
EXTERIOR WITH RECESSED DOOR: 34-1/2" x 39-11/16" x 41-7/16" (876mm x 1008mm x 1053mm)
INTERIOR: 20-1/2" x 16-1/4" x 28-1/16" (520mm x 411mm x 712mm)

WATER REQUIREMENTS
TWO (2) COLD WATER INLETS - DRINKING QUALITY
ONE (1) TREATED WATER INLET: 3/4" NPT* * Can manifold off of one
ONE (1) UNTREATED WATER INLET: 3/4" NPT* 3/4" line.
LINE PRESSURE: 30 to 90 psi 2.1 to 6.3 bar
WATER DRAIN: 1-1/2" (40mm) CONNECTION WITH A 2" MINIMUM AIR GAP INSTALLED AS CLOSE TO THE OVEN AS POSSIBLE. MATERIALS MUST WITHSTAND TEMPERATURES UP TO 200°F (93°C).
CLEARANCE REQUIREMENTS
LEFT: 0" (0mm) 18" (457mm) FOR SERVICE ACCESS
RIGHT: 0" (0mm) NON-COMBUSTIBLE SURFACES 2" (51mm) COMBUSTIBLE SURFACES
TOP: 20" (508mm) FOR AIR MOVEMENT
BACK: 4" (102mm) BOTTOM: 5-1/8" (130mm) FOR LEGS, AIR INTAKE
INSTALLATION REQUIREMENTS
• Oven must be installed level. • Hood installation is required.
• Water supply shut-off valve and back-flow preventer when required by local code.

WATER QUALITY STANDARDS
It is the sole responsibility of the owner/operator/purchaser of this equipment to verify that the incoming water supply is comprehensively tested and if required, a means of "water treatment" provided that would meet compliance requirements with the published water quality standards published below. Non-compliance with these minimum standards will potentially damage this equipment and/or components and VOID the original equipment manufacturer's warranty. Alto-Shaam recommends using OptiPure® [www.optipurewater.com] products to properly treat your water.
Contaminant Inlet Water Requirements
Free Chlorine Less than 0.1 ppm (mg/L)
Hardness 30-70 ppm
Chloride Less than 30 ppm (mg/L)
pH 7.0 to 8.5
Silica Less than 12 ppm (mg/L)
Total Dissolved Solids (tds) 50-125 ppm

ELECTRICAL (NO CORD, NO PLUG - DEDICATED CIRCUIT REQUIRED) DO NOT CONNECT TO A G.F.I. OUTLET									
MODEL	VOLTAGE	PH	HZ	AMPS	kW	BREAKER	AWG	CONNECTION	
CTC6-10E	208 – 240	3	50/60	21.9 – 25.3	7.9 – 10.5	25 - 30	8	L1, L2, L3, G	
	380 – 415	3	50	13.4 – 14.6	9.0 – 10.5	16	8	L1, L2, L3, N, G	
	440 – 480	3*	60	11.6 – 12.6	9.0 – 10.5	15	10 – 8	L1, L2, L3, G	

*ELECTRICAL SERVICE CHARGE APPLIES

WEIGHT	SHIP DIMENSIONS	PAN CAPACITY	PRODUCT MAXIMUM:
NET 524 lbs est 238 kg	(L x W x H) 56" x 45" x 51"*	FULL-SIZE: 20" x 12" x 2-1/2" Six (6)	72 lb (33 kg)
SHIP 574 lbs* 260 kg*	(1422 x 1143 x 1295mm)*	GN 1/1: 530 x 325 x 65mm Six (6)	VOLUME MAXIMUM: 45 quarts (57 liters)
*DOMESTIC GROUND SHIPPING INFORMATION. CONTACT FACTORY FOR EXPORT WEIGHT AND DIMENSIONS.		*HALF-SIZE SHEET: 18" x 13" x 1" Six (6)	*ADDITIONAL WIRE SHELVES REQUIRED FOR MAXIMUM CAPACITY
		*ON WIRE SHELVES ONLY	