

### Mobile - Starter Units with Casters with Camguard™ antimicrobial

#### 5 Shelf Units, Vented Shelf Plates only

##### 2 Post Heights (with 5" (12,7 cm) Casters)

67" (170,2 cm) and 75" (190,5 cm)

##### 3 Shelf Widths

18" (45,7 cm), 21" (53,3) and 24" (61 cm)

##### 3 Shelf Lengths

36", 42", 48" (91,4 cm, 106,7 cm, 121,9 cm)



#### • Starter Unit includes:

- Two Post Kits for Mobile Units.
- Five Vented Shelf Kits.
- Four Premium or Standard Casters.

**\*Note:** For High Density Camshelving systems order 4 Premium Swivel Locking Casters by designating (HD) at the end of the Starter Unit product codes.

**Case Pack:** One carton contains all components to build one unit.

### Features & Benefits

#### Versatile Storage

Rolls smoothly into any environment, indoors or outdoors, including walk-in coolers and freezers, dry storage, wet areas or front of the house display. Works in temperatures down to -36°F (-30°C) or warm environments up to 190° F (88°C). Weldless and rust free.

#### Completely Mobile

Mobile Starter Units include two Premium Total Locking Casters and two Premium Swivel Locking Casters or two Standard Swivel Chrome Casters and two Swivel Chrome with Brake Casters. Premium Casters are made with a zinc plated post and non-marking polyurethane wheel. Premium Casters can be used in wet areas or in walk-in refrigerators and freezers. Standard casters are chrome plated and can be used for dry storage. Premium Swivel Locking Caster has a locking stem that locks in one direction for rigid positioning. Use four Swivel Locking Casters to create High Density Camshelving systems. The caster controls the direction the unit travels in, eliminating the need for stationary rail tracking. The Premium Total Locking Caster has a brake that locks both the motion and the swivel when set in place. Use two Total Locking Casters and two Swivel Locking Casters for standard Mobile Camshelving Units.

#### Easy to Clean

Camshelving shelf plates contain Camguard™ antimicrobial, a silver-ion technology that inhibits the growth of mold, fungus and bacteria that may cause odors, stains and product degradation. Camguard is incorporated throughout the shelf plate material so that it will never wash off or wear out. The shelf plates remove easily and can be placed in an open end Camrack® (OETR314) for washing. The traverses and post kits are smooth polypropylene so they can be wiped or steam cleaned. The traverses can be easily removed and washed in a conveyor dishwasher.

#### Easy to Assemble

Assembles in minutes with the use of a rubber mallet. Requires no bolts or nuts, clips or stainless steel connectors. Molded in dovetails on posts ensure that traverses set easily into place.

Item No. \_\_\_\_\_

Specifier Identification No. \_\_\_\_\_

Code No. \_\_\_\_\_

Quantity \_\_\_\_\_



Premium Casters.



Standard Casters.

#### Strong as Steel

Posts and traverses are made of a steel core coated with polypropylene. Uniquely engineered post connectors offer exceptional cross stabilization. Casters are made of reinforced nylon. Maximum weight-bearing capacity of 750 pounds (340 kg) per mobile unit.

#### Easy to Adjust

Requires use of rubber mallet. Shelves can be adjusted at 4" (10,2 cm) increments. Add a shelf to an existing unit by simply ordering the appropriate Shelf Kit.

#### Optional Accessories

Place the 3/2" (8,9 cm) rubber Donut Bumper over the top of the Caster before placing the Caster in the Post. Protects walls and other pieces of equipment from being damaged during mobile unit transport. Identification Tags clip easily onto traverses.

### Approvals



Components \* Does not include 6" (15 cm) Shelf Plate.

## Mobile - Starter Units with Casters 5 Shelf Units, Vented Shelf Plates only

### FIVE SHELF STARTER UNIT

for Mobile Camshelving includes two Post Kits for Mobile Units, five Vented Shelf Kits, two Premium Total Locking Casters and two Swivel Locking Casters or two Standard Swivel Chrome Casters and two Swivel Chrome with Brake.

#### 67" (170,2 cm) Height 18" (45,7 cm) Width

Premium caster code	Standard caster code	traverse in. cm	case lbs. (cube)	case kg. (cube m <sup>3</sup> )
CSUR58366	CSURS58366	36" 91,4	98.80 (5.90)	44,82 (0,1671)
CSUR58426	CSURS58426	42" 106,7	109.70 (5.90)	49,76 (0,1671)
CSUR58486	CSURS58486	48" 121,9	116.30 (5.90)	52,75 (0,1671)

#### 75" (190,5 cm) Height 18" (45,7 cm) Width

Premium caster code	Standard caster code	traverse in. cm	case lbs. (cube)	case kg. (cube m <sup>3</sup> )
CSUR58367	CSURS58367	36" 91,4	100.90 (5.90)	45,77 (0,1671)
CSUR58427	CSURS58427	42" 106,7	111.80 (5.90)	50,71 (0,1671)
CSUR58487	CSURS58487	48" 121,9	118.40 (5.90)	53,71 (0,1671)

#### 67" (170,2 cm) Height 21" (53,3 cm) Width

Premium caster code	Standard caster code	traverse in. cm	case lbs. (cube)	case kg. (cube m <sup>3</sup> )
CSUR51366	CSURS51366	36" 91,4	105.60 (7.17)	46,99 (0,2030)
CSUR51426	CSURS51426	42" 106,7	116.35 (7.17)	52,78 (0,2030)
CSUR51486	CSURS51486	48" 121,9	123.65 (7.17)	56,09 (0,2030)

#### 75" (190,5 cm) Height 21" (53,3 cm) Width

Premium caster code	Standard caster code	traverse in. cm	case lbs. (cube)	case kg. (cube m <sup>3</sup> )
CSUR51367	CSURS51367	36" 91,4	107.10 (7.17)	48,56 (0,2030)
CSUR51427	CSURS51427	42" 106,7	119.85 (7.17)	54,36 (0,2030)
CSUR51487	CSURS51487	48" 121,9	127.15 (7.17)	57,67 (0,2030)

#### 67" (170,2 cm) Height 24" (61 cm) Width

Premium caster code	Standard caster code	traverse in. cm	case lbs. (cube)	case kg. (cube m <sup>3</sup> )
CSUR54366	CSURS54366	36" 91,4	108.55 (8.50)	49,24 (0,2407)
CSUR54426	CSURS54426	42" 106,7	119.55 (8.50)	54,23 (0,2407)
CSUR54486	CSURS54486	48" 121,9	130.50 (8.50)	59,19 (0,2407)

#### 75" (190,5 cm) Height 24" (61 cm) Width

Premium caster code	Standard caster code	traverse in. cm	case lbs. (cube)	case kg. (cube m <sup>3</sup> )
CSUR54367	CSURS54367	36" 91,4	112.05 (8.50)	50,83 (0,2407)
CSUR54427	CSURS54427	42" 106,7	123.05 (8.50)	55,82 (0,2407)
CSUR54487	CSURS54487	48" 121,9	134.00 (8.50)	60,78 (0,2407)

**NOTE:** For High Density Camshelving systems order 4 Premium Swivel Locking Casters by designating (HD) at the end of the Starter Unit product codes.

### Architect Specs

- Posts:** Internal steel core, reinforced polypropylene exterior.
- Post Connectors:** Reinforced polypropylene.
- Traverses:** Internal steel core, reinforced polypropylene exterior.
- Vented/Solid Shelf Plates:** Reinforced polypropylene with Camguard™ antimicrobial.
- Premium Casters:** Reinforced nylon with zinc plated post and thermoplastic rubber wheels.
- Standard Casters:** Chrome plated with rubber wheels.

### Optional Accessories

- Donut Bumper for Caster** CSRDB **Color:** Dark Gray **Case pack:** 4 each
- Identification Tag 6"** CSID **Color:** White/Clear **Case pack:** 12 each
- Identification Tag 3"** CSID3 **Color:** White/Clear **Case pack:** 12 each

### Standard Colors

- Speckled Gray (480)

### Approvals



**Components** \* Does not include 6" (15 cm) Shelf Plate.