

PROJECT NAME: _____

LOCATION: _____


SPECIFIER ITEM NO. _____ **QTY:** _____

ENCORE PART NO. _____

Encore[®] 8" (203mm) Deck Mount Faucet
with Tubular Swing Spout and Lever Handles

KL41-8xxx-SE1 Series

- KL41-8106-SE1 6" spout, ceramic valves
- KL41-8006-SE1 6" spout, compression valves
- KL41-8108-SE1 8" spout, ceramic valves
- KL41-8008-SE1 8" spout, compression valves
- KL41-8110-SE1 10" spout, ceramic valves
- KL41-8010-SE1 10" spout, compression valves
- KL41-8112-SE1 12" spout, ceramic valves
- KL41-8012-SE1 12" spout, compression valves



Dimensions shown in inches (mm) are for reference only and are subject to change.

1/2" NPSM Male Inlets
Operating Temperature: 40-180°F (5-83°C)
Operating Pressure: 15-125psi
1-1/8" (29mm) holes for deck are recommended to accommodate 1/2" supply nipples

Approximate shipping weight - 5 lbs
Warranty - 2 years parts

Solid heavy duty cast body is specification and commercial quality for hand sinks.

Commercial Quality Features

- Tubular swing spout design
- ADA-compliant lever handles
- Built-in check valves to prevent cross-flow and back-flow
- Leak proof double O-ring spout design
- Stainless steel spout

SANIGUARD[®] Product Protection

- Permanently incorporated on all touch points of Encore plumbing fixtures
- Inorganic, silver ion technology inhibits growth of common bacteria, yeasts, mold and fungi, minimizes cross-contamination

SPECIFICATIONS:

Deck Mount Faucet to be Encore KL41 Series in the following configuration:

- _____ KL41-8106-SE1 6" spout, ceramic valves
- _____ KL41-8006-SE1 6" spout, compression valves
- _____ KL41-8108-SE1 8" spout, ceramic valves
- _____ KL41-8008-SE1 8" spout, compression valves
- _____ KL41-8110-SE1 10" spout, ceramic valves
- _____ KL41-8010-SE1 10" spout, compression valves
- _____ KL41-8112-SE1 12" spout, ceramic valves
- _____ KL41-8012-SE1 12" spout, compression valves

Faucet body to be constructed of polished chrome plated brass with total lead content less than 0.25% by weighted average. Handles to be lever and incorporated with SANIGUARD treatment. Supply inlets to be 8" on center. Valves to be 1/4-turn with integral check valve to prevent cross-flow and back-flow. Spout to be stainless steel tubular swing style with leak proof double O-ring seal design. Color coded temperature indexes shall meet international standards. 2.2gpm aerator @ 60psi standard with full flow stream bubbler screen spout tip.

Model No.	A	B	C
KL41-8106-SE1	6"(152mm)	4-3/8"(111mm)	2-5/8"(66mm)
KL41-8006-SE1	6"(152mm)	4-3/8"(111mm)	2-5/8"(66mm)
KL41-8108-SE1	8"(203mm)	5-5/16"(135mm)	3-1/16"(78mm)
KL41-8008-SE1	8"(203mm)	5-5/16"(135mm)	3-1/16"(78mm)
KL41-8110-SE1	10"(254mm)	5-13/16"(148mm)	3-9/16"(90mm)
KL41-8010-SE1	10"(254mm)	5-13/16"(148mm)	3-9/16"(90mm)
KL41-8112-SE1	12"(304mm)	6-1/4" (159mm)	4"(101mm)
KL41-8012-SE1	12"(304mm)	6-1/4" (159mm)	4"(101mm)

For a complete list of available options for KL41-8000 Series, see product configurator on reverse.

COMPLIES WITH:
THE FEDERAL "REDUCTION OF LEAD
IN DRINKING WATER ACT" -
2011 - US SENATE BILL NO. S.3874
NSF/ANSI 61/9, ANNEX G



KL41-8xxx-SE1 Series



1890 Swarthmore Avenue, PO Box 2020, Lakewood, NJ 08701
 Phone: 800-526-3694, 732-363-4700, Fax: 732-364-8110
www.encoreplumbing.com • www.componenthardware.com

Faucet Configuration for KL41-8000 Series

