



Project: _____	AIA# _____
Item #: _____ Qty: _____	SIS# _____
Model #: _____	

# Soda Gun Holders

SHA-4, SHA-6, SHB-4, or SHB-6



SHA-6 shown in an installation setting



SHA-6 with access cover removed

NOTE: Soda gun holder to accommodate Wunder-Bar® 14-button soda gun is also available. Add the suffix '-14' to the model number. A clearance height of 39-1/2" is required.

### Standard Features

- All stainless steel construction
- Designed to house Wunder-Bar® soda gun (10-button or smaller)
- Built-in soda gun cradle with hole for drip cup
- Readily removable cover for access to soda brix adjustments
- Allows you to dictate the soda gun location
- Eliminates the need for tubing bundles above the work surface
- Clips are provided for mounting between two other pieces of underbar equipment (there is no provision for leg mounting)
- Includes backsplash, front rail, and front skirt to match adjacent equipment

### Specifications

*Drain*

- Mounting slot provided for standard Wunder-Bar® drip cup holder. Drain connection required on drip cup.

*Soda Gun Style*

- Designed to house Wunder-Bar® soda gun (10-button or smaller)

*Materials*

- 20 gauge stainless steel parts include: front, backsplash, sides, front rail and access cover base plate.
- 18 gauge stainless steel parts include: access cover



### Installation Details




Figure 1



Figure 2




Figure 3



Figure 4



Figure 5


1. Begin with the plastic drip cup holder and align a 10-32 nut over the forward hole. Thread a bolt through the socket. Remove the bolt and secure the nut with a drop of glue, if necessary. (See Figure 1)
2. Install plastic tubing through the grommet provided in the front cover until approximately 5" of tubing remains. (See Figure 2)
3. Connect the end of tubing remaining outside of the front cover to the drain socket provided on the bottom of the soda gun drip cup. (See Figure 3)
4. Insert the soda gun drip cup into the rectangular opening of the cover, simultaneously pushing the drain tube toward the cover until the screw hole in the top cover is aligned with the nut. Secure with a 10-32x1/2" thumb screw. (See Figure 4)
5. To complete assembly, place the soda gun holder cover over the top of the base and install a 10-32 thumb screw into the face of the unit. (See Figure 5) Do not forget to run the inside portion of the drain tube to a floor drain.

<b>Glastender, Inc.</b> • 5400 North Michigan Road • Saginaw, MI • 48604-9780 989.752.4275 • 800.748.0423 • Fax 989.752.4444 <a href="http://www.glastender.com">www.glastender.com</a>	Approval/Notes:
Specifications subject to change without notice. For current specifications please visit our website.	

# Soda Gun Holders

## Dimensional Information

### PLAN VIEWS




SHA-4

SHA-6

SHB-4


SHB-6

### SIDE ELEVATIONS



"A" DEPTH

SHA-4, SHA-6



"B" DEPTH

SHB-4, SHB-6