

## BIG TOP SANDWICH PREP TABLES

VSP60-24B

- Equipped with Secure-Temp 1.0™ Technology™
- 3 Year Parts & Labor Warranty Plus an Additional 2 Year Compressor Warranty
- Exclusive 2 Year Warranty on Santoprene Door Gaskets

**VICTORY ULTRASPEC™**  
FEATURING: **SecureTemp™**  
1.0

Secure-Temp 1.0™ is the industry's first and only full service temperature monitoring solution for your kitchen. Secure-Temp 1.0™ is standard on all Victory models and is HACCP compliant & meets NAFEM's data protocol.

There are NO software or monthly monitoring fees.  
Optional add on kits are available for additional units.

### STANDARD FEATURES

- Secure-Temp 1.0™ Technology
- Front-Breathing Refrigeration System
- Electronic Control
- Expansion Valve Technology
- Stainless Steel Exterior/Stainless Steel Interior
- Santoprene Door Gaskets with Exclusive 2 Year Warranty
- Environmentally Friendly R134A Refrigerant
- CFC Free Foamed In-Place Polyurethane
- Self-Closing Doors with 120° Hold Open feature
- 2 Epoxy Coated Shelves Standard Per Door Section
- Heavy Duty pan divider supports supplied
- Hinged, Insulated, Flat Lift Up Lids
- Locking Divider Bars
- Stainless Steel Pan Dividers
- 10" Wide Cutting Board
- 6" Casters, 2 With Brakes, Standard



VSP60-24B

### OPTIONS & ACCESSORIES

- ADA Compliant 3" Diameter Casters
- 6" Overall Height Adjustable SS Legs
- Single and Double Overshelves
- Stainless Steel Back
- Cylinder Locks
- Optional Voltages: 220/50/1, 220/60/1



Please refer to [www.enersustar.com](http://www.enersustar.com) to view the most up-to-date product listing and performance data

3779 Champion Blvd—Winston-Salem, NC 27105

PH: (888) 845-9800 - Fax: (800) 253-5168

sales@victoryrefrigeration.com www.victoryrefrigeration.com

**CABINET CONSTRUCTION**

Exterior construction includes heavy-duty stainless steel finish on front, sides, top, door(s) and grille. Removable hoods and insulated lid assemblies are made of matching stainless steel. Cabinet back and bottom are constructed of galvanized steel. Interior liner is made of aluminum for superior resistance to corrosion.

Cabinet insulation is CFC free foamed-in-place polyurethane of two-inch minimum thickness. Six-inch casters, 2 with brakes, are standard. Legs are available as an option.

Composite cutting board supplied with cabinet is 10" wide. It is readily removable for cleaning. Two epoxy-coated steel wire shelves per section are supplied as standard. Pans furnished are 4" deep and made of polycarbonate plastic.

**DOOR CONSTRUCTION**

Doors are mounted to face of cabinet on cartridge style hinges permitting them to self-close under their own weight. Hinges also allow doors to stay open 120° and permit easy door removal for service and cleaning if required. A plug in type vinyl magnetic gasket is attached to each door for positive seal. Door handle contoured to permit easy opening of doors with fingers from both top and bottom of handle.

**REFRIGERATION SYSTEM**

More robust refrigeration system provides added capacity and efficiency. Systems are designed using CFC free R134a refrigerant and expansion valve between condenser and evaporator. Recirculated, forced air from evaporator is moved under pans, which are recessed 2" from top of cabinet. Forced air over the condenser is drawn through grille under door as well as the back and bottom of cabinet. Automatic condensate evaporator is provided to eliminate the need of floor drains.

CHARACTERISTICS	VSP60-24B
Net Capacity (cu. ft.)	17.1
Width, Overall (in.)	60"
Depth, Overall (in.)	38 1/2"
Depth, Door(s) Open 90° (in.)	55 1/8"
Height Overall (with lids open)	57 9/16"
No. Shelves	4
No. of 1/6 Size Pans	24
No. of Doors	2

**ELECTICAL DATA**

Condensing Unit Voltage	115/60/1
Total Amperes	9.6

**NOTE:** Plug style, voltage and full load amps may vary depending on certain options selected such as optional voltages and compressor upgrades.

**REFRIGERATION DATA**

Condensing Unit Size	1/3 HP
Refrigerant	R-134A

<b>CRATED WEIGHT</b>	405 LBS
----------------------	---------

\* Remote units use R-404A refrigerant standard and come with 6" legs

