

6235



MODEL 6235

SOFT SERVE FREEZER

Twin twist flavor, Countertop, Gravity feed, Microprocessor control, Independent refrigeration and control system for each flavor

Product Offering

Offer all popular soft serve variations from low or non-fat ice cream to custards, yogurt and sorbet.

Freezing Cylinder

Two, 1.7 Liter (1.8 quarts)

Mix Hopper

Two, 12 Liters (12.68 quarts)

Separate hopper refrigeration maintains mix temperature below 4.4°C (40°F) during Cool and Standby modes.

Mix Low Indicator

When mix level is low, the Mix Low light turns "ON" to alert operator to add mix.

Standby

Maintains product temperature in the mix hoppers and freezing cylinders below 4.4°C (40°F) during long no-use periods.

Microprocessor Controls

Automatically regulates refrigeration and maintains consistent product quality by controlling product temperature and viscosity.

Counter

Records number of dispenses per day and total number of dispenses.

Temperature Display

Displays hopper and cylinder temperature, helps control product safety.

Output

48 Quarts/Hour

Safety Protections

- Low temperature and motor overload cutouts protect from cylinder over freezing.
- High pressure switch prevents compressor overheat.
- Thermal overload protects from motor overheat.





ISO9001
CERTIFIED



Flexible Blade Beater
Higher Capacity, Higher Overrun





Weight	Kg / lb
Net	174 / 384
Shipping	191 / 421

Packaging Volume 0.70 CBM / 24.58 CBF

Dimensions	Net (mm/in)	Shipping (mm/in)
Width	553 / 21.8	640 / 25.2
Depth	792 / 31.2	950 / 37.4
Height	954 / 37.6	1145 / 45.1

Electrical	Maximum Fuse Size	Min. Circuit Ampacity	Poles (P) Wires(W)
208-230/60/1	20	15	- 2P/3W

Plug L6-20P

This unit may be manufactured in other electrical characteristics. Refer to the local Distributor for availability. (For exact electrical information, always refer to the data label of the unit.)

Note
Continuing research results in steady improvements; therefore these specifications are subject to change without notice.

Specifications

Electrical
One dedicated electrical connection is required. Unit shall be cord connected or permanently connected. Consult your local Spaceman distributor for available cord & receptacle specifications as per local codes.

Motor
Two, 1.25HP

Refrigeration System
Main Compressor: One, 6500 BTU/HR, R404A

Separate Hopper Cooling Compressor:
One, 480 BTU/HR, R134A
(BTUs may vary depending on compressor used.)

Air Cooled
Minimum clearance of 152mm (6") on unit left, right and back sides is required to achieve optimum performance.

- Options**
- Top Air Discharge Chute (air cooled only).
 - Water Cooled.
 - Local language Control systems: English, French, Spanish, German, Dutch, Czech, Chinese.