



PRODUCT: \_\_\_\_\_

SKU NUMBER: \_\_\_\_\_


QUANTITY: \_\_\_\_\_



TRAP SHOOTER

WALL AND TILE BRUSH

HUMMER JET JR.



300-5356: 2.2 gpm / 8.3 lpm @ 1000 psi / 76 bars, 115V

300-5357: 2.2 gpm / 8.3 lpm @ 1000 psi / 69 bars, 208V

300-5358: 2.9 gpm / 11 lpm @ 850 psi / 59 bars, 115V

300-5359: 2.9 gpm / 11 lpm @ 800 psi / 55 bars, 208V

300-5371: 2.9 gpm / 11 lpm @ 800 psi / 55 bars, 230V

300-5372: 2.2 gpm / 11 lpm @ 1100 psi / 69 bars, 230V

## FEATURES

- 2hp Motor TEFC, 1725rpm, 1 phase Draws 15A
- 3 cylinder CAT® super flow plunger pump
- SMT-200-RW manual rewind hose reel
- Quick coupler set (connects hose to unit)
- Quick coupler set (connects gun to hose)
- 50ft/15.3m high pressure hose (steel braided)
- Anti-backflow protection/float tank
- Water Level Float Switch Assembly
- Adjustable chemical injector
- Sanitizer chemical selector with flush feature
- 2 1gal/3.8L chemical baskets
- Pressure gauge, 2000psi/138bars, liquid filled
- Stainless steel cover and frame
- Stainless steel wall mount brackets with gun hanger
- 6ft/2m- water inlet supply hose
- 4ft/1.3m Cord with GFC
- Maintenance Kit: Water filter, replacement filter and two hydraulic oils
- ETL-CSA listed to UL 1776
- Shipping Weight: 239lb/104.3kg
- Includes: Hummer Jet Jr.®, Wall & Tile Brush, 10 ft Trapshooter

SMT - 600WDF Wall Mount System

**Spray Master Technologies®**

**TOLL FREE: 800.548.3373**

115 E. LINDEN, ROGERS, ARKANSAS 72756 USA


PHONE: +1 479.636.5776

FAX: +1 479.636.3245

**WWW.SPRAYMASTERTECH.COM**



# SMT - 600WDF Wall Mount System



## Equipment Specifications

### Clearances

Left side	12"/30cm
Right side	12"/30cm
Overhead	14"/35cm
Floor	36"/91cm
Front	36"/91cm

### Plumbing

3/4"/2cm Hose Bib with 5gpm/.14Lpm @  
30psi/20.6bars. 120°F/49°C Max

### Electrical

115V, 16A dedicated circuit or  
208-230V, 9A GFCI.

## Installation Specifications

### Electrical:

One (1) 115V, 60hz, single phase, 20A, 'Dedicated Circuit' with standard receptacle. NOTE: For 208V or 230V units a 15A wall receptacle is required.

### Water:

One (1) warm water outlet 120°F/49°C MAX with standard 3/4"/1.9cm hose bib with shut-off valve. A pressure gauge in the water line can be helpful although it is not mandatory. A minimum of 5 gal. / 19L per minute and a line pressure not less than 30psi/20.6bars, is required.

### Location:

Heated utility room or closet with ventilation. Minimum 14in/.35m clearance above unit required to remove cover. The cover must be removed for servicing the unit. The unit can be serviced without removing it from the wall.

### General Recommendations:

Floor drains are essential in new facilities to receive the greatest utilization and maximum efficiency of your SPRAY MASTER Pressure Washer. Floor materials and wall coverings which can be cleaned with pressurized water are desirable. Locate electrical outlets above washing areas.