





SBB-59	
Doors	2
Capacity (cu. ft.)	15
Shelves	4
НР	3/8
Amps	4.8
Volts	115
Dimensions	58.7" x 27.2" x 37.1"
Shipping weight	267 lbs.

SBB-59G	
Doors	2
Capacity (cu. ft.)	15
Shelves	4
HP	3/8
Amps	4.8
Volts	115
Dimensions	58.7″ x 27.2″ x 37.1″
Shipping weight	293 lbs.

SBB-69	
Doors	2
Capacity (cu. ft.)	19
Shelves	4
HP	3/8
Amps	4.8
Volts	115
Dimensions	68.9″ x 27.2″ x 37.1″
Shipping weight	315 lbs.

SBB-69G	
Doors	2
Capacity (cu. ft.)	19
Shelves	4
HP	3/8
Amps	4.8
Volts	115
Dimensions	68.9″ x 27.2″ x 37.1″
Shipping weight	346 lbs.

BACK-BAR	
COOLERS	

SBB-59	SBB-69	SBB-90
SBB-59G	SBB-69G	SBB-90G

FEATURES:

- Black painted stainless/galvanized steel exterior
- Stainless steel interior
- Top made from 304-grade, 16-gauge stainless
- Temperature range 32°F to 45°F
- Evaportator fan delay with open door
- Heavy-duty 3" casters (optional)
- LED-lighted interior
- . Glass Door models include triple-pane glass
- Easy front service access with ref. unit on slide-out tray
- . Heavy-duty, easy-grip, stainless steel handles



Intertek

Intertek

SBB-90	
Doors	3
Capacity (cu. ft.)	27
Shelves	6
HP	3/8
Amps	4.8
Volts	115
Dimensions	90.2" x 27.2" x 37.1"
Shipping weight	375 lbs.

SBB-90G	
Doors	3
Capacity (cu. ft.)	27
Shelves	6
HP	3/8
Amps	4.8
Volts	115
Dimensions	90.2″ x 27.2″ x 37.1″
Shipping weight	419 lbs.

In the pursuit of a better product, durability and performance, SATURN reserves the right to change specifictions, materials and design without further notice.

www.GetSaturn.com