# HUMIDIFIED CABINETS

## Models HFD2AS,HFD2ASPT, HFD2ACR, HFD2APTCR, HFD2AP, HFD2APTP, HFD3AS, HFD3ASPT, HFD3ACR, HFD3APTCR HFD3AP, & HFD3APTP

## Features/Benefits:

- ★ Star's humidified cabinets are designed to deliver your "grab-n-go" products at the right temperature and texture every time.
- ★ State of the art electronic controls provide accurate temperature and humidity control throughout the cabinet.
- $\star$  LED temperature display for improved visibility from across the room.
- ★ Six pre-programmed channels are factory preset, or easily select the specific temperature to fit your humidity requirements.
- ★ Choose from three merchandising options: pizza racks, pretzel racks and universal wire shelves.
- ★ Temperature ranges from 70°F to 190°F to fit a variety of menu items.
- ★ Large water reservoir for extended operation without refilling.
- ★ Low water level sensing device alerts operator when water is low.
- ★ Illuminated cabinet for better visibility and merchandising.
- ★ Lighted on-off switch to ensure safe operation.
- ★ Water drain for for easy cleaning.
- ★ Available in single door or pass through models.
- ★ Attractive body style and graphics will compliment any foodservice operation.
- ★ "Fresh & Fast" colorful graphics to build impulse sales.

## **Application:**

Star's humidified cabinets are designed for constant use and reliability. Name your product; pizza, pretzels, chicken, pastries, bagels, hot sandwiches, ribs and more, Star's humidity cabinets will hold your food products at the right temperature and texture much longer than traditional means.

## **Quality Construction:**

Cabinets are constructed of stainless steel, tempered glass panels and doors with aluminum alloy corner post. Chrome plated wire racks, lighted on/off switch, electric control to maintain accurate temperature and humidity control. HFD-2 Series are standard with NEMA 5-15P (or NEMA 5-20P for Canada) and HFD-3 are come with NEMA 5-20P standard. Units comes complete with a 6 foot lead-in cord.

## Warranty:

Humidity cabinets are covered by Star's one year parts and labor warranty.





Model HFD2AP



## Model HFD3ACR



 Star Manufacturing International Inc. - 10 Sunnen Drive - P.O. Box 430129 - St. Louis, MO 63143-3800

 Phone: (800) 264-7827 - FAX: (800) 264-6666 - www.star-mfg.com
 S15




## Star Manufacturing International, Inc.


## HUMIDIFIED CABINETS


Models HFD2AS,HFD2ASPT, HFD2ACR, HFD2APTCR, HFD2AP, HFD2APTP, HFD3AS, HFD3ASPT, HFD3ACR, HFD3APTCR

HFD3AP, & HFD3APTP

С







### **Models & Specifications**

Model No.	Approximate	Dimensions			Electrical Data				Weight	
		(A)	(B)	(C)						
	Capacity	Width	Depth	Height	Volts	Watts	Amps	NEMA	Installed	Shipping
HFD2AS*	36 Sandwiches	21-1/8"	22-3/4"	34"					88 lbs.	126 lbs.
Single Door		(53.7 cm)	(57.8 cm)	(86.4 cm)	120	1550	12.9	5-15P*	(39.6 kg)	(56.7 kg)
HFD2ASPT*	36 Sandwiches	21-1/8"	23-3/4"	34"					90 lbs.	126 lbs.
Double Door		(53.7 cm)	(60.3 cm)	(86.4 cm)	120	1550	12.9	5-15P*	(40.5 kg)	(56.7 kg)
HFD2ACR*	3-16" Pizzas	21-1/8"	22-3/4"	34"					88 lbs.	134 lbs.
Single Door		(53.7 cm)	(57.8 cm)	(86.4 cm)	120	1550	12.9	5-15P*	(39.6 kg)	(60.3 kg)
HFD2APTCR*	3-16" Pizzas	21-1/8"	23-3/4"	34"					90 lbs.	134 lbs.
Double Door		(53.7 cm)	(60.3 cm)	(86.4 cm)	120	1550	12.9	5-15P*	(40.5 kg)	(60.3 kg)
HFD2AP*	72 Large	21-1/8"	22-3/4"	34"					88 lbs.	134 lbs.
Single Door	Pretzels	(53.7 cm)	(57.8 cm)	(86.4 cm)	120	1550	12.9	5-15P*	(39.6 kg)	(60.3 kg)
HFD2APTP*	72 Large	21-1/8"	23-3/4"	34"					90 lbs.	134 lbs.
Double Door	Pretzels	(53.7 cm)	(60.3 cm)	(86.4 cm)	120	1550	12.9	5-15P*	(40.5 kg)	(60.3 kg)
HFD3AS	64 Sandwiches	28-1/4"	25-3/4"	37-1/4"					126 lbs.	156 lbs.
Single Door		(71.7 cm)	(65.4 cm)	(94.6 cm)	120	1800	15	5-20P	(56.7 kg)	(70.2 kg)
HFD3ASPT	64 Sandwiches	28-1/4"	26-3/4"	37-1/4"					129 lbs	156 lbs.
Double Door		(71.7 cm)	(67.9 cm)	(94.6 cm)	120	1800	15	5-20P	(58 kg)	(70.2 kg)
HFD3ACR	4-18" Pizzas	28-1/4"	25-3/4"	37-1/4"					126 lbs.	166 lbs.
Single Door		(71.7 cm)	(65.4 cm)	(94.6 cm)	120	1800	15	5-20P	(56.7 kg)	(74.7 kg)
HFD3APTCR	4-18" Pizzas	28-1/4"	26-3/4"	37-1/4"					129 lbs.	166 lbs.
Double Door		(71.7 cm)	(67.9 cm)	(94.6 cm)	120	1800	15	5-20P	(58 kg)	(74.7 kg)
HFD3AP	112 Large	28-1/4"	25-3/4"	37-1/4"					126 lbs.	163 lbs.
Single Door	Pretzels	(71.7 cm)	(65.4 cm)	(94.6 cm)	120	1800	15	5-20P	(56.7 kg)	(73.3 kg)
HFD3APTP	112 Large	28-1/4"	26-3/4"	37-1/4"					129 lbs.	163 lbs.
Double Door	Pretzels	(71.7 cm)	(67.9 cm)	(94.6 cm)	120	1800	15	5-20P	(58 kg)	(73.3 kg)
* Consider models with 5 20D slug systems										

\* Canadian models with 5-20P plug available

### Model Accessories

HFD-2 Models			HFD-3 Models				
Model #	Accessory	Description	Model #	Accessory	Description		
3URS-2A	Universal Rack	3 Shelves	4URS-3A	Universal Rack	4 Shelves		
3CR-2A	Pizza Rack	3 Tier Circle	4CR-3A	Pizza Rack	4 Tier Circle Pizza Rack		
3P-2A	Pretzel	Rack 3 Tier Pretzel Arm (Double Prong)	4P-3A	Pretzel Rack	4 Tier Pretzel Tree (Double Prong)		
CR-2	Pizza Rack	Circle Rack	CR-3	Pizza Rack	Circle Rack		
P-2	Pretzel Rack	Single Tier Pretzel Arm (Double Prong)	P-3	Pretzel Rack	Single Tier Pretzel Arm (Double Prong)		
URS-2	Universal Rack	Shelf	URS-3	Universal Rack	Shelf		

#### Typical Specifications

Cabinet is constructed of stainless steel, tempered glass panels and doors, and aluminum alloy corner posts. A state of the art electronic control is used to maintain accurate temperature/humidity control as well as monitor and indicate the water reservoir level. This control features 6 pre-programmed temperature/humidity presets which can be used as factory set or reset for your specific needs. The unit is available in a single door or two door configuration which can be easily cleaned and reversed if desired. The unit is supplied with a lighted on-off switch and a 6 ft. lead-in cord. A universal stationary rack, circular pizza rack or pretzel rack are available for all units. Humidity cabinets approved by ULS, UL and CUL. Printed in the U.S.A.

Due to periodic changes in designs, methods, procedures, policies and regulations, the specifications contained in this sheet are subject to change without notice. While Star Manufacturing exercises good faith efforts to provide information that is accurate, we are not responsible for errors or omissions in information provided or conclusions reached as a result of using the specifications. By using the information provided, the user assumes all risks in connection with such use.

Star Manufacturing International Inc. - 10 Sunnen Drive - P.O. Box 430129 - St. Louis, MO 63143-3800 Phone: (800) 264-7827 - FAX: (800) 264-6666 - www.star-mfg.com