DIPPING CABINETS







- Removable cabinet covers allow easy access to the product.
- Digital temperature control holds product at a consistent dipping temperature.
- Custom designed for use with Ross frozen custard machines.
- Easy installation.
- Container storage compartments hold 4.25 gallon (16 liter) square buckets, ideal for scooping.
- Heavy Duty swivel casters allow cabinet to be portable.



	MDC2				
Dimensions	Cabinet	with crate			
width	24" (61,0 cm)	60" (152,4 cm)			
height	36" (91,4 cm)	44" (111,8 cm)			
depth	14-1/4" (36,2 cm)	35-3/4" (90,8 cm)			
Weight	203 lbs (92,0 kg)	383 lbs (173,7 kg)			
Electrical	1 Phase, 115 VAC, 60Hz				
running amps	approximately 6.0A				
connection type	NEMA5-15P cord provided				
Dipping Well	Two - 4.25 gallon square buckets with lids				




	MDC3				
Dimensions	Cabinet	with crate			
width	34" (86,4 cm)	60" (152,4 cm)			
height	36" (91,4 cm)	44" (111,8 cm)			
depth	14-1/4" (36,2 cm)	35-3/4" (90,8 cm)			
Weight	203 lbs (92,0 kg)	383 lbs (173,7 kg)			
Electrical	1 Phase, 115 VAC, 60Hz				
running amps	approximately 7.8A				
connection type	NEMA5-15P cord provided				
Dipping Well	Three - 4.25 gallon square buckets with lids				



	MDC4				
Dimensions	Cabinet	with crate	44.75" —		
width	44-3/4" (113,7 cm)	60" (152,4 cm)			
height	36" (91,4 cm)	44" (111,8 cm)			
depth	14-1/4" (36,2 cm)	35-3/4" (90,8 cm)			
Weight	218 lbs (98,8 kg)	383 lbs (173,7 kg)	36"		
Electrical	1 Phase, 115 VAC, 60Hz		1		
running amps	approximately 7.8A				
connection type	NEMA5-15P	cord provided	T	一冊	
Dipping Well	Four - 4.25 gallon sq	uare buckets with lids	<u></u>	П	

Continuous research leads to ongoing product improvements; therefore, these specifications are subject to change without notice.





ISO 9001:2000 Registered

FOODSERVICE EQUIPMENT

502 Highway 67 Kiel, WI 53042-1600 920-894-2293 800-558-5807

Fax: 920-894-7029

E-mail: foodservice@stoelting.com www.stoeltingfoodservice.com