

TRUE FOOD SERVICE EQUIPMENT, INC.

2001 East Terra Lane • O'Fallon, Missouri 63366 (636)240-2400 • Fax (636)272-2408 • (800)325-6152 • Intl Fax# (001)636-272-7546 Parts Dept. (800)424-TRUE • Parts Dept. Fax# (636)272-9471 • www.truemfg.com

Project Name: _____

Location: _____

Model #:

Item #: _____ Qty: ____

SIS #

AIA #

Model: G4SM-23-LD

Glass Four Sided Merchandiser: Swing Door Refrigerator with LED Lighting



Shown with optional black exterior.

ROUGH-IN DATA

Specifications subject to change without notice. Chart dimensions rounded up to the nearest ¹/₈" (millimeters rounded up to next whole number).

			Cabinet Dimensions (inches) (mm)					NEMA	Cord Length (total ft.)	Crated Weight (lbs.)	
Model	Doors	Shelves	L	D†	Н	HP	Voltage	Amps	Config.	(total m)	(kg)
G4SM-23-LD	1	4	27½	301⁄8	785⁄8	1⁄2	115/60/1	10.0	5-15P	9	375
			699	766	1998	1⁄2	230-240/50/1	5.0		2.74	171

† Depth does not include 1¹/₈" (29 mm) for door handle.

 \blacktriangle Plug type varies by country.

		APPROVALS:	AVAILABLE AT:		
1/14	Printed in U.S.A.				

G4SM-23-LD

- The world's #1 manufacturer of glass door merchandisers.
- Oversized, factory balanced, refrigeration system holds 33°F to 38°F (.5°C to 3.3°C).
- Exterior attractive, high luster copper aluminum finish with black trim.
- Interior attractive, NSF approved, white aluminum interior liner with stainless steel floor.
- Door is self closing with a positive seal, torsion type closure system.
- "Low-E", double pane thermal insulated glass in door assembly, sides and rear. The latest in energy efficient technology.
- Illuminated exterior front sign panel.
- Entire cabinet structure is foamed-in-place using Ecomate. A high density, polyurethane insulation that has zero ozone depletion potential (ODP) and zero global warming potential (GWP).

Bottom mounted units feature

- "No stoop" lower shelf to maximize product visibility.
- Storage on top of cabinet.
- Easily accessible condenser coil for cleaning.

Model: G4SM-23-LD

Glass Four Sided Merchandiser: Swing Door Refrigerator with LED Lighting



STANDARD FEATURES

DESIGN

True's commitment to using the highest quality materials and oversized refrigeration systems provides the user with colder product temperatures, and lower utility costs in a stylish merchandiser that creates a dynamic 360° product display.

REFRIGERATION SYSTEM

- Factory engineered, self-contained, capillary tube system using environmentally friendly (CFC free) 134A refrigerant.
- Extra large evaporator coil balanced with higher horsepower compressor and large condenser; maintains cabinet temperatures of 33°F to 38°F (.5°C to 3.3°C).
- Sealed, cast iron, self-lubricating evaporator fan motor(s) and larger fan blades give True merchandisers a more efficient low velocity, high volume airflow design. This unique design ensures more consistent, colder holding temperatures and faster recovery in high use situations.
- Bottom mounted condensing unit positioned for easy maintenance; "no stoop" lower shelf maximizes visibility by raising merchandised product to higher level.

CABINET CONSTRUCTION

- Exterior attractive, high luster copper aluminum finish with black trim.
- Low-E, double pane thermal insulated glass sides and door assembly. The latest in energy efficient technology.
- Interior attractive, NSF approved, black aluminum interior liner with stainless steel floor.
- Insulation entire cabinet structure is foamed-inplace using Ecomate. A high density, polyurethane insulation that has zero ozone depletion potential (ODP) and zero global warming potential (GWP).
- Welded, heavy duty steel frame rail, black powder coated for corrosion protection.


WARRANTY

Three year warranty on all parts

and labor and an additional 2

year warranty on compressor. (U.S.A. only)

PLAN VIEW



- Frame rail fitted with leg levelers.
- Illuminated exterior front sign panel. Variety of sign options available.

DOOR

- "Low-E", double pane thermal insulated glass door assembly with extruded aluminum frame. The latest in energy efficient technology.
- Door fitted with 12" (305 mm) long extruded handle.
- Self closing door. Positive seal, torsion type closure system.
- Magnetic door gasket of one piece construction, removable without tools for ease of cleaning.

SHELVING

- Four (4) adjustable, heavy duty, white PVC coated wire shelves 23 % "L x 20 % "D (601 mm x 531 mm). Four (4) chrome plated shelf clips included per shelf.
- Shelf support pilasters made of same material as cabinet interior; shelves are adjustable on 1/2" (13 mm) increments.

LIGHTING

LED interior lighting provides more even lighting throughout the cabinet. Safety shielded.

MODEL FEATURES

- Evaporator is epoxy coated to eliminate the potential of corrosion.
- See our website www.truemfg.com for latest color and sign offerings.
- Listed under NSF-7 for the storage and/or display of packaged or bottled product.

ELECTRICAL

NEAREST WHOLE MILLIMETER

WITHOUT NOTICE

Unit completely pre-wired at factory and ready for final connection to a 115/60/1 phase, 15 amp dedicated outlet. Cord and plug set included.



OPTIONAL FEATURES/ACCESSORIES

Upcharge and lead times may apply.

- 230 240V / 50 Hz.
- Black exterior.
- White exterior.
- Cherry exterior.
- Black aluminum interior liner.
- G" (153 mm) standard legs.
- □ 6" (153 mm) seismic/flanged legs.
- 2½" (64 mm) diameter castors.
- □ 4" (102 mm) diameter castors.
- □ Red wine thermostat.
- Chocolate thermostat.
- White wine thermostat.
- Barrel lock (factory installed).
- Black shelves.
- □ TrueFlex/TrueTrac gravity feed organizers.
- □ True offer's five versions of the G4SM-23 with a variety of features to increase the merchandiser's function and versatility, allowing it to be customized to your needs.
- Remote cabinets (condensing unit supplied by others; system comes standard with 404A expansion valve and requires R404A refrigerant). Consult factory technical service department for BTU information. All remote units must be hard wired during installation.

55'

(1397 mm)

¥

2415/16"

(634 mm)

METRIC DIMENSIONS ROUNDED UP TO THE Model Flevation Right Plan 3D Back KCL G4SM-23-LD TFAY10P TFAY103 TFAY10E TFAY10S SPECIFICATIONS SUBJECT TO CHANGE

271/2 (699 mm) 27" (686 mm)

PLAN VIEW

301/16 (764 mm)

315/32'

(792 mm)

1³/32" (

(28 mm)

TRUE FOOD SERVICE EQUIPMENT

2001 East Terra Lane • O'Fallon, Missouri 63366 • (636)240-2400 • Fax (636)272-2408 • (800)325-6152 • Intl. Fax# (001)636-272-7546 • www.truemfg.com