Image: Construction of the state o	
Model: DM-19T-LD WHT WHTTRM All White LED Lighting Swing Dod	
	 GDM-19T-LD WHT WHTTRM The world's #1 manufacturer of glass door merchandisers. Oversized, factory balanced, refrigeration system holds 33°F to 38°F (.5°C to 3.3°C). Exterior - non-peel or chip white laminated vinyl; durable and permanent. Interior - attractive, NSF approved, white aluminum interior liner with stainless steel floor. Self closing door. Positive seal, torsion type closure system. "Low-E", double pane thermal insulated glass door assembly with extruded aluminum frame. The latest in energy efficient technology. LED interior lighting, safety shielded. Entire cabinet structure is foamedin-place using Ecomate. A high density, polyurethane insulation that has zero ozone depletion potential (ODP) and zero global warming potential (GWP). Bottom mounted units feature "No stoop" lower shelf to maximize product visibility. Storage on top of cabinet. Easily accessible condenser coil for cleaning.
ROUGH-IN DATA Chart dimensions rou	Specifications subject to change without noti unded up to the nearest $\%$ " (millimeters rounded up to next whole numbers)
Cabinet Dimensions (inches) (mm)	Cord Crated Length Weight

			(inches) (mm)					NEMA	Length (total ft.)	Weight (lbs.)	
Model	Doors	Shelves	L	D†	Н	HP	Voltage	Amps	Config.	(total m)	(kg)
GDM-19T-LD WHT WHTTRM	1	4	27	241⁄8	78%	1⁄3	115/60/1	8.1	5-15P	9	275
			686	632	1998					2.74	125

	APPROVALS:	AVAILABLE AT:
1/13Printed in U.S.A.		

GDM-19T-LD WHT WHTTRM

Glass Door Merchandiser: All White LED Lighting Swing Door Refrigerator



STANDARD FEATURES

DESIGN

 True's commitment to using the highest quality materials and oversized refrigeration systems provides the user with colder product temperatures, and lower utility costs in an attractive merchandiser that brilliantly displays packaged food and beverages.

REFRIGERATION SYSTEM

- Factory engineered, self-contained, capillary tube system using environmentally friendly (CFC free) 134A refrigerant.
- Extra large evaporator coil balanced with higher horsepower compressor and large condenser; maintains cabinet temperatures of 33°F to 38°F (.5°C to 3.3°C).
- Sealed, cast iron, self-lubricating evaporator fan motor(s) and larger fan blades give True merchandisers a more efficient low velocity, high volume airflow design. This unique design ensures faster temperature pull down of warm product, colder holding temperatures and faster recovery in high use situations.
- Bottom mounted condensing unit positioned for easy maintenance. "No stoop" lower shelf maximizes visibility by raising merchandised product to higher level.

CABINET CONSTRUCTION

- Exterior non-peel or chip white laminated vinyl; durable and permanent.
- Interior attractive, NSF approved, white aluminum liner with stainless steel floor.
- Insulation entire cabinet structure is foamedin-place using Ecomate. A high density, polyurethane insulation that has zero ozone depletion potential (ODP) and zero global warming potential (GWP).

• Welded, heavy duty steel frame rail, black powder coated for corrosion protection.

- Frame rail fitted with leg levelers.
- Illuminated exterior sign panel. Variety of sign options available.

DOOR

- "Low-E", double pane thermal insulated glass door assembly with extruded aluminum frame. The latest in energy efficient technology.
- Door fitted with 12" (305 mm) long integrated handle.
- Self closing door. Positive seal, torsion type closure system.
- Magnetic door gasket of one piece construction, removable without tools for ease of cleaning.

SHELVING

- Four (4) adjustable, heavy duty PVC coated wire shelves 22% "L x 18¼"D (574 mm x 464 mm).
 Four (4) chrome plated shelf clips included per shelf.
- Shelf support pilasters made of same material as cabinet interior; shelves are adjustable on ½" (13 mm) increments.

LIGHTING

- LED interior lighting, safety shielded. MODEL FEATURES
- Evaporator is epoxy coated to eliminate the potential of corrosion.
- See our website www.truemfg.com for latest color and sign offerings.
- Convenient clean-out drain built in cabinet floor.
- Listed under NSF-7 for the storage and/or display of packaged or bottled product.

ELECTRICAL

 Unit completely pre-wired at factory and ready for final connection to a 115/60/1 phase, 15 amp dedicated outlet. Cord and plug set included.




OPTIONAL FEATURES/ACCESSORIES

- Upcharge and lead times may apply.
- G" (153 mm) standard legs.
- □ 6" (153 mm) seismic/flanged legs.
- \Box 2 $\frac{1}{2}$ " (64 mm) diameter castors.
- 4" (102 mm) diameter castors.
 - Red wine thermostat.
- □ White wine thermostat.
- Chocolate thermostat.
- Barrel lock (factory installed).
- Additional shelves.
- TrueFlex gravity feed organizers.
- Pricing strips.
- Remote cabinets (condensing unit supplied by others; system comes standard with 404A expansion valve and requires R404A refrigerant). Consult factory technical service department for BTU information. All remote units must be hard wired during installation.

3D

Back



TRUE FOOD SERVICE EQUIPMENT

2001 East Terra Lane • O'Fallon, Missouri 63366 • (636)240-2400 • Fax (636)272-2408 • (800)325-6152 • Intl. Fax# (001)636-272-7546 • www.truemfg.com