

T&S BRASS AND BRONZE WORKS, INC.

2 Saddleback Cove / P.O. Box 1088 Travelers Rest, SC 29690 Model No.

EC-3100-HG

Item No.

Travelers Rest, SC: 800-476-4103 • Simi Valley, CA: 800-423-0150 • Fax: 864-834-3518 • www.tsbrass.com						
ChekPoint"	This Space	for Archite	ct/Engineer	Approval		
O CHERPOINT	Job Name			Date		
ADA Compliant	Model Specified_			Quantity		
	Customer/Wholes	saler				
	Contractor					
. U	Architect/Engine	er				
3 5/8" x 4 3/16" x 2" Deep [92mm x 106mm x 51mm] Water Resistant Control Module w/ Internal Flow Control Setting AC or DC operated w/ (4) AA Batteries If Hydro-Generator is Hardwire Capable using Termin	Switches, Not Used.	\ Va		eneck 1 [8.3 L/min] sistant Aerator		
☐ 24" [610mm] Sensor Cable			4	11"		
Sensor Cable	\	-	4	1/8" [286mm]		
Removable	7 5/16"		[10)5mm]		
Strainer	[185mm]					
DECK				<u> </u>		
DECK	2 1/4" Max.		T O	1/8" [3mm]		
	_ 2 1/4 Max. [57mm]		Piı	n installed		
	1" [25mm] /		1001	Anti-rotation ature. Remove		
	eck Hole	r de		if desired.		
St. Steel Hose (1)				ee Mounting		
	s Optional 0 VAC Adapt	or I		ole Detail)		
	' [3658mm] L	10°		Mounting Hole		
No AA Batteries Double	Power Cord.	- The State of the		Detail		
	ve Rubber Pluude lule and Cable	1860		Ø1" [25mm]		
Power to Faucet. to Coni	nect)	ľ				
Temperature Mixing Valve Furnished w/ (2)		8	8	* 1"		
w/ Integral Check Valves — 3/8" Compression				[25mm]		
NOTE: Supply Stops by Others 18" [457mm] Flex.	St. Steel Su	oply Ho		⊅5/32" [4mm]		
Product Specifications: Chrome Plated Brass Electronic Faucet: Deck Mount Rigi	٦	awn	Checked	Approved		
Gooseneck w/ VR Aerator, AC/DC Control Module w/ In	ternal'	KJG	GEF	JHB		
Flow Cont. Setting Switches, Temperature Control Mixing w/Integral Check Valves,, Hydro-Generator, 18" Long Ho	Valve Scatt	ale: 1:	1	Date: 03/30/12		
Supply Stop Flexible Connector Hoses		I .'		03/30/12		



T&S BRASS AND BRONZE WORKS, INC.

2 Saddleback Cove / P.O. Box 1088 Travelers Rest, SC 29690 Model No.


EC-3100-HG

Item No.


Travelers Rest, SC: 800-476-4103 • Simi Valley, CA: 800-423-0150 • Fax: 864-834-3518 • www.tsbrass.com



ITEM NO.	SALES NUMBER	DESCRIPTION
1	B-0199-06	VR Aerator w/ Key
2	044A	3/8" to Aerator Adapter
3	006575-45	-015 O-Ring
4	017195-45	Angled Sensor w/ Cable
5	016297-45	Inlet Hose, Faucet, 1/2" NPSM-F x 1/4" NPSM-F
6	016647-45	ChekPoint Module (Blue)
7	5EF-0002	Double Gang, Plug-in AC Transformer
8	5EF-0006	Mechanical Mixing Valve
10 015425-45 Vanda		Supply Hose, 9/16-24 Female x 1/2" NPSM
		Vandal Resistant Key
		Hydro-generator and Swivel Coupling
12	017506-45	1/2 NPSM Swivel Coupling
13	EC-FILTER	Replacement Filter



A maximum of (8) ChekPoint Faucets can be hardwire connected and powered by ChekPoint Hardwire AC Transformer. EC-HARDWIRE (Sold Separately)



Flow Control Switches are located inside Module Housing in Black Box next to Battery Compartment.
*Switches are set to DEFAULT position: Auto Time Out = 10 seconds
Shut Off Delay = 1 second
Auto Flush = OFF

Remove (4) screws and back cover to access switches.

*Available Water Flow Control Selections:

(6) Auto Time Out Selections - 10 sec, 25 sec, 45 sec, 60 sec, 3 min, 20 min

(4) Shut Off Delay Selections - 1 sec, 2 sec, 4 sec, 10 sec

Auto Flush for 30 Seconds After Every 12 Inactive Hours - ON or OFF

Product Specifications:
Chrome Plated Brass Electronic Faucet: Deck Mount Rigid
Gooseneck w/ VR Aerator, AC/DC Control Module w/ Internal
Flow Cont. Setting Switches, Temperature Control Mixing Valve
w/ Integral Check Valves,, Hydro-Generator, 18" Long Hot & Cold
Supply Stop Flexible Connector Hoses

Drawn	Checked	Approved
KJG	GEF	JHB
Scale:		Date:
ГИ	S	03/30/12