

Carson, CA 90746 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Proje	ct ·
FIUJE	ω.

Model #: Item # :

Qty :

Available W/H :

Approval :

Solid Door Refrigerator

____ FEATURES / BENEFITS ____

DIGITAL TEMPERATURE CONTROL SYSTEM

Provides precise and constant temperature. This level of precision allows food products to remain fresh over an extended period of time.

HIGH-TECH MONITOR

The unit will beep if the door has been opened for more than 30 seconds. The monitor digitally displays the present temperature and current status of the refrigerator. You can easily change the temperature by adjusting the thermostat.

STAINLESS STEEL CABINET CONSTRUCTION

The Turbo Air New Maximum model boasts a stainless steel interior and stainless steel exterior with clear coat AL side panels (galvanized steel top, bottom and back). It guarantees the utmost in cleanliness and long product life. Unlike other companies' products, the sharp corners and edges have been rounded to reduce the risk of injury. The New Maximum can add a touch of style to the most refined setting.

EFFICIENT REFRIGERATION SYSTEM

Turbo Air's solid door refrigerators are designed with oversized and balanced (CFC Free R-134A) refrigeration systems. These include efficient evaporators and condensers for faster cooling and greater efficiency.

AUTOMATIC EVAPORATOR FAN MOTOR DELAYS Through stopping the evaporator fan when the refrigerator door opens, the circulation of hot, moist air into the refrigerator is prevented. This increases energy efficiency and lengthens the life of the compressor.

ADJUSTABLE, HEAVY DUTY, PE(POLYETHYLENE) **COATED WIRE SHELVES**

HIGH-DENSITY POLYURETHANE INSULATION The entire cabinet structure and solid doors are foamed-in-place using

high density, CFC free polyurethane insulation.

ERGONOMICALLY DESIGNED DOORS

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. Self-closing and stay open door features make this the ultimate choice in customer convenience.

MAGNETIC DOOR GASKETS

Magnetic door gaskets are of one piece construction, removable without tools for ease of cleaning and replacement.

BOTTOM MOUNT COMPRESSOR UNITS

Turbo Air's bottom mount compressor allows easier access for service and extra storage space above. In addition, the lower area provides a cooler and loss greasy operating onvironment which result

Reach-In Bottom Mounts New Maximum Series

Model : MSR-23NM



REFRIGERATOR HOLDS 33°F ~ 38°F FOR THE BEST IN FOOD PRESERVATION

in reduced con	o , ,	ing time.					5 YEAR WARRANTY (U.S.A coty) ENERGY STAR® Qualified
Model	Swing Door	CU./FT.	#of Shelves	HP	AMPS	Crated Weight (lbs.)	$L \ge D \ge H^*$ (inches)
MSR-23NM	1	23	3	1/4	5.5	254	27 x 303/4 x 781/4

* Height does not include 5" caster height or 6" optional legs.

Solid Door Refrigerator

Model: MSR-23NM

ELECTRICAL DATA					
Voltage	115/60/1				
Plug Type	(i) NEMA-5-15P				
Full Load Amperes	5.5				
Compressor HP	1/4				
Feed Wires with Ground	3				
Cord Length ft.	7				
Refrigerant	R-134A				
DIMENSIONAL DATA					
# of Doors	1				
# of Racks Accepted	1				
Net Capacity cu. ft.	23				
Ext. Length Overall in.	27 (686mm)				
Ext. Depth Overall in.	303/4 (781mm)				
Ext. Height Overall in.*	781/4 (1987mm)				
Int. Length Overall in.	23 (584mm)				
Int. Depth Overall in.	243/4 (629mm)				
Int. Height Overall in.	603/8 (1534mm)				
Gross Weight lbs.	254				
# of Shelves	3				
Shelf Size (LxD) in.	215/8 x 231/4				

Design and specifications subject to change without notice. Actual shipping weight may differ due to extra packing materials for product protection. * Height does not include 5" caster height or 6" optional legs.

2 Year Parts and Labor Warranty **WARRANTY**: Additional 3 Year Warranty on Compressor

- INCANDESCENT INTERIOR LIGHTING
- DOOR LOCKS
- Self-Contained System
- 4" SWIVEL CASTERS
- Solid and Sturdy Grille Design
- TRAY RACK AVAILABLE (OPTIONAL)

OPTIONAL ACCESSORIES :

- □ 5" Diameter swivel casters
- □ 6" Standard legs
- □ Additional stainless steel shelves
- Additional PE coated wire shelves
- Half door bun tray racks. Each holds up to seven 18"Lx26"D sheet pans (sold separately)
- Full door bun tray racks. Each holds up to fifteen 18"Lx26"D sheet pans (sold separately)

(NSE)


YEAR


KNIFE

(GERMAN

PLAN VIEW

(unit : inch)







Ver.201301

ENERGY STAR® 5 YEAR WARRANTY Qualified

- **Turbo Air** : 800-627-0032 **GK** : 800-500-3519
- Warranty : 800-381-7770 AC : 888-900-1002



 (\mathbb{I})

ŰL

c

ŰL



GREEN WORLD

