

Carson, CA 90746 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project :		
Model #:		
Item #:	Qty:	
Available W/H :		
Approval :		

Mega Top Unit

Food Prep Tables-Mega Top M3 Series

Model: MST-28-12



___ FEATURES / BENEFITS =__

■ COLD AIR COMPARTMENT

Our innovative "Cold Air Compartment" maintains temperature evenly for each pan to preserve fresh food longer. In addition, the compartment isolates pans from the reach-in area to prevent food spillage.

STAINLESS STEEL CABINET CONSTRUCTION

The Turbo Air M3 model boasts a stainless steel exterior (galvanized steel back and bottom). Interior is stainless steel floor with AL sides and back. It guarantees the utmost in cleanliness and long product life. It can add a touch of style to the most refined setting.

Convenient Cutting Board Side Rail

Our cutting board is 91/2" deep and 1/2" thick to provide ample working space, and is made of easy to use and sanitize LDPE (Low Density Polyethylene). The new side rail cutting board bracket makes it easy to secure and remove the cutting board and it accepts different sizes too (max. 1/2" thickness)

■ Hot Gas Condensate System

Through Turbo Air's creative innovation, the condensate system surfaces have been specially treated to resist corrosion. This not only increases efficiency without the risk of refrigerant leakage from corrosion, but also prevents the overflow of condensate water.

HIGH-DENSITY POLYURETHANE INSULATION

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

■ Efficient Refrigeration System

M3's solid door refrigerators are designed with oversized and balanced (CFC Free R-134A) refrigeration systems. These include efficient evaporators and condensers for faster cooling and greater efficiency.

■ MAGNETIC DOOR GASKETS

Magnetic door gaskets are of one piece construction, removable without tools for ease of cleaning and replacement.

ADJUSTABLE, HEAVY DUTY, PE (POLYETHYLENE) COATED WIRE SHELVES

■ ERGONOMICALLY DESIGNED DOORS

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience. ABS sheet door liners resist water condensation with thermal efficiency.

■ REFRIGERATOR HOLDS 33°F ~ 39°F FOR THE BEST IN FOOD PRESERVATION











Model	Swing Door	CU./FT.	#of Shelves	#of Pans	#of Hood	HP	AMPS	Crated Weight (lbs.)	L x D*x H [†] (inches)
MST-28-12	1	8	1	12	1	1/5	3.3	220	271/2 x 34 x 39

(unit: inch)

Model: MST-28-12

ELECTRICAL DATA						
Voltage	115/60/1					
Plug Type	① NEMA-5-15P					
Full Load Amperes	3.3					
Compressor HP	1/5					
Cord Length ft.	9					
Refrigerant	R-134A					
DIMENSIONAL DATA						
Ext. Length Overall in.	27 _{1/2} (698mm)					
Ext. Depth Overall in.*	34 (864mm)					
Ext. Height Overall in.+	39 (991mm)					
# of Doors	1					
# of Shelves	1					
# of Pans	12					
Net Capacity cu. ft.	8					
Gross Weight lbs.	220					
Net Weight lbs.	206					

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.


■ WARRANTY: 2 Year Parts and Labor Warranty Additional 3 Year Warranty on Compressor

- SELF-CONTAINED SYSTEM
- 4" DIA. SWIVEL CASTERS
- STANDARD 1/6 SIZE, 4" DEEP CONDIMENT PANS INCLUDED
- 91/2" DEEP, 1/2" THICK CUTTING BOARD INCLUDED


■ OPTIONAL ACCESSORIES:

- 2.5" Diameter casters
- ☐ 5" Diameter casters
- ☐ 6" ABS plastic legs
- Additional stainless steel shelves
- ☐ Additional PE coated wire shelves

PLAN VIEW



PLAN VIEW



SIDE VIEW

Ver.201301





















■ **Turbo Air**: 800-627-0032 ■ **GK**: 800-500-3519

■ Warranty: 800-381-7770 ■ AC: 888-900-1002

^{*} Depth does not include 3" for cutting boards and 1" for rear spacers.

[†] Height does not include 5-7/8" for caster height.