

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

| Project :       |          | _ |
|-----------------|----------|---|
| Model #:        |          | _ |
| Item #:         | Qty:     | _ |
| Available W/H : | <u> </u> | _ |
| Approval :      |          | _ |

# Sakura Sushi Case

Display Cases Refrigerated Sushi Cases

ITS INNOVATIVE DESIGN AND NEW TECHNOLOGY WILL POSITION TURBO AIR AS THE LEADER IN SUSHI CASE PRODUCTS FOR MANY YEARS TO COME

Model : SAKURA-70-L SAKURA-70-R



# 

- BEAUTIFULLY CURVED, ANGLED DOWN TOP FRONT GLASS
- EQUIPPED NSF APPROVED THERMOMETER
- 1" DIAMETER DRAIN HOLE WITH PLASTIC COVER
- SLIGHTLY TILTED BOTTOM FOR BETTER DRAINAGE
- LARGER INTERIOR FOR OPTIMIZED DISPLAY EFFECT
- 304 STAINLESS STEEL SOLID FOOD PLATES
- OVERSIZED AND BALANCED CFC FREE R-134A REFRIGERATION SYSTEM
- TEMPERED GLASS DOORS WITH DURABLE PLASTIC DOOR HANDLES AT CHEF SIDE
- EXTERIOR BODY IS BEAUTIFULLY MADE FROM UNIQUE AND STYLISH 304 STAINLESS STEEL MATERIAL



- SIDE MOUNT COMPRESSOR MAKES IT EASY TO BE SERVICED WITHOUT BEING MOVED
- ELEGANT CONTEMPORARY EURO DESIGN ENHANCES ANY STORE APPLICATION
- EASY CLEANING AND EXCELLENT DURABILITY
- REFRIGERATOR MAINTAINS 35°F ~ 41°F FOR THE BEST IN FOOD PRESERVATION
- AMBIENT TEMPERATURE RANGE 50°F ~ 80°F, SATURATION TEMPERATURE 39°F
- CONDENSER LOCATES ON LEFT OR RIGHT FROM THE FRONT VIEW
- DRAIN HOLE LOCATES ON LEFT FROM THE CHEF SIDE.
- RECOMMENDED OPERATING CONDITIONS
   SAKURA models are designed to operate in environments where temperature & humidity do not exceed 75°F and 55% relative humidity.









| Mo             | del                | Compressor<br>Location | Sliding<br>Door | CU./FT. | Bottom<br>Shelves | НР  | AMPS | Crated<br>Weight (lbs.) | L x D*x H<br>(inches) |
|----------------|--------------------|------------------------|-----------------|---------|-------------------|-----|------|-------------------------|-----------------------|
| SAKUR<br>SAKUR | RA-70-L<br>RA-70-R | Left<br>Right          | 4               | 2.1     | 5                 | 1/6 | 3    | 117                     | 711/4 x 141/8 x 111/2 |

Ver.201407 \* Depth does not include 5/8" for drain.

# Sakura Sushi Case

# **Model: SAKURA-70-L** SAKURA-70-R

| ELECTRICAL DATA         |                            |  |  |  |  |  |
|-------------------------|----------------------------|--|--|--|--|--|
| Voltage                 | 115/60/1                   |  |  |  |  |  |
| Plug Type               |                            |  |  |  |  |  |
| Full Load Amperes       | 3                          |  |  |  |  |  |
| Compressor HP           | 1/6                        |  |  |  |  |  |
| Cord Length ft.         | 9                          |  |  |  |  |  |
| Refrigerant             | R-134A                     |  |  |  |  |  |
| DIMENSIONAL DATA        |                            |  |  |  |  |  |
| Net Capacity cu. ft.    | 2.1                        |  |  |  |  |  |
| Ext. Length Overall in. | 71 <sub>1/4</sub> (1810mm) |  |  |  |  |  |
| Ext. Depth Overall in.* | 141/8 (360mm)              |  |  |  |  |  |
| Ext. Height Overall in. | 11 <sub>1/2</sub> (292mm)  |  |  |  |  |  |
| Int. Length Overall in. | 567/8 (1445mm)             |  |  |  |  |  |
| Int. Depth Overall in.  | 12 (305mm)                 |  |  |  |  |  |
| Int. Height Overall in. | 61/2 (165mm)               |  |  |  |  |  |
| # of Sliding Doors      | 4                          |  |  |  |  |  |
| # of Bottom Shelves     | 5                          |  |  |  |  |  |
| Gross Weight lbs.       | 120                        |  |  |  |  |  |
| Net Weight lbs.         | 98                         |  |  |  |  |  |

Design and specifications subject to change without notice.

■ WARRANTY: 1 Year Parts and Labor Warranty
Additional 4 Year Warranty on Compressor

- SELF-CONTAINED SYSTEM
- No Plumbing Required
- SIMPLE PLUG-IN INSTALLATION

#### **PLAN VIEW** (unit: inch)




## SAKURA-70-R



### SAKURA-70-L

### **TOP VIEW**




SAKURA-70-R



SAKURA-70-L

## **FRONT VIEW**



Ver.201407









■ **Turbo Air**: 800-627-0032

■ **GK**: 800-500-3519

■ **Warranty**: 800-381-7770

■ **AC**: 888-900-1002











Actual shipping weight may differ due to extra packing materials for product protection.

<sup>\*</sup> Depth does not include 5/8" for drain.