

Carson, CA 90746 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

| D | 1 | |
|------|-------|---|
| Pro | IDCT. | • |
| 1 10 | 1000 | |
| | | |

Model #: Item # :

Qty :

Underbar Equipment

Beer Dispensers

Available W/H :

Approval :

Beer Dispensers





TBD-1SB

- Does not include keg couplers - 2 Year Parts and Labor Warranty for SB Unit

*—*FEATURES / BENEFITS —

EFFICIENT REFRIGERATION SYSTEM

Turbo Air's refrigerators are designed with oversized and balanced R-134A (CFC Free) refrigeration systems. Theses include efficient evaporators and condensers for faster cooling and greater efficiency.

Forced Air Cooling System Fast cooling and balanced temperature throughout the cabinet.

STAINLESS STEEL CABINET CONSTRUCTION

Super Deluxe (SD) models boast a stainless steel exterior (except galvanized steel back and bottom). SB models are attractive wear-resistant black vinyl exterior. Heavy gauge stainless steel countertop is perfect for sanitation and durability. Interior is stainless steel floor and door liners with white painted galvanized steel inside walls. Turbo Air Beer Dispenser model guarantees utmost in cleanliness and long product life. It also can add a touch of style to the most refined setting.

HIGH-DENSITY POLYURETHANE INSULATION

The entire cabinet structure is foamed-in-place using high density, CFC free polyurethane insulation.

3" DIAMETER STAINLESS STEEL INSULATED **BEER COLUMNS**

ERGONOMICALLY DESIGNED DOORS

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience.

SIDE MOUNT COMPRESSOR UNIT

Through positioning the compressor to the side, the refrigerator can be serviced without being moved. By innovatively creating a front breathing feature, this model can provide high efficiency in narrow spaces.

- INCANDESCENT INTERIOR LIGHTING
- REFRIGERATOR HOLDS 33°F ~ 38°F FOR THE **BEST IN BEVERAGE PRESERVATION**

| _ | | | | | | | |
|----|--------|---------------|----------------|------|------|-------------------------|--------------------------------------|
| Ν | Model | Swing Door | 1/2 Barrels | HP | AMPS | Crated Weight (lbs.) | $L \underset{(inches)}{x D^* x H^+}$ |
| ТВ | BD-1SD | 1 | 1 | 1/10 | 4 | 198 | 235/8 x 313/4 x 387/8 |
| ТВ | BD-1SB | 1 | 1 | 1/10 | 4 | 198 | 235/8 x 313/4 x 387/8 |

* Depth does not include 2" for rear spacers. + Height does not include 5" for caster height. Height does not include 15-1/8" for draft arm.

Beer Dispensers

Model : TBD-1SD/SB

| ELECTRICAL DATA | | | | |
|--------------------------|---------------|--|--|--|
| Voltage | 115/60/1 | | | |
| Plug Type | NEMA-5-15P | | | |
| Full Load Amperes | 4 | | | |
| Compressor HP | 1/10 | | | |
| Refrigerant | R-134A | | | |
| Cord Length (ft.) | 8.5 | | | |
| Lamp (w) | 25W | | | |
| DIMENSIONAL DATA | | | | |
| Cubic feet (1/2 Barrels) | 1 | | | |
| Ext. Length Overall in. | 235/8 (600mm) | | | |
| Ext. Depth Overall in.* | 313/4 (806mm) | | | |
| Ext. Height Overall in.† | 387/8 (988mm) | | | |
| Gross Weight lbs. | 198 | | | |
| Net Weight Ibs. | 175 | | | |
| # of Swing Door | 1 | | | |

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection. * Depth does not include 2" for rear spacers.


† Height does not include 5" for caster height. Height does not include 15-1/8" for draft arm.

3 Year Parts and Labor Warranty WARRANTY: Additional 2 Year Warranty on Compressor (SD Model)


- 2 Year Parts and Labor Warranty WARRANTY : Additional 3 Year Warranty on Compressor (SB Model)
- SELF-CONTAINED SYSTEM
- 4" SWIVEL CASTERS STANDARD
- DOOR LOCKS STANDARD

PLAN VIEW


(unit : inch)



PLAN VIEW



FRONT VIEW



SIDE VIEW

Ver.201301

Turbo Air : 800-627-0032 **GK** : 800-500-3519 ■ Warranty: 800-381-7770 ■ AC: 888-900-1002



5 YEAR WARRANTY

(GERMAN

Intertek

(NSF.)



