

1250 Victoria St Carson, CA 90746 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project :		
Model #:		
Item #:	Qty:	
Available W/H :		
Approval :		

## **Direct Cooling Type Cases**

Bakery & Deli Cases Low Profile

Model: TCDD-48-2-L





\* Red wine and white color come standard

### = FEATURES / BENEFITS=

#### ■ MODERN DESIGN

By harmonizing curvature and rigidness, our modern style product designs are user-friendly while maintaining the highest product visibility and aesthetics.

#### ■ ENVIRONMENTALLY FRIENDLY, EFFICIENT REFRIG-ERATION SYSTEM

Turbo Air's refrigerators are designed with oversized and balanced environmentally friendly R-134A (CFC Free) refrigeration. Theses include large evaporators and condensers for faster cooling and balanced temperature throughout the cabinet.

## ■ ATTRACTIVE CURVED GLASS AND ELEGANT EURO DESIGN

Curved tempered front glass and minimal frame provide full product visibility to optimize display effects. Its elegant contemporary euro design and luxurious wine colored case will not only enhance any store atmosphere but also will keep product presentation at its best and beautiful.

- CANTILEVERED WIRED SHELVES ADJUSTABLE UP AND DOWN, TILTED
- 304 STAINLESS STEEL FLOOR AND AIR FLOW GRILLE
- **HIGH-DENSITY POLYURETHANE INSULATION**

The entire cabinet structure is foamed-in-place using high density, CFC free polyurethane insulation.

- SELF-CONTAINED SYSTEM, NO PLUMBING REQUIRED
- SIMPLE PLUG-IN INSTALLATION
- EASY ACCESS CONTROL PANEL
- SLIDING REAR DOORS FOR PRODUCT LOADING AND UNLOADING
- HEAVY DUTY, WHITE PE COATED WIRE SHELVES
- SAFETY SHIELDED TOP FLUORESCENT LIGHT LAMP
- EASY TO CONTROL TEMPERATURE AND LIGHT SWITCH
- REAR ACCESS OF COMPRESSOR COMPARTMENT FOR QUICK AND EASY SERVICE
- REFRIGERATED DELI CASE HOLDS AVG. 36°F ~ 42°F FOR FRESHER DELI PRODUCTS

#### ■ RECOMMENDED OPERATING CONDITIONS

TCDD models are designed to operate in environments where temperature & humidity do not exceed 75°F and 55% relative humidity.









Model	CU./FT.	# of Shelves	НР	AMPS	Crated Weight (lbs.)	L x D x H (inches)
TCDD-48-2-L	9.3	1	1/3	6.1	500	481/2 x 30 x 417/8

(unit: inch)

# Direct Cooling Type Cases


### Model: TCDD-48-2-L

ELECTRICAL DATA				
Voltage	115/60/1			
Plug Type	① NEMA-5-15P			
Full Load Amperes	6.1			
Compressor HP	1/3			
Refrigerant	R-134A			
DIMENSIONAL DATA				
Net Capacity cu. ft.	9.3			
Ext. Length Overall in.	48 <sub>1/2</sub> (1232mm)			
Ext. Depth Overall in.	30 (762mm)			
Ext. Height Overall in.	417/8 (1063mm)			
Int. Length Overall in.	451/4 (1148mm)			
Int. Depth Overall in.	245/8 (625mm)			
Int. Height Overall in.	153/4 (399mm)			
Gross Weight lbs.	500			
Net Weight lbs.	421			
# of Shelves	1			
Self Size	441/4 x 173/4			


Design and specifications subject to change without notice. Actual shipping weight may differ due to extra packing materials for product protection.

## ■ WARRANTY: 2 Years Parts and Labor Warranty Additional 3 Years Warranty on Compressor

### **PLAN VIEW**



**FRONT VIEW** 



**SIDE VIEW** 


Ver.201301











■ **Turbo Air**: 800-627-0032 ■ **GK**: 800-500-3519







