

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project :		
Model # :		
Item #:	Qty:	
Available W/H :		
Approval :		

## Milk Coolers

Milk Coolers Super Deluxe Series

Model: TMKC-58D

3 YEAR PARTS & LABOR WARRANTY





### \_\_FEATURES / BENEFITS \_\_\_

### **■ EFFICIENT REFRIGERATION SYSTEM**

Turbo Air's milk coolers are designed with oversized and balanced (CFC Free R-134A) refrigeration systems. It also includes efficient evaporators and condensers for faster cooling and greater efficiency, which result in saving ownership costs. Forced-air refrigeration system keep milk cold after a prolonged period of time, allowing it to be fresh and cold.

■ EXTERIOR DIGITAL TERMOMETER STANDARD FOR EASY VISIBILITY

Exterior digital temperature display allows easy reading, precise, and constant temperature. This level of precision allows milk to remain fresh and safe over an extended period of time.

- STURDY AND CLEAN, DURABLE CABINET CONSTRUCTION Exterior is stainless steel or white coated steel with stainless steel door. Interior is comprised of stainless steel.
- HIGH-DENSITY POLYURETHANE INSULATION

  The entire cabinet construction is foamed-in-place using high density, environmental friendly CFC free polyurethane insulation.
- CONVENIENT BOTTOM FLOOR DRAIN STANDARD WITH HOSE ADAPTER

Floor drain is located in the rear on the right hand side for easy clean out. The hose adapter allows for convenient connecting to drain hose.

- HEAVY DUTY FLOOR RACKS STANDARD
- Door Support Bumpers Standard
- STAINLESS STEEL SELF-SERVICE DOORS HAVE DROP FRONT FEATURE AND HOLD-OPEN FLIP-UP TOP LID
- REFRIGERATOR HOLDS 33°F ~ 38°F FOR THE BEST IN MILK PRESERVATION
- 4" SWIVEL CASTERS STANDARD FOR EASY MOVEMENT, TWO WITH BRAKES TO LOCK THE UNIT IN PLACE
- SELF-CONTAINED SYSTEM
- CORNER BUMPERS AVAILABLE AS OPTIONAL
- DUAL SIDED FOR CONVENIENT ACCESS

Dual sided model offers convenient and efficient access to refrigerated products from both sides of the unit. Dual access milk cooler provides easy stocking and maximum serving possibility.

#### ■ Door Lock Standard for Added Safety





Model	# of Doors	# of Floor Rack	CU./FT.	Crate Capacity (13 x 13 x 11)	НР	AMPS	Crated Weight (lbs.)	L x D*x H † (inches)
TMKC-58D-**	4	3	24.5	16	1/2	7.0	376~403	58 x 327/8 x 415/8

(unit: inch)

## Milk Coolers

## Model: TMKC-58D-\*\*

ELECTRICAL DATA					
Voltage	115/60/1				
Plug Type	NEMA-5-15P				
Full Load Amperes	7.0				
Compressor HP	1/2				
Cord Length ft.	9				
Refrigerant	R134a				
DIMENSIONAL DATA					
Net capacity cu.ft	24.50				
Ext. Length Overall in.	58 (1475mm)				
Ext. Depth Overall in.*	327/8 (836mm)				
Ext. Height Overall in.†	415/8 (1056mm)				
# of Doors	4				
Crate Capacity (13"x13"x11")	16				

Design and specifications subject to change without notice.


Actual shipping weight may differ due to extra packing materials for product protection.

# ■ WARRANTY: 3 Year Parts and Labor Warranty Additional 2 Year Warranty on Compressor


#### \*\* Product number

Model	Gloss Weight (lbs.)	EXTERIOR	INTERIOR
TMKC-58D-WA	383	White Vinyl & Stainless Steel	Aluminum
TMKC-58D-WS	403	White Vinyl & Stainless Steel	Stainless Steel
TMKC-58D-SA	376	Stainless Steel	Aluminum
TMKC-58D-SS	396	Stainless Steel	Stainless Steel

### **PLAN VIEW**



**PLAN VIEW** 



Ver.201401



■ **Turbo Air**: 800-627-0032 ■ **GK**: 800-500-3519

■ Warranty: 800-381-7770 ■ AC: 888-900-1002











 $<sup>^{\</sup>star}$  Depth does not include 5/8" (15mm) for bumpers.

<sup>†</sup> Height does not include 5" (127mm) casters.