

1250 Victoria St Carson, CA 90746 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project :		
Model #:		
Item #:	Qty:	
Available W/H :		
Approval :		

Sandwich/Salad Unit

Food Prep Tables-Sandwich/Salad Prep Super Deluxe Series

Model: TST-48SD

EXCEPTIONAL 3 YEAR PARTS & LABOR WARRANTY



■ COLD AIR COMPARTMENT

Our innovative "Cold Air Compartment" maintains temperature evenly for each pan to preserve fresh food longer. In addition, the compartment isolates pans from the reach-in area to prevent food spillage.

■ STAINLESS STEEL CABINET CONSTRUCTION

The Turbo Air Super Deluxe model boasts a stainless steel interior and exterior (galvanized steel back & bottom). It guarantees the utmost in cleanliness and long product life. The Super Deluxe can add a touch of style to the most refined setting.

■ CONVENIENT CUTTING BOARD SIDE RAIL

Our cutting board is 91/2" deep and 1/2" thick to provide ample working space, and is made of easy to use and sanitize LDPE (Low Density Polyethylene). The new side rail cutting board bracket makes it easy to secure and remove the cutting board and it accepts different sizes too (max. 1/2" thickness)

■ HOT GAS CONDENSATE SYSTEM

Through Turbo Air's creative innovation, the condensate system surfaces have been specially treated to resist corrosion. This not only increases efficiency without the risk of refrigerant leakage from corrosion, but also prevents the overflow of condensate water.

■ INSULATED PAN COVER

■ HIGH-DENSITY POLYURETHANE INSULATION

The entire cabinet structure and solid doors are foamed-in-place high density, CFC free polyurethane insulation.

■ Efficient Refrigeration System

Turbo Air's solid door refrigerators are designed with oversized and balanced (CFC Free R-134A) refrigeration systems. These include efficient evaporators and condensers for faster cooling and greater efficiency.

■ MAGNETIC DOOR GASKETS

Magnetic door gaskets are of one piece construction, removable without tools for ease of cleaning and replacement.

■ STURDY, CLEAN STAINLESS SHELVING

Shelves are the most important part of cleanliness as they come in direct contact with food. After a while, PVC coated wire shelves may peel, rust and lead to unsanitary conditions. Only the Turbo Air Super Deluxe series uniquely provides stainless shelving.

■ ERGONOMICALLY DESIGNED DOORS

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience. ABS sheet door liners resist water condensation with thermal efficiency.

REFRIGERATOR HOLDS 33°F ~ 39°F FOR THE BEST IN FOOD PRESERVATION















Model	Swing Door	CU./FT.	#of Shelves	#of Pans	HP	AMPS	Crated Weight (lbs.)	L x D*x H† (inches)
TST-48SD	2	12	2	12	1/3	6.5	273	481/4 x 30 x 37

(unit: inch)

Sandwich/Salad Unit

Model: TST-48SD

ELECTRICAL DATA						
Voltage	115/60/1					
Plug Type	① NEMA-5-15P					
Full Load Amperes	6.5					
Compressor HP	1/3					
Feed Wires with Ground	3					
Cord Length ft.	9					
Refrigerant	R-134A					
DIMENSIONAL DATA						
Ext. Length Overall in.	481/4 (1225mm)					
Ext. Depth Overall in.*	30 (762mm)					
Ext. Height Overall in.†	37 (940mm)					
# of Doors	2					
# of Shelves	2					
# of Pans	12					
# of Hood	1					
Net Capacity cu. ft.	12					
Gross Weight lbs.	273					
Net Weight lbs.	243					

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

Exceptional 3 Year Parts and Labor Warranty Additional 2 Year Warranty on Compressor

- SELF-CONTAINED SYSTEM
- 4" DIA. SWIVEL CASTERS
- STANDARD 1/6 SIZE, 4" DEEP CONDIMENT PANS INCLUDED
- 91/4" DEEP, 1/2" THICK CUTTING BOARD INCLUDED
- 2.5" DIA. CASTERS AVAILABLE (OPTIONAL)

■ OPTIONAL ACCESSORIES:

☐ 2.5" Diameter casters


5" Diameter casters


☐ 6" ABS plastic legs

☐ Additional stainless steel shelves

☐ Stainless steel double over-shelf

PLAN VIEW





Ver 201301















■ **Turbo Air**: 800-627-0032 ■ **GK**: 800-500-3519

■ Warranty: 800-381-7770 ■ AC: 888-900-1002











^{*} Depth does not include 1" for rear spacers.

[†] Height does not include 5-7/8" for caster height.