

Carson, CA 90746 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project :	
Model #:	
Item #:	Qty:
Available W/H :	
Approval :	

Undercounter Freezer-Drawers

Undercounters Super Deluxe Series

Model: TUF-28SD-D2

EXCEPTIONAL 3 YEAR PARTS & LABOR WARRANTY



___FEATURES / BENEFITS =__

■ STAINLESS STEEL CABINET CONSTRUCTION

The Turbo Air Super Deluxe model boasts a stainless steel interior and exterior (galvanized steel back & bottom). It guarantees the utmost in cleanliness and long product life. The Super Deluxe can add a touch of style to the most refined setting.

- DURABLE STAINLESS STEEL DRAWERS Drawers are easy to clean and assemble.
- HOT GAS CONDENSATE SYSTEM

Through Turbo Air's creative innovation, the condensate system surfaces have been specially treated to resist corrosion. This not only increases efficiency without the risk of refrigerant leakage from corrosion, but also prevents the overflow of condensate water.

■ HIGH-DENSITY POLYURETHANE INSULATION The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

■ EFFICIENT REFRIGERATION SYSTEM

Turbo Air's solid door freezers are designed with oversized and balanced (CFC Free R-404A) refrigeration systems. These include efficient evaporators and condensers for faster freezing and greater efficiency.

■ ERGONOMICALLY DESIGNED DOORS & DRAWERS

Customers' fatigue fades away with easy door grip and drawers that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience. ABS sheet door liners resist water condensation with thermal efficiency.

■ MAGNETIC DOOR GASKETS

Magnetic door and drawer gaskets are of one piece construction, removable without tools for ease of cleaning and replacement.

■ FREEZER HOLDS -5°F ~ -10°F FOR THE BEST IN FROZEN FOOD PRESERVATION











Model	Swing Door	Drawers	CU./FT.	#of Shelves	HP	AMPS	Crated Weight (lbs.)	L x D*x H [†] (inches)
TUF-28SD-D2	-	2	7		1/3	5.3	169	271/2 x 30 x 305/8

(unit: inch)

Model: TUF-28SD-D2

ELECTRICAL DATA					
Voltage	115/60/1				
Plug Type					
Full Load Amperes	5.3				
Compressor HP	1/3				
Cord Length ft.	9				
Refrigerant	R-404A				
DIMENSIONAL DATA					
Net Capacity cu. ft.	7				
Ext. Length Overall in.	271/2 (699mm)				
Ext. Depth Overall in.*	30 (762mm)				
Ext. Height Overall in.†	305/8 (777mm)				
# of Doors					
# of Shelves	-				
Gross Weight lbs.	169				
Net Weight lbs.	152				

Design and specifications subject to change without notice.


Actual shipping weight may differ due to extra packing materials for product protection.

- WARRANTY : Exceptional 3 Year Parts and Labor Warranty Additional 2 Year Warranty on Compressor
- SELF-CONTAINED SYSTEM
- 4" SWIVEL CASTERS
- 2.5" DIA. CASTERS AVAILABLE (OPTIONAL)
- LEGS AVAILABLE FOR ALL MODELS (OPTIONAL)


■ OPTIONAL ACCESSORIES:

- ☐ 2.5" Diameter casters
- ☐ 5" Diameter casters
- ☐ 6" ABS plastic legs

PLAN VIEW



PLAN VIEW



SIDE VIEW

Ver.201301







Turbo air













^{*} Depth does not include 1" for rear spacers.

[†] Height does not include 5-7/8" for caster height.