

1250 Victoria St Carson, CA 90746 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

| Project : | | |
|-----------------|------|--|
| Model #: | | |
| Item #: | Qty: | |
| Available W/H : | | |
| Approval : | | |

Undercounter Refrigerator

Undercounters Super Deluxe Series

Model: TUR-36SD

EXCEPTIONAL 3 YEAR PARTS & LABOR WARRANTY



___FEATURES / BENEFITS ___

■ STAINLESS STEEL CABINET CONSTRUCTION

The Turbo Air Super Deluxe model boasts a stainless steel interior and exterior (galvanized steel back & bottom). It guarantees the utmost in cleanliness and long product life. The Super Deluxe can add a touch of style to the most refined setting.

■ STURDY, CLEAN STAINLESS SHELVING

Shelves are the most important part of cleanliness as they come in direct contact with food. After a while, PVC coated wire shelves may peel, rust and lead to unsanitary conditions. Only the Turbo Air Super Deluxe series uniquely provides stainless shelving.

■ HOT GAS CONDENSATE SYSTEM

Through Turbo Air's creative innovation, the condensate system surfaces have been specially treated to resist corrosion. This not only increases efficiency without the risk of refrigerant leakage from corrosion, but also prevents the overflow of condensate water.

■ EFFICIENT REFRIGERATION SYSTEM

Turbo Air's solid door refrigerators are designed with oversized and balanced (CFC Free R-134A) refrigeration systems. These include efficient evaporators and condensers for faster cooling and greater efficiency.

■ HIGH-DENSITY POLYURETHANE INSULATION

The entire cabinet structure and solid doors are foamed-inplace using high density, CFC free polyurethane insulation.

■ ERGONOMICALLY DESIGNED DOORS

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience. ABS sheet door liners resist water condensation with thermal efficiency.

■ MAGNETIC DOOR GASKETS

Magnetic door gaskets are of one piece construction, removable without tools for ease of cleaning and replacement.

■ REFRIGERATOR HOLDS 33°F ~ 38°F FOR THE BEST IN FOOD PRESERVATION











ENERGY STAR® Qualified

| Model | Swing Door | CU./FT. | #of Shelves | НР | AMPS | Crated Weight (lbs.) | L x D*x H† (inches) |
|----------|---------------|---------|----------------|-----|------|-------------------------|---------------------|
| TUR-36SD | 2 | 11 | 2 | 1/3 | 6.6 | 187 | 361/4 x 30 x 305/8 |

Model: TUR-36SD

| ELECTRICAL DATA | | | | | | |
|--------------------------|---------------|--|--|--|--|--|
| Voltage | 115/60/1 | | | | | |
| Plug Type | | | | | | |
| Full Load Amperes | 6.6 | | | | | |
| Compressor HP | 1/3 | | | | | |
| Cord Length ft. | 9 | | | | | |
| Refrigerant | R-134A | | | | | |
| | | | | | | |
| DIMENSIONAL DATA | | | | | | |
| Net Capacity cu. ft. | 11 | | | | | |
| Ext. Length Overall in. | 361/4 (921mm) | | | | | |
| Ext. Depth Overall in.* | 30 (762mm) | | | | | |
| Ext. Height Overall in.† | 305/8 (777mm) | | | | | |
| # of Doors | 2 | | | | | |
| # of Shelves | 2 | | | | | |
| Gross Weight lbs. | 187 | | | | | |
| Net Weight lbs. | 167 | | | | | |

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.


■ WARRANTY : Exceptional 3 Year Parts and Labor Warranty Additional 2 Year Warranty on Compressor


- SELF-CONTAINED SYSTEM
- 4" SWIVEL CASTERS

■ OPTIONAL ACCESSORIES:

- ☐ 2.5" Diameter casters
- ☐ 5" Diameter casters
- ☐ 6" ABS plastic legs
- ☐ Additional stainless steel shelves
- ☐ Stainless steel double over-shelf

PLAN VIEW (unit: inch)





SIDE VIEW

Ver.201301









ENERGY STAR® Qualified

■ **Turbo Air**: 800-627-0032 ■ **GK**: 800-500-3519

■ Warranty: 800-381-7770 ■ AC: 888-900-1002









^{*}Depth does not include 1" for rear spacers.

[†] Height does not include 5-7/8" for caster height.