Project

Item Number

Quantity

Value Series Slicer

Univex Corporation



Features:

- Medium Duty, Moderate Volume Slicer
- 10" Precision slicing German hollow ground blade
- Unique drip tray fence redirects liquids away from controls and operator towards distinctive concaved base casting for easy cleaning
- Ergonomic comfort design operation
- Powerful 1/2 hp motor standard
- Adjustable slice thickness from 0 to 7/8"
- Capable of slicing a moderate amount cheese
- Easily removable sharpener for cleaning
- Quick and simple disassembly of carriage and feed grip for easy and thorough cleaning
- Sanitary polished & anodized aluminum construction
- · Carriage easily detaches for ease of washing and sanitizing.

7510 **Value Series** Manual Slicer

7510: 1/2HP Value series slicer





Certified by NSF International to Meet and Exceed the NSF/ ANSI 2010 standards

10 " Precision slicing German hollow ground blade Unique smooth curve transitions to redirect liquids away from controls and operator Carriage detaches for easy washing/ sanitization Powerful 1/2 hp motor standard

- Heavy duty 3-1/2 lb gravity feed grip
- Permanantly mounted protective edge guard for operator safety

Optional Accessories:

- · Heavy Duty Clear Plastic Cover
- Stainless Steel Vegetable Chute
- · Sturdy Stainless Steel Stand

Warranty:

• 1 year, on-site parts and labor

Warranty Details

The 7510 carries a 1 year, on-site parts and labor warranty against any flaws in materials and workmanship. This period begins on the date of the purchase and, provided the unit is used in accordance with our instructions, is in full effect for 1 year from that date. Any work performed under this warranty must be performed between the hours of 8am and 5pm Monday through Friday. Univex will not pay for overtime charges for work performed other then during normal business hours. Damage incurred in transit or from installation error, accident, alteration or misuse is not covered. Univex shall not be liable for any consequential compensatory, incidental, or special damages. Contact the Univex service department for any warranty claims


> **Univex Corporation** www.Univexcorp.com

3 Old Rockingham Rd Salem, NH 03079 United States of America Telephone (800) 258-6358 Intl Tel. (603) 8936191 Fax (800) 356-5614 Intl Fax (603) 8931249



7510 Value Slicer

7510



Width 21" (53.34cm)

B: Depth 30" (76.2cm)

Height 21" (53.34cm)

Auto or Manual	Motor	Volts	Hz	Amps	Drive Type	Blade RPM	Cheese slicing	Blade Diameter	Max Slice	Produ Rec (Rectangle)	uct Cutting Capac S (Square)	ity R (Round)
Manual	1680 RPM 1/2 HP (.37kW)	115V 220V	60 50-60	4amp 2.5amp	Belt Driven	345	Medium Volume	10" (25.4cm)	.875" (22.2mm)	9" x 5" (22.8cm x 12.7cm)	5" x 5" (12.7cm x 12.7cm)	7" (17.8cm)

Carriage stroke: 10" (25.4cm) Controls: Manual slice thickness knob, push button on/off, Attached blade sharpener

NSF International certified ANSI/ NSF 8

This slicer is certified by NSF International to meet and exceed the NSF 8 standard. Here is a list of highlighted features that are standard on our entire ANSI/ NSF8 certified slicer line:

- Improved liquid and food particle diversion from all control surfaces
- Improved seals and gaskets for longer life and greater sanitary standards
- Clear and easy to follow cleaning and sanitizing instructions

Shipping Information:

 Freight Class:
 85

 Net Weight:
 79lbs (35.8kg)

 Shipping Weight:
 86.9lbs (39.4kg)

Shipping Box Dimensions:

 Height:
 22.8" (580mm)

 Width:
 20.5" (520mm)

 Length:
 27.1" (690mm)









Univex Corporation www.Univexcorp.com

3 Old Rockingham Rd Salem, NH 03079 United States of America Telephone (800) 258-6358 Intl Tel. (603) 8936191 Fax (800) 356-5614 Intl Fax (603) 8931249